





LED LARGE ADJUSTABLE WALL PACK

LAW74 SERIES



74W



PRODUCT DESCRIPTION:

With flexible installation features and architectural-grade design, LED Large Adjustable Wall Packs offer discreet, but powerful lighting for outdoor locations. The wall packs are constructed with a fixture head that pivots up to 120 degrees, to precisely aim light while minimizing glare and backlight. Wall packs are issued unscrewed, so they are ready to install right out of the box.

FEATURES:

- Fixture head pivots fully up to 120° from mounting plane
- Efficacy of 85 lm/W translates to as much as 70% energy savings over HID incumbents
- 70 CRI min
- Universal 120-277V power supply
- Power Factor > 0.9; THD < 25%
- 120,000-hour L70 lifetime, TM-21 standards @ 25°C
- 10kV surge protection standard

CONTROLS:

120VAC/208-277VAC Photocontrol: Voltage-specific photocontrols power the fixture when light levels reach 20 lux or below, and turn it off at 30 lux or higher. Operating temperature of -30°F-120°F. Photocell mounted externally.

CONSTRUCTION:

- Die-cast housing, durable powder coat finish
- Spirit level makes for an easy installation

POLE MOUNTING:


- For mounting to 4" square poles, please see accessory chart

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: LAW74U50PC27BSS

LAW74	U	50		B	SS
FAMILY	VOLTAGE	CCT	CONTROL	FINISH	SURGE SUPPRESSION
LAW74= 74W, 250W Metal Halide equivalent	U= 120-277V	50= 5000K	(OMIT)= None, std PC12= 120V Photocontrol PC27= 277V Photocontrol	B= Bronze, std	SS= 10kV surge suppressor, std.

ACCESSORY

ORDER CODE	MODEL NUMBER	DESCRIPTION	ACCESSORIES IMAGE
74904	LAWPA	Galvanized steel adapter plate with 2AF Volara crosslinked polyethylene gaskets for mounting luminaire to 4" pole	

SPECIFICATIONS:

		LAW74U50BSS	LAW74U50BPC12BSS	LAW74U50BPC27BSS
ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Lumens Delivered (lm)	6230		
	Efficacy (lm/W)	85		
	CCT	5000K		
	Lumen Maintenance (L70)	> 120,000 hours		
	Color Rendering Index (CRI)	70		
ELECTRICAL	Input Power (W)	74		
	Power Factor	> 0.9		
	Input Voltage (V)	120-277, 50/60Hz	100-120V, 50/60Hz	208-277V, 50/60Hz
	Surge Supression	10kV		
PHYSICAL	Lens	Sealed borosilicate glass lens		
	Housing	Aluminum		
	Mounting	Gasketed back plate can be mounted to recessed outlet box or direct to surface		
	Operating Temperature	-22°F-104°F		
	Weight	9.80 lbs		
APPLICATION	Certification	RoHS, UL, FCC, LM-79, LM-80, TM-21, DLC		
	Environment	IP66		
	Humidity	20% - 85% RH, non condensing		
	Warranty	5 Years		

ORDERING*:

ORDER CODE	MODEL	OPTIONS	EFFICACY (lm/w)	OUTPUT (LUMENS)	NOMINAL POWER (WATTS)	CCT	FINISH
74522	LAW74U50BSS	None	85	6230	74	5000K	Bronze
74580	LAW74U50PC12BSS	120V Photocontrol					
74581	LAW74U50PC27BSS	277V Photocontrol					

*Please contact your MaxLite representative to order products that don't have order codes listed here.