CRC

SAFETY DATA SHEET

1. Identification

Product identifier Screwloose® Super Penetrant

Other means of identification

Product code 03059

Recommended use General purpose penetrant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc. Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1
Hazardous to the aquatic environment, acute Category 2

Hazardous to the aquatic environment, acute hazard

OSHA defined hazards Not classified.

Label elements

Environmental hazards



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause

drowsiness or dizziness. Toxic to aquatic life.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Avoid breathing gas/mist/vapor. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves and eye/face protection. Wash hands thoroughly after handling. Avoid release to

the environment.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical attention.

Material name: Screwloose® Super Penetrant 1739 Version #: 01 Issue date: 10-07-2013

Storage

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

40.85% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Light		64742-47-8	50 - 60
Stoddard Solvent		8052-41-3	20 - 30
Distillates (petroleum), Solvent-refined Heavy Paraffinic		64741-88-4	5 - 10
Dipropylene glycol monopropyl ether (dpmp)		29911-27-1	3 - 5
Carbon dioxide		124-38-9	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause drowsiness o dizziness. May cause redness and pain.
Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Alcohol resistant foam. Water. Water spray. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
General fire hazards	Extremely flammable aerosol.

Material name: Screwloose® Super Penetrant 1739 Version #: 01 Issue date: 10-07-2013

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Form Components Type Value PEL 9000 mg/m3 Carbon dioxide (CAS 124-38-9) 5000 ppm Distillates (petroleum), PFI 5 mg/m3 Mist. Solvent-refined Heavy Paraffinic (CAS 64741-88-4) 2000 mg/m3 500 ppm Stoddard Solvent (CAS **PEL** 2900 mg/m3 8052-41-3) 500 ppm **US. ACGIH Threshold Limit Values** Components Value **Form** Type Carbon dioxide (CAS STEL 30000 ppm 124-38-9) **TWA** 5000 ppm

US. ACGIH Threshold Limit \ Components	values Type	Value	Form
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	TWA	5 mg/m3	Inhalable fraction.
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	100 mg/m3	
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	STEL	10 mg/m3	Mist.
,	TWA	5 mg/m3	Mist.
Stoddard Solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
,	TWA	350 mg/m3	
ogical limit values	No biological exposure limits noted for	or the ingredient(s).	

Biological limit values

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves: Nitrile. Neoprene. Other Wear appropriate chemical resistant clothing.

Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to Respiratory protection

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Aerosol.

Color Clear. Light amber.

Odor Petroleum. Not available. Odor threshold pН Not available.

-121 °F (-85 °C) estimated Melting point/freezing point Initial boiling point and boiling 315 °F (157.2 °C) estimated

range

141 °F (60.6 °C) Tag Closed Cup

Slow **Evaporation rate**

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

0.6 % estimated

Flash point

Flammability limit - upper

(%)

Vapor pressure

oer 6 % estimated

1069.1 hPa estimated

Vapor density> 4 (air = 1)Relative density0.81 estimatedSolubility (water)Not available.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperature 401 °F (205 °C) estimated

Decomposition temperatureNot available.Viscosity (kinematic)Not available.Percent volatile98.3 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion May be fatal if swallowed and enters airways.

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Product Species Test Results
Screwloose® Super Penetrant

1003C@ Oup

AcuteDermal

LD50 Rabbit 3127.7244 mg/kg estimated

Oral

LD50 Rat 7008.563 mg/kg estimated

1093.5911 ml/kg estimated

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Narcotic effects.

Material name: Screwloose® Super Penetrant 1739 Version #: 01 Issue date: 10-07-2013

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

toxicity	Toxic to a	Toxic to aquatic life.	
Product		Species	Test Results
Screwloose® Super P	enetrant		
Acute			
Crustacea	EC50	Daphnia	2034.588 mg/l, 48 hours estimated
Fish	LC50	Fish	3.7233 mg/l, 96 hours estimated
Components		Species	Test Results
Dipropylene glycol mo	nopropyl ether (dpi	mp) (CAS 29911-27-1)	
Acute			
Other	EC50	Pseudokirchnerella subcapitata	> 1000 mg/l, 96 hours
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	> 100 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	> 100 mg/l, 96 hours
Distillates (petroleum)	, Hydrotreated Ligh	t (CAS 64742-47-8)	
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	2.2 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Dipropylene glycol monopropyl ether (dpmp) 0.87 OECD 107 Stoddard Solvent 3.16 - 7.15

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Empty container can be recycled. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of

contents/container in accordance with local/regional/national regulations.

Hazardous waste code Not regulated.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosol

Transport hazard class(es)

Aerosols, flammable, limited quantity

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN1950 **UN number**

UN proper shipping name Aerosols, flammable, limited quantity

Transport hazard class(es)

2.1 Class Subsidiary risk

Not applicable. **Packing group**

Environmental hazards No. 10L **FRG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Cargo aircraft only

Other information

Passenger and cargo

aircraft

Allowed. Allowed.

IMDG

UN number UN1950

UN proper shipping name AEROSOLS, LIMITED QUANTITY

Transport hazard class(es)

Class 2 Subsidiary risk

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910,1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Not regulated. Food and Drug

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Section 311/312** Delayed Hazard - No **Hazard categories** Fire Hazard - Yes

Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely

No hazardous substance

US state regulations

US. New Jersey RTK - Substances: Listed substance

Carbon dioxide (CAS 124-38-9) Stoddard Solvent (CAS 8052-41-3)

US. Massachusetts RTK - Substance List

Carbon dioxide (CAS 124-38-9) Stoddard Solvent (CAS 8052-41-3)

US. Pennsylvania RTK - Hazardous Substances

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Stoddard Solvent (CAS 8052-41-3)

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

FPA

VOC content (40 CFR

51.100(s))

98.3 %

51.100(5))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

Inventory name

State

Consumer products This product is regulated as a Penetrant. This product is compliant for use in all 50 states.

 VOC content (CA)
 24.4 %

 VOC content (OTC)
 24.4 %

International Inventories

Country(s) or region

odulitiy(3) of region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date10-07-2013Prepared byAllison Cho

Version # 01

Further information CRC # 575H

HMIS® ratings Health: 2
Flammability: 4
Physical hazard:

Physical hazard: 0 Personal protection: B

NFPA ratings Health: 2

Flammability: 4 Instability: 0

On inventory (yes/no)*

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.

Material name: Screwloose® Super Penetrant 1739 Version #: 01 Issue date: 10-07-2013