# CRC.

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Lectra-Motive® Electric Parts Cleaner

Other means of identification

Product code 05019

Recommended use Energized electrical cleaner

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

**Telephone** 

**General Information** 215-674-4300 **Technical** 800-521-3168

**Assistance** 

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

**Environmental hazards** Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause drowsiness or dizziness. May cause cancer. Toxic to aquatic life

with long lasting effects.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face

Category 2

protection. Avoid release to the environment.

Response If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off

contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned:

Get medical attention. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: Lectra-Motive® Electric Parts Cleaner
05019 Version #: 03 Revision date: 09-17-2014 Issue date: 01-14-2014

#### Supplemental information

When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

# 3. Composition/information on ingredients

RΛ	ıv	TI I	res

Chemical name	Common name and synonyms	CAS number	%
Tetrachloroethylene	Perchloroethylene	127-18-4	90 - 100

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical Skin contact

advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause Most important redness and pain.

symptoms/effects, acute and

delayed Indication of immediate medical attention and special

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Because rapid absorption may occur through lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. If layage is performed, suggest endotracheal and/or esophageal control. If burn is present, treat as any thermal burn, after decontamination. Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary. No specific antidote.

**General information** 

treatment needed

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

corrosive gases such as hydrogen chloride and possibly phosgene.

Containers should be cooled with water to prevent vapor pressure build up.

No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### **Environmental precautions**

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

# 7. Handling and storage

## Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

# Occupational exposure limits

## US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Туре	Value	
Tetrachloroethylene (CAS 127-18-4)	Ceiling	200 ppm	
,	TWA	100 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Tetrachloroethylene (CAS 127-18-4)	STEL	100 ppm	
,	TWA	25 ppm	

#### **Biological limit values**

# **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Tetrachloroethylene (CAS 127-18-4)	0.5 mg/l	Tetrachloroethy lene	Blood	*
	3 ppm	Tetrachloroethy lene	End-exhaled air	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

## US - Minnesota Haz Subs: Skin designation applies

Tetrachloroethylene (CAS 127-18-4)

Skin designation applies.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Viton®. Polyvinyl alcohol (PVA). Ethyl vinyl alcohol laminate

(EVAL).

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

SDS US

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. **Form** Liquid. Color Colorless. Odor Irritating. **Odor threshold** 50 ppm

Not available. pН

-8.1 °F (-22.3 °C) estimated Melting point/freezing point Initial boiling point and boiling 250.3 °F (121.3 °C) estimated

range

None (Tag Closed Cup) Flash point

**Evaporation rate** Very fast. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Not available. Flammability limit - lower

(%) Flammability limit - upper

Not available.

Vapor pressure 13 mm Hg (68 °F (20 °C))

Vapor density 5.76 (air = 1)

1.62 Relative density

0.02 % (77 °F (25 °C)) Solubility (water)

Partition coefficient 2.9

(n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Viscosity (kinematic) Not available. Percent volatile 100 % estimated

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** 

Possibility of hazardous

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Welding. When exposed to extreme heat or hot surfaces,

vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and

possibly phosgene.

Incompatible materials Strong oxidizing agents. Metals. Powdered metal. Amines. Strong bases.

**Hazardous decomposition** 

products

Hydrogen chloride. Trace amounts of chlorine and phosgene.

## 11. Toxicological information

## Information on likely routes of exposure

Single dose oral toxicity is considered to be extremely low. Swallowing large amounts may cause Ingestion

injury if aspirated into the lungs. This may be rapidly absorbed through the lungs and result in

injury to other body systems.

Inhalation Headache. Nausea, vomiting. Vapors have a narcotic effect and may cause headache, fatigue,

dizziness and nausea. Prolonged inhalation may be harmful. May cause damage to organs by

inhalation.

Skin contact Causes skin irritation.

Direct contact with eyes may cause temporary irritation. Eye contact

Material name: Lectra-Motive® Electric Parts Cleaner

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache,

dizziness, tiredness, nausea and vomiting.

## Information on toxicological effects

Narcotic effects. Acute toxicity

**Product Species Test Results** 

Lectra-Motive® Electric Parts Cleaner

**Acute** Dermal

LD50 Rabbit 3228 mg/kg estimated

Inhalation

LC50 Rat > 20 mg/l, 4 hours

Oral

LD50 Rat 2629 mg/kg estimated

Causes skin irritation. Skin corrosion/irritation

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization Not available.

Skin sensitization Based on available data, the classification criteria are not met. Frequent or prolonged contact may

defat and dry the skin, leading to discomfort and dermatitis.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Tetrachloroethylene (CAS 127-18-4) 2A Probably carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Tetrachloroethylene (CAS 127-18-4) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Narcotic effects. May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** May be an aspiration hazard. Swallowing large amounts may cause injury if aspirated into the

lungs. This may be rapidly absorbed through the lungs and result in injury to other body systems.

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May cause **Chronic effects** 

damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Product		Species	Test Results
Lectra-Motive® Elect	ric Parts Cleaner		
Aquatic			
Fish	LC50	Fish	18.7329 mg/l, 96 hours estimated
Components		Species	Test Results
Tetrachloroethylene (	(CAS 127-18-4)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4.73 - 5.27 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Material name: Lectra-Motive® Electric Parts Cleaner

05019 Version #: 03 Revision date: 09-17-2014 Issue date: 01-14-2014

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Partition coefficient n-octanol / water (log Kow)

Lectra-Motive® Electric Parts Cleaner 2.88 Tetrachloroethylene 2.88

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products This material and its container must be disposed of as hazardous waste. Consult authorities before disposal. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable

regulations.

D039: Waste Tetrachloroethylene Hazardous waste code

F001: Waste Tetrachloroethylene - Spent halogenated solvent used in degreasing

F002: Waste Tetrachloroethylene - Spent halogenated solvent

**US RCRA Hazardous Waste U List: Reference** 

U210 Tetrachloroethylene (CAS 127-18-4)

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

DOT

UN1897 **UN number** 

UN proper shipping name Transport hazard class(es) Tetrachloroethylene (RQ = 100 lbs), Limited Quantity

6.1(PGIII) Class

Subsidiary risk Label(s) 6.1 Packing group Ш

**Environmental hazards** 

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IB3, N36, T4, TP1 **Special provisions** 

153 Packaging exceptions 203 Packaging non bulk Packaging bulk 241

IATA

UN1897 **UN** number

**UN** proper shipping name

Tetrachloroethylene

Transport hazard class(es)

Class 6.1(PGIII)

Subsidiary risk Packing group Ш **Environmental hazards** Yes **ERG Code** 61

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed.

aircraft

Cargo aircraft only Allowed.

**IMDG** 

**UN** number UN1897

**UN proper shipping name** 

TETRACHLOROETHYLENE, LIMITED QUANTITY

Transport hazard class(es)

Class 6.1(PGIII)

Subsidiary risk Ш Packing group

**Environmental hazards** 

Marine pollutant Yes

Material name: Lectra-Motive® Electric Parts Cleaner 05019 Version #: 03 Revision date: 09-17-2014 Issue date: 01-14-2014 EmS F-A, S-A

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

General information DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

## SARA 304 Emergency release notification

Not regulated.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

# US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Tetrachloroethylene (CAS 127-18-4)

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Tetrachloroethylene (CAS 127-18-4)

## **CERCLA Hazardous Substances: Reportable quantity**

Tetrachloroethylene (CAS 127-18-4)

100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Tetrachloroethylene (CAS 127-18-4)

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely No hazardous substance

## **US state regulations**

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

## US. New Jersey Worker and Community Right-to-Know Act

Tetrachloroethylene (CAS 127-18-4)

#### **US. Massachusetts RTK - Substance List**

Tetrachloroethylene (CAS 127-18-4)

## US. Pennsylvania Worker and Community Right-to-Know Law

Tetrachloroethylene (CAS 127-18-4)

#### **US. Rhode Island RTK**

Tetrachloroethylene (CAS 127-18-4)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

## US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Tetrachloroethylene (CAS 127-18-4) Listed: April 1, 1988

Material name: Lectra-Motive® Electric Parts Cleaner

05019 Version #: 03 Revision date: 09-17-2014 Issue date: 01-14-2014

# Volatile organic compounds (VOC) regulations

**EPA** 

VOC content (40 CFR 0 %

51.100(s))

Consumer products

(40 CFR 59, Subpt. C)

Not regulated

State

**Consumer products** 

This product is regulated as an Energized Electrical Cleaner for the following states: California, Connecticut, Delaware, District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and Virginia. It is for energized equipment use only. It is not to be used for motorized vehicle maintenance or their parts. This product is compliant for use in all 50 states.

VOC content (CA) 0 % VOC content (OTC) 0 %

#### **International Inventories**

**Philippines** 

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Philippine Inventory of Chemicals and Chemical Substances (PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date01-14-2014Revision date09-17-2014Prepared byAllison Cho

Version # 03

Further information CRC # 491G
HMIS® ratings Health: 2\*
Flammability: 0

Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0 Instability: 0

NFPA ratings



SDS US

Yes

Yes

#### **Disclaimer**

CRC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.