



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE PM-500

"This product is certified OU Kosher Pareve"  
"This product is Halal certified"

\*NSF International H-1 Registered  
NSF ISO21469 Certification

## DESCRIPTION

LUBRIPLATE PM-500 contains emulsifying agents, which wet the lubricated surfaces and provide an oiliness film for moving parts.

## APPLICATIONS

LUBRIPLATE PM-500 has been and is being used, very successfully, in pear machines and other applications where an NSF International H-1 registered\* white oil is required. LUBRIPLATE PM-500 is specially suited for water conditions existing in the machinery operation.

## ADVANTAGES

⇒ USP Grade White Oil used in these formulations.

*"LUBRIPLATE PM-500 contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".*

*\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

*Manufactured with ingredients that comply with FDA 21 CFR 178.3570.*

## STORAGE RECOMMENDATIONS

1. Products should be stored between 40°F-120°F.
2. Products should be stored in a dry covered environment.
3. Products should not be stored in warm, direct sunlight.
4. improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	530
Viscosity cSt @ 40°C	ASTM D-445	101
Viscosity SUS @ 210°F	ASTM D-2161	63
Viscosity cSt @ 100°C	ASTM D-445	10.8
API Gravity	ASTM D-287	28.7
Color	ASTM D-1500	0.0
Flash Point	ASTM D-92	420°F/216°C
Fire Point	ASTM D-92	485°F/252°C
Pour Point	ASTM D-97	-5°F/-21°C
SAE Viscosity		30
ISO Viscosity		100

## PACKAGING AVAILABLE

## Part No.

35 lb. Drum  
405 lb. Drum

L0192-035  
L0192-040

**\*NSF International H-1 Registration No.**  
(Meets former USDA 1998 Guidelines)

**126122**

