

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).

Date of issue: August 19, 2018 Supersedes: August 10, 2015 Version: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Name:** Sherlock Leak Detector Type II  
**Product Code:** T2  
**Other means of identification:** Type II  
**Synonyms:** None Known

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use:** Leak testing  
Recommended Temperature Range: -65 °F to 160 °F  
Recommended Shelf Life: 2 years from date of manufacture.

**Recommended Use Restrictions:** Other than those identified above.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name:** Winton Products Company Inc.  
**Company Address:** 2500 West Blvd.  
Charlotte, NC, 28236  
United States of America

**Company Telephone Number:** 704-399-5151  
**Company Fax Number:** 704-392-5389  
**Company Email:** [wintonprod@aol.com](mailto:wintonprod@aol.com)  
**Company Website:** <http://www.wintonproducts.com>

#### 1.4. Emergency telephone number

**Emergency number:** CHEMTREC - 1-800-424-9300 (24h)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US, GHS-CA)

Classification of the substance/mixture in accordance with US OSHA Hazard Communication Standard (HCS) (HAZCOM 2012) and Canadian Hazardous Products Regulations (HPR) Workplace Hazardous Materials Information System (WHMIS 2015).

##### Physical Hazards:

None

##### Health Hazards:

Acute Tox. (Oral) – Category 4  
Specific Target Organ Toxicity – Category 2 (Kidneys) (Oral)

##### Environmental Hazards:

Not adopted by OSHA (HAZCOM 2012).

Not adopted by WHMIS 2015.

##### PHNOC (Physical Hazards Not Otherwise Classified): (Canada)

None Known

##### HHNOC (Health Hazards Not Otherwise Classified): (Canada)

None Known

##### HNOC (Hazards Not Otherwise Classified): (USA)

None Known

##### WHMIS Classification:

D2B (WHMIS 1998)

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).

### 2.2. Label elements

#### Hazard pictograms:



GHS07



GHS08

#### Signal Word:

Warning

#### Hazard Statements:

H302 - Harmful if swallowed.

H373 - Causes damage to organs (Kidneys) through prolonged or repeated exposure via ingestion.

#### Precautionary statements:

##### Prevention:

P260 – Do not breathe dust/fume/gas/mist/vapors/spray.

P264 – Wash thoroughly after handling.

P270 – Do not eat, drink or smoke when using this product.

##### Response:

P301+P312 – IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.

P330 – Rinse mouth.

P314 – Get medical advice/attention if you feel unwell.

##### Storage:

No GHS Storage Statements

##### Disposal:

P501: Dispose of contents/container to a suitable disposal site, in accordance with applicable local/regional/national and international regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US/CA)

Not Applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	CAS Number	Concentration (Wt.%)	Hazard Classification
Ethylene glycol	107-21-1	55-65	Acute Tox. Oral 4:H302 STOT SE 2:H373

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### First-aid measures general:

If in doubt, seek medical advice/attention.

#### First-aid measures after inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If respiratory symptoms or other adverse effects develop: Get medical advice/attention. Assist ventilation as required. Always use a barrier or bag-valve mask device. If breathing has stopped, provide artificial respiration. Seek medical attention immediately.

#### First-aid measures after skin contact:

IF ON SKIN: Wash with plenty of water. If irritation or rash occurs: get medical advice/attention.

#### First-aid measures after eye contact:

IF IN EYES: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. If eye irritation occurs and persists: seek medical advice/attention.

#### First-aid measures after ingestion:

IF SWALLOWED: Immediately remove the victim from the source of exposure. Ensure that the patient/victim has an unobstructed airway. Do not induce vomiting. Seek Immediate medical attention. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Adverse Effects Acute/Delayed:

##### Inhalation:

May cause cough, dizziness and headache. Exposure to very high levels of ethylene glycol vapor causes irritation of mucous membranes and the upper respiratory tract. Exposure to ethylene glycol concentrations higher than 80 ppm results in intolerable respiratory discomfort and cough.

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).

<b>Skin Contact:</b>	May cause mild skin irritation. Symptoms include: redness, itching, inflammation and rash.
<b>Eye Contact:</b>	May cause mild eye irritation. Symptoms include: redness, tearing, inflammation, burning and itching. Exposure to liquid ethylene glycol may result in swelling of the eyelid and swelling around the cornea, inflammation of the conjunctiva and iris and conjunctival or corneal injury.
<b>Ingestion:</b>	Harmful if swallowed. Seek immediate medical attention. Contains ethylene glycol. Ethylene glycol is rapidly absorbed after ingestion. Early ethylene glycol intoxication resembles ethanol intoxication. The symptoms of acute exposure to ethylene glycol include: central nervous system depression, intoxication, euphoria, stupor, and respiratory depression. The course of ethylene glycol toxicity is classically divided into three broad overlapping categories of adverse health effects. Stage 1 (the neurological stage) lasts from 30 minutes to 12 hours after ingestion. Stage 2 (the cardiopulmonary stage) occurs between 12 and 24 hours after ingestion. Stage 3 (the renal stage) occurs between 24 and 72 hours after ingestion. Adverse health effects can be delayed significantly by the co-ingestion of alcohol. Nausea and vomiting may occur as a result of gastrointestinal irritation. Severe toxicity may result in coma, loss of reflexes, seizures (uncommon), and irritation of the tissues lining the brain. Kidney (renal) failure can occur 24 to 72 hours after acute ethylene glycol ingestion. Some loss of kidney function may be permanent.
<b>Effects of Chronic Exposure:</b>	Chronic or repeated exposure to ethylene glycol causes kidney damage (via ingestion), irritation of the throat, headache, low backache, loss of consciousness and nystagmus.
<b>Medical Conditions Aggravated by Exposure:</b>	No additional information.

### 4.3. Indication of any immediate medical attention and special treatment needed

If Ingested: Seek immediate medical attention.

#### Notes to Physician

For large ingestions of ethylene glycol, attempt to aspirate stomach (gastric) contents using a nasogastric tube, if it can be done within the first 30 to 60 minutes. In all patient/victims with known or suspected ethylene glycol poisoning, perform blood tests (CBC, blood glucose, serum electrolytes, magnesium, calcium, BUN, creatinine, lactate, ethylene glycol level, and ethanol level), arterial blood gas (ABG) levels and osmolality, and a urinalysis. Repeat these tests as necessary to closely monitor the progression of toxic effects. Contact a medical toxicologist or a regional poison control center for assistance in evaluating the anion and osmolar gaps and to decide whether antidotal therapy, intravenous sodium bicarbonate, or hemodialysis is needed. Antidotes fomepizole or ethanol should be administered intravenously as soon as possible to block the conversion of ethylene glycol to formic acid and prevent acidosis. Fomepizole is preferred as its efficacy and safety have been demonstrated, and its therapeutic dose is more easily maintained. Once the patient/victim has become acidotic, administration of fomepizole or ethanol may not provide much benefit, but they may be administered at the discretion of the physician in charge. Folinic acid (leucovorin) should also be administered intravenously to increase the rate at which formate is metabolized into less toxic chemicals. Haemodialysis is the most effective form of treatment for an acidotic patient/victim and may be used when the blood ethylene glycol level is greater than 50 mg/dL, with severe metabolic or fluid abnormalities despite other therapeutic interventions, or in cases of kidney failure. Caution: Ethanol and fomepizole dosing must be adjusted during haemodialysis. Thiamine and pyridoxine facilitate a more rapid metabolism of ethylene glycol to non-toxic metabolites and should be given as a single dose IV (100 mg daily).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media:</b>	Powder, alcohol-resistant foam, water spray, carbon dioxide.
<b>Unsuitable extinguishing media:</b>	None Known

### 5.2. Special hazards arising from the substance or mixture

<b>Hazardous Combustion products:</b>	Irritating or toxic substances will be emitted upon burning including: Carbon monoxide and Carbon dioxide.
---------------------------------------	--

### 5.3. Advice for firefighters

<b>Firefighting instructions:</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate all non-emergency personnel from area. Irritating or toxic substances will be emitted upon burning including: carbon monoxide and carbon dioxide.
-----------------------------------	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unnecessary personnel. Ventilate area. Wear recommended personal protective equipment (See Section 8). Do not walk through spilled material. Eliminate ignition sources. Avoid contact with skin, eyes and clothing. Do not breathe mist/vapors/gases/spray. Stop leak if able to do so.

### 6.2. Environmental precautions

Prevent entry to drains, sewer and public waters. Notify authorities if liquid enters sewers or public waters.

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).

### 6.3. Methods and material for containment and cleaning up

**For containment:** Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

**Methods for cleaning up:** Wipe up with absorbent material (for example cloth). Thoroughly decontaminate area after spill cleanup.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Precautions for safe handling:** Wear recommended personal protective equipment (See Section 8). Use only with adequate ventilation. Avoid contact with skin, eyes and clothing. Do not ingest. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Provide good ventilation in process areas to prevent formation of vapor.

**Hygiene measures:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Keep only in original container. Store in a dry, well-ventilated place. Keep cool. Keep container closed when not in use. Make sure containers are properly labeled. Store away from incompatible materials. KEEP OUT OF REACH OF CHILDREN.

**Incompatible materials:** Strong bases, strong acids, oxidizing and reducing agents, isocyanates, nitrosating agents.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Ethylene glycol (107-21-1)		
ACGIH TLV	TWA (8 hr.)	25 ppm (vapor fraction) [2016]
ACGIH TLV	STEL	50 ppm (vapor fraction) 10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only) [2016]
OSHA PEL	CEILING (vacated)	50 ppm (125 mg/m <sup>3</sup> )
NIOSH PEL	No Established Limits for Occupational Exposure.	

### 8.2. Exposure controls

**Appropriate engineering controls:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Personal protective equipment:** Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

**Hand protection:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling this product. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

**Skin and Body protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical resistant apron.

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).

<b>Eye protection:</b>	Wear eye/face protection. Wear as appropriate: Safety glasses, safety glasses with side shields, safety goggles.
<b>Respiratory protection:</b>	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state:</b>	Liquid
<b>Appearance:</b>	Clear
<b>Color:</b>	Ice Blue
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Not available
<b>Relative evaporation rate (butyl acetate=1):</b>	Not available
<b>Relative evaporation rate (water=1):</b>	3.4
<b>Melting point:</b>	Not available
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	219°F, 104 °C
<b>Flash point:</b>	>100°C
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Flammability (solid, gas):</b>	Not applicable
<b>Vapor pressure:</b>	17.55 mm Hg
<b>Relative vapor density at 20 °C:</b>	1.14 (air=1)
<b>Relative density:</b>	1.039 (water = 1)
<b>Density:</b>	Not available
<b>Solubility:</b>	Water: 100 %
<b>Log Pow:</b>	Not available
<b>Log Kow:</b>	Not available
<b>Viscosity, kinematic:</b>	Not available
<b>Viscosity, dynamic:</b>	Not available
<b>Explosive properties:</b>	Not available
<b>Oxidizing properties:</b>	Not available
<b>Explosion limits:</b>	Not available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Not reactive under recommended storage and handling conditions.

### 10.2. Chemical stability

Stable under recommended storage and handling conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions not anticipated under recommended storage and handling conditions.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Moisture. Incompatible Materials.

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).

### 10.5. Incompatible materials

Strong Bases, Strong Acids, Oxidizing Agents, Aldehydes

### 10.6. Hazardous decomposition products

During a fire irritating and toxic substances will be released including: Carbon monoxide and carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Principle Routes of Exposure:** Ingestion; Inhalation; Skin and eye contact.

**Target Organs:** Skin, Eyes, Central Nervous System, Respiratory Tract, Kidneys

### 11.2 Symptoms related to the physical, chemical and toxicological characteristics

#### Acute Effects/Symptoms:

- Inhalation:** May cause cough, dizziness and headache. Exposure to very high levels of ethylene glycol vapor causes irritation of mucous membranes and the upper respiratory tract. Exposure to ethylene glycol concentrations higher than 80 ppm results in intolerable respiratory discomfort and cough.
- Skin Contact:** May cause skin irritation. Symptoms include: redness, itching, inflammation and rash.
- Eye Contact:** May cause mild eye irritation. Symptoms include: redness, tearing, inflammation, burning and itching. Exposure to liquid ethylene glycol may result in swelling of the eyelid and swelling around the cornea, inflammation of the conjunctiva and iris and conjunctival or corneal injury.
- Ingestion:** Harmful if swallowed. Seek immediate medical attention. Contains ethylene glycol. Ethylene glycol is rapidly absorbed after ingestion. Early ethylene glycol intoxication resembles ethanol intoxication. Symptoms include: central nervous system depression, intoxication, euphoria, stupor, and respiratory depression. The course of ethylene glycol toxicity is classically divided into three broad overlapping categories of adverse health effects. Stage 1 (the neurological stage) lasts from 30 minutes to 12 hours after ingestion. Stage 2 (the cardiopulmonary stage) occurs between 12 and 24 hours after ingestion. Stage 3 (the renal stage) occurs between 24 and 72 hours after ingestion. Adverse health effects can be delayed significantly by the co-ingestion of alcohol. Nausea and vomiting may occur as a result of gastrointestinal irritation. Severe toxicity may result in coma, loss of reflexes, seizures (uncommon), and irritation of the tissues lining the brain. Kidney (renal) failure can occur 24 to 72 hours after acute ethylene glycol ingestion. Some loss of kidney function may be permanent.
- Delayed Effects/Symptoms:** Chronic or repeated exposure to ethylene glycol causes kidney damage (via ingestion), Irritation of the throat, headache, low backache, loss of consciousness and nystagmus.

#### Delayed and immediate effects and chronic effects from short or long-term exposure:

- Acute toxicity:** Oral: Harmful if swallowed. (Ethylene glycol can be more toxic in humans than in animals.)
- Skin corrosion/irritation:** Does not meet the criteria for classification.
- Serious eye damage/irritation:** Does not meet the criteria for classification.
- Respiratory or skin sensitization:** Does not meet the criteria for classification.
- Germ cell mutagenicity:** Does not meet the criteria for classification.
- Carcinogenicity:** Does not meet the criteria for classification. This product contains no ingredient(s) suspected of being or known to be a carcinogen under OSHA, NTP, IARC and/or NIOSH.
- Reproductive toxicity:** Does not meet the criteria for classification.
- Specific target organ toxicity (single exposure):** Does not meet the criteria for classification.
- Specific target organ toxicity (repeated exposure):** Causes damage to organs (kidneys) through repeated or prolonged exposure via ingestion.
- Aspiration Hazard:** Does not meet the criteria for classification.

#### Toxicity Data (Numerical Values such as Acute Toxicity Data and Irritation Studies):

Ethylene glycol (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rabbit	9530uL/kg (9.53mL/kg)
LD50 intravenous mouse	5500 mg/kg
LDLo oral human	398 mg/kg

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).

### SECTION 12: Ecological information

#### 12.1. Ecotoxicity (aquatic and terrestrial, where available)

No data on the product itself.

##### Ingredient data:

Ethylene glycol (107-21-1)	
LC50 fish	72860 mg/L/96h (Static)
EC50 Daphnia	> 100 mg/L/48h (Static)
ErC50 Algae (growth rate)	6500 - 13000 mg/L/96h
NOEC chronic fish	15380 mg/L/7d, (Static)
NOEC chronic Daphnia	8590 mg/L/7d, (Static)

#### 12.2. Persistence and degradability

Sherlock Leak Detector Type II	
Persistence and degradability	No data available.

#### 12.3. Bioaccumulative potential

Sherlock Leak Detector Type II	
Bioaccumulative potential	No data available.

#### 12.4. Mobility in soil

Sherlock Leak Detector Type II	
Ecology - soil	No data available.

#### 12.5. Results of PBT and vPvB assessment

Sherlock Leak Detector Type II	
Results – PBT and vPvB	No data available.

#### 12.6. Other adverse effects

None Known

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>Handling for Disposal:</b>	Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.
<b>Methods of Disposal:</b>	Dispose of in accordance with all applicable federal, state, provincial and local regulations.
<b>Empty Container Warning:</b>	Contaminated packaging may contain traces of the product and therefore should be disposed of in the same way as product.

### SECTION 14: Transport information

#### US Department of Transportation (DOT)

Not Regulated for Transport.

#### Canadian Transportation of Dangerous Goods Act/Regulations (TDG)

Not Regulated for Transport.

#### IMDG (Transport by sea)

Not Regulated for Transport.

#### IATA (Air transport)

Not Regulated for Transport.

#### Environmental Hazards

Marine Pollutant: NO

#### Special Precautions for User

No additional information.

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).


### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No additional information

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

*The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.*

Sherlock Leak Detector Type II									
USA OSHA Hazard Communication Standard (According to Federal Register/ Vol. 77, No.58/ Mon Mar 26, 2012/Rules & Regulations)	Classified as a hazardous product. See Section 2 for details.								
National Fire Protection Association® (NFPA®) Classification									
American Coatings Association (ACA) Hazardous Materials Identification System ® (HMIS ®) III Classification	<table><tr><td>Health</td><td>2*</td></tr><tr><td>Flammability</td><td>1</td></tr><tr><td>Physical Hazard</td><td>0</td></tr><tr><td>Personal Protection</td><td>C</td></tr></table>	Health	2*	Flammability	1	Physical Hazard	0	Personal Protection	C
Health	2*								
Flammability	1								
Physical Hazard	0								
Personal Protection	C								

### USA Federal Regulations

#### OSHA:

Hazardous according to OSHA HCS (HAZCOM 2012).

#### TSCA:

All product ingredients are listed on or exempt from the TSCA inventory.

#### SARA (Superfund Amendments and Reauthorization Act):

##### CERCLA RQ (lbs.) Ingredients (>0.1%):

Ethylene Glycol (CAS-No. 107-21-1) RQ: 5000 lbs.

##### EPCRA 302 Extremely Hazardous (>0.1%):

No product ingredients listed.

##### EPCRA 313 Toxic Chemicals (>0.1%):

Ethylene Glycol (CAS-No. 107-21-1)

National Fire Protection Association® (NFPA®) Classification

National Fire Protection Association® (NFPA®) Classification

### USA State Regulation

#### California Proposition 65 (California Safe Drinking Water and Toxic Enforcement Act):

##### Prop. 65 Ingredients:

Ethylene Glycol (CAS-No. 107-21-1) (Developmental Toxin – Oral)

Diethanolamine (CAS-No. 111-42-2) (Carcinogen)

Coconut oil diethanolamine condensate (cocamide diethanolamine) (Carcinogen)

#### State Right To Know Ingredients:

##### Massachusetts RTK:

Ethylene Glycol (CAS-No. 107-21-1)

##### Pennsylvania RTK:

Ethylene Glycol (CAS-No. 107-21-1)

# Sherlock Leak Detector Type II

## Safety Data Sheet

USA – According to the OSHA Hazard Communications Standard (HCS) (HAZCOM 2012).

Canada – According to the Hazardous Products Regulations (HPR) (WHMIS 2015).

New Jersey RTK:	Ethylene Glycol (CAS-No. 107-21-1)
CANADA Federal Regulations	
WHMIS 2015:	Hazardous according to WHMIS 2015.
DSL (Domestic Substances List):	All product ingredients are released or listed on the Canadian DSL.

15.2. Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out on this product.

SECTION 16: Other information	
Indication of changes	: Revision
Data sources	: GHS-US, GHS-CA classification parameters. References available upon request.
Date of Issue:	: August 23, 2018

**DISCLAIMER OF LIABILITY:**

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H-phrases:	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H302	Harmful if swallowed
H373	May cause damage to organs through prolonged or repeated exposure