



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 22429
DESCRIPTION: 10/4 STRANDED TYPE SEOWW SUBMERSIBLE FLEXIBLE POWER CABLE
CONSTRUCTION: This cable consists of four bare copper insulated conductors cabled with fillers and an overall jacket.
APPROVALS: UL Standard 62, CSA 22.2 No. 49, NEC Article 400., MSHA
APPLICATION: 600V Portable Oil and Water Resistant Submersible Outdoor Flexible Power Cable
 Class I Div II Hazardous Locations per NEC 501.140 with approved connectors, seals, and installation. (Subject to local authority having jurisdiction.)

Conductor	10 AWG Bare Copper
Stranding	104/30
Insulation Material	105C TPE
Insulation Thickness	0.046" Nom.
Insulated Conductor Diameter	0.204" Nom.
Number of Conductors	4
Lay Length	4.25" Nom.
Filler Type	Polypropylene
Separator/Wrap	Paper Tissue
Jacket Material	105C TPE
Jacket Thickness	0.106" Nom.
Overall Cable Diameter	0.705" Nom.
Approximate Cable Weight	328.7 Lbs/1M' Nom.
Flame Rating	UL/CSA Horizontal Flame Test

Electrical Properties:

Temperature Rating	-50°C to 105°C
Operating Voltage	600 V RMS Max.
DC Resistance per Conductor @ 20°C	0.99 Ohms/1M' Nom.
Max Ampacity per Conductor (Per NEC Table 400-5a)	25 amps/cond (Assume three current carrying conductors)

(Note: Because of 105C temperature rating, higher current can be used under engineering supervision)

Insulation Colors	Black White Red Green
Jacket Color	Black (Other colors available for minimum order)
Legend (Surface Print)	CCI SEOPRENE 105 10 AWG (5.26mm ²) 4/C SEOWW (UL) 600V -50C TO 105C CSA LL39753 ST00W(TPE) 600V -50C TO 105C FT2 WATER RESISTANT P-241-3-MSHA

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____ Date Signed _____

Customer Approval _____

Specification Issue Date: October 27, 2009