

Revision Number: 002.2

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Instant Product type/use: Cyanoacrylate Restriction of Use: None identified Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE 495 INSTANT ADHESIVE known as 495(TM) Super Bonder® Instant Cyanoacrylate IDH number:

209591

Item number:49561Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW	
WARNING:	BONDS SKIN IN SECONDS.	
	COMBUSTIBLE LIQUID.	
	CAUSES EYE IRRITATION.	
MAY CAUSE RESPIRATORY IRRITATION.		

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
EYE IRRITATION	2B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)	

Precautionary Statements

Prevention:	
	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.
Response:	
	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Storage:	-
	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	
-	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Ethyl 2-cyanoacrylate	7085-85-0	80 - 100

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4.	FIRST AID MEASURES
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.
Ingestion:	Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.
Symptoms:	See Section 11.
Notes to physician:	Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal bums they should be treated symptomatically after adhesive is removed.
5. Fl	IRE FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Ventilate area. Do not allow product to enter sewer or waterways.

Clean-up methods:

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Storage:

Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	1 ppm STEL 0.2 ppm TWA (Respiratory sensitization) (Dermal sensitization)	None	None	None
Engineering controls:			t ventilation if general ve below established expo	
Respiratory protection:	limit(s).		r if there is potential to e espirator if there is poter	•
Eye/face protection:	be used goggles	if the potential for splas or safety glasses with s	s with side shields. Full f shing or spraying of prod side shields. Full face pro g or spraying of product	uct exists. Safety ptection should be
Skin protection:	PVC, n		s necessary to prevent c e gloves and aprons as n or cotton.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:Colorless to light yellowOdor:IrritatingOdor threshold:Not available.pH:Not available.Vapor pressure:< 700 mbar (50 °C (122°F)) NoneBoiling point/range:> 149 °C (> 300.2 °F)NoneMetting point/range:Not available.Vapor density:Not available.Flash point:80 - 93 °C (176°F - 199.4 °F) NoneFlash point:Not available.Flammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Flammability:Not available.Flammability:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:SolublePartition coefficient (n-octanol/water):Not available.Viscosity:25.0 - 45.0 mPa.sViscosity:30 - 50 cpDecomposition temperature:Not available.		
Odor:IrritatingOdor threshold:Not available.pH:Not available.Vapor pressure:< 700 mbar (50 °C (122°F)) NoneBoiling point/range:> 149 °C (> 300.2 °F)NoneMelting point/range:Not available.Vapor density:Not available.Vapor density:Not available.Flash point:80 - 93 °C (176°F - 199.4 °F) NoneFlammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Flammability:Not available.Flammability:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:SolublePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:30 - 50 cp	Physical state:	Liquid
Odor threshold:Not available.pH:Not available.Vapor pressure:< 700 mbar (50 °C (122°F)) NoneBoiling point/range:> 149 °C (> 300.2 °F)NoneMelting point/range:Not available.Vapor density:Not available.Flash point:80 - 93 °C (176°F - 199.4 °F) NoneFlammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Flammability:Not applicableFummability:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:SolublePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:25.0 - 45.0 mPa.sViscosity:30 - 50 cp	Color:	Colorless to light yellow
pH:Not available.Vapor pressure:< 700 mbar (50 °C (122°F)) NoneBoiling point/range:> 149 °C (> 300.2 °F)NoneMelting point/ range:Not available.Vapor density:Not available.Flash point:80 - 93 °C (176°F - 199.4 °F) NoneFlammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Flammability:Not available.Flammability:Not available.Fummability:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:SolubilePartition coefficient (n-octanol/water):Not available.Viscosity:25.0 - 45.0 mPa.sViscosity:30 - 50 cp	Odor:	Irritating
Vapor pressure:< 700 mbar (50 °C (122°F)) None	Odor threshold:	Not available.
Boiling point/range:> 149 °C (> 300.2 °F)NoneMelting point/ range:Not available.Vapor density:Not available.Flash point:80 - 93 °C (176°F - 199.4 °F) NoneFlammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Flammability:Not available.Flammability:Not available.Furmability:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:SolubilePartition coefficient (n-octanol/water):Not available.Voc content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	pH:	Not available.
Melting point/ range:Not available.Vapor density:Not available.Flash point:80 - 93 °C (176°F - 199.4 °F) NoneFlammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Flammabily:Not available.Flammabily:Not available.Flammability:Not available.Fundation rate:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:SolubilePartition coefficient (n-octanol/water):Not available.Voc content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:30 - 50 cp	Vapor pressure:	< 700 mbar (50 °C (122°F)) None
Melting point/ range:Not available.Vapor density:Not available.Flash point:80 - 93 °C (176°F - 199.4 °F) NoneFlammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Flammability:Not available.Flammability:Not available.Fummability:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:SolubilePartition coefficient (n-octanol/water):Not available.Viscosity:25.0 - 45.0 mPa.sViscosity:30 - 50 cp	Boiling point/range:	> 149 °C (> 300.2 °F)None
Flash point:80 - 93 °C (176°F - 199.4 °F) NoneFlammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Flammability:Not available.Flammability:Not available.Flammability:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:SolubileSolubility in water:SolubilePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	Melting point/ range:	Not available.
Flammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.Autoignition temperature:Not available.Flammability:Not available.Flammability:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:InsolubleSolubility in water:SolubilePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	Vapor density:	Not available.
Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not available. Flammability: Not available. Solubility in water: Polymerises in presence of water. Solubility in water: Insoluble Solubility in water: Soluble Partition coefficient (n-octanol/water): Not available. VOC content: < 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated) Viscosity: 25.0 - 45.0 mPa.s Viscosity: 30 - 50 cp	Flash point:	80 - 93 °C (176°F - 199.4 °F) None
Autoignition temperature:Not available.Flammability:Not applicableEvaporation rate:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:InsolubleSolubility in water:SolublePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	Flammable/Explosive limits - lower:	Not available.
Flammability:Not applicableEvaporation rate:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:InsolubleSolubility in water:SolublePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:25.0 - 45.0 mPa.sViscosity:30 - 50 cp	Flammable/Explosive limits - upper:	Not available.
Evaporation rate:Not available.Solubility in water:Polymerises in presence of water.Solubility in water:InsolubleSolubility in water:SolublePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	Autoignition temperature:	Not available.
Solubility in water:Polymerises in presence of water.Solubility in water:InsolubleSolubility in water:SolublePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	Flammability	Not applicable
Solubility in water:InsolubleSolubility in water:SolublePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	Evaporation rate:	Not available.
Solubility in water:SolublePartition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	Solubility in water:	Polymerises in presence of water.
Partition coefficient (n-octanol/water):Not available.VOC content:< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)	Solubility in water:	Insoluble
VOC content: < 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated) Viscosity: 25.0 - 45.0 mPa.s Viscosity: 30 - 50 cp	Solubility in water:	Soluble
Viscosity: 25.0 - 45.0 mPa.s Viscosity: 30 - 50 cp	Partition coefficient (n-octanol/water):	Not available.
Viscosity: 30 - 50 cp	VOC content:	< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)
	Viscosity:	25.0 - 45.0 mPa.s
Decomposition temperature: Not available.	Viscosity:	30 - 50 cp
	Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITYStability:Stable under recommended storage conditions.Hazardous reactions:Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and
alcohols.Hazardous decomposition
products:NoneIncompatible materials:Water, amines, alkalis and alcohols.Reactivity:Not available.Conditions to avoid:Spontaneous polymerization.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Sk

Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation. Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.
Skin contact:	May cause skin irritation. Bonds skin in seconds. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.
Eye contact: Ingestion:	Irritating to eyes. Causes excessive tearing. Eyelids may bond. Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.

Hazardous Component(s)	LD50s and LC50s		Immediate and Delayed Health Effects	
Ethyl 2-cyanoacrylate	None		Irritan	t, Allergen, Respiratory
Hazardous Component(s)	NTP Carcinogen	IARC Ca	rcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl 2-cyanoacrylate	No	N	lo	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

	19 CFR)
Proper shipping name:	Combustible liquid, n.o.s. (Cyanoacrylate ester)
Hazard class or division:	Combustible Liquid
Identification number:	NA 1993
Packing group:	III
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)
· · · · ·	
Proper shipping name:	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

Product name: LOCTITE 495 INSTANT ADHESIVE known as 495(TM) Super Bonder® Instant Page 4 of 5

Exceptions:

Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Reactive, Fire, Immediate Health, Delayed Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 9

Prepared by:

by: Product Safety and Regulatory Affairs

Issue date: 08/25/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.