## **Safety Data Sheet**



Revision Number: 005.0 Issue date: 02/25/2021

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Super Lube(R) Synthetic-Based

Lubricant with PTFE

Product type/use: Lubricant Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 209807

Item number:82328Region:United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

# EMERGENCY OVERVIEW NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

| HAZARD CLASS | HAZARD CATEGORY |
|--------------|-----------------|
| None         | None            |

| PICTOGRAM(S) |
|--------------|
| None         |

#### **Precautionary Statements**

Prevention: Not prescribed Response: Not prescribed Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                        | CAS Number | Percentage* |
|---|------------|-------------|
| 1-Decene, homopolymer, hydrogenated           | 68037-01-4 | 60 - 80     |
| White mineral oil (petroleum), highly refined | 8042-47-5  | 10 - 30     |
| Amorphous fumed silica                        | 68611-44-9 | 1 - 5       |
| Ethene, tetrafluoro-, homopolymer             | 9002-84-0  | 1 - 5       |

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact:

Remove contaminated clothing and footwear. Wash with soap and water. If symptoms develop and persist, get medical attention. Wash clothing before

reuse.

IDH number: 209807 Product name: Super Lube(R) Synthetic-Based Lubricant with PTFE

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Never give anything by mouth

to an unconscious person. Get medical attention.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

**Hazardous combustion products:** Oxides of carbon. Toxic fluorine compounds. Toxic and irritating vapors.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Remove all sources of ignition. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder.

inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Remove the absorbed material, and place in an appropriate

chemical waste container for disposal.

#### 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Vapors will accumulate readily and may ignite

explosively. Refer to Section 8.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                        | ACGIH TLV                              | OSHA PEL                              | AIHA WEEL | OTHER   |
|---|--|---------------------------------------|-----------|---|
| 1-Decene, homopolymer, hydrogenated           | 5 mg/m3 TWA mist<br>10 mg/m3 STEL mist | 5 mg/m3 TWA mist                      | None      | None  |
| White mineral oil (petroleum), highly refined | 5 mg/m3 TWA Inhalable fraction.        | 5 mg/m3 TWA mist<br>5 mg/m3 PEL Mist. | None      | None  |
| Amorphous fumed silica                        | None                                   | 0.8 mg/m3 TWA<br>20 MPPCF TWA         | None      | None  |
| Ethene, tetrafluoro-, homopolymer             | None                                   | None                                  | None      | 10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. |

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits. In case of insufficient ventilation, wear suitable respiratory

equipment.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

IDH number: 209807 Product name: Super Lube(R) Synthetic-Based Lubricant with PTFE

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste White Color: Odor: None Odor threshold: Not available. Not available. pH: Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available. Specific gravity: 1.05

Vapor density: Not available.

Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability:

Flammability:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not available.

Not available.

VOC content: 66.56 % EPA Method 24

Viscosity: Not available.

Decomposition temperature: Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Toxic fluorine compounds. Irritating organic fragments.

**Incompatible materials:** Strong oxidizing agents. Acids and bases.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Store away from

incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### **Potential Health Effects/Symptoms**

**Inhalation:** May cause respiratory tract irritation.

Skin contact: May cause skin irritation. Eye contact: May cause eye irritation.

**Ingestion:** Not a likely route of entry. May be harmful if swallowed.

| Hazardous Component(s)                        | LD50s and LC50s                       | Immediate and Delayed Health Effects |
|---|---------------------------------------|--------------------------------------|
| 1-Decene, homopolymer, hydrogenated           | None                                  | No Target Organs                     |
| White mineral oil (petroleum), highly refined | Inhalation LC50 (Rat, 4 h) = > 5 mg/l | Irritant                             |
| Amorphous fumed silica                        | None                                  | No Target Organs                     |
| Ethene, tetrafluoro-, homopolymer             | None                                  | No Target Organs                     |

| Hazardous Component(s)                        | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|----------------|-----------------|--|
| 1-Decene, homopolymer, hydrogenated           | No             | No              | No                                       |
| White mineral oil (petroleum), highly refined | No             | No              | No                                       |
| Amorphous fumed silica                        | No             | No              | No                                       |
| Ethene, tetrafluoro-, homopolymer             | No             | No              | No                                       |

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

## U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

IDH number: 209807 Product name: Super Lube(R) Synthetic-Based Lubricant with PTFE

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 02/25/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.