

AS 631     EG,  GR

**2-HOLE SPLICE CLEVIS**

Use with AS 200 & AS 210  
Std Pkg 25 - Wt/100 pcs: 123 Lbs.

AS 629     EG,  GR

**3-HOLE SPLICE CLEVIS**

Use with AS 200 & AS 210  
Std Pkg 20 - Wt/100 pcs: 195 Lbs.

AS 616     EG,  GR,  ZTC

**4-HOLE SPLICE CLEVIS**

Use with AS 200 & AS 210  
Std Pkg 10 - Wt/100 pcs: 233 Lbs.

AS 644     EG,  GR

**2-HOLE SPLICE CLEVIS**

Use with AS 500 & AS 520  
Std Pkg 20 - Wt/100 pcs: 76 Lbs.

AS 645     EG,  GR

**3-HOLE SPLICE CLEVIS**

Use with AS 500 & AS 520  
Std Pkg 10 - Wt/100 pcs: 116 Lbs.

AS 646     EG,  GR,  ZTC

**4-HOLE SPLICE CLEVIS**

Use with AS 500 & AS 520  
Std Pkg 10 - Wt/100 pcs: 128 Lbs.

Page notes unless otherwise specified: 1/4" thick, 1 5/8" wide, holes 9/16" diameter, spaced 1 7/8" on center and 1 3/16" from end.

**LEGEND:**

GR: Powder Coated Supr-Green    EG: Electro-Galvanized    PG: Pre-Galvanized    AL: Aluminum    HG: Hot Dipped Galvanized    PL: Plain    SS: Stainless Steel    ZTC: Zinc Trivalent Chromium  
Stainless Steel (SS), Zinc Trivalent Chromium (ZTC) and Hot Dipped Galvanized (HG) are specialty finishes. Pricing is located in the Specialty Strut Section of the Anvil-Strut price book.

PROJECT INFORMATION		APPROVAL STAMP	
Project:		<input type="checkbox"/> Approved	
Address:		<input type="checkbox"/> Approved as noted	
Contractor:		<input type="checkbox"/> Not approved	
Engineer:		Remarks:	
Submittal Date:			
Notes 1:			
Notes 2:			