ROD ATTACHMENTS

Fig. 290: Right-Hand Thread **Fig. 290L:** Left-Hand Thread

Size Range: 3/8" through $2^{1}/2$ " Material: Forged steel **Finish:** Plain or Zinc Plated (Hot-Dip Galvanized optional) Service: For use on high temperature piping installations. Approvals: Complies with Federal Specification A-A-1192A (Type 17), WW-H-171-E (Type 17), ANSI/MSS SP-69 and MSS SP-58 (Type 17).

Features:

- Supports loads equal to the full limitation of the hanger rod.
- Provides flexible connection when used with straight thread rod.

Ordering: Specify rod size, figure number, name and finish. If other than standard combination of eye nut number and rod size, specify eye nut number and special rod tapping size. Note: The acceptability of galvanized coatings at temperatures above 450°F is at the discretion of the end user. Larger eye nuts featuring smaller rod sizes are commonly available.

	FIG. 290, 290L: LOADS (LBS) • WEIGHTS (LBS) • DIMENSIONS (IN)										
Rod Size A	Max Load		Weight	В	C	D	Е	F	G	u	Eye Nut
	650° F	750° F	weigill	D	U	U	C C	r	u	H	Number
3⁄8	730	572	0.28	15/32	13/16	13/32	1 ¹⁷ / ₃₂	31/32	5⁄8	1	0
1/2	1,350	1,057	0.28								
5⁄8	2,160	1,692	0.62	- 1½	1 ³ ⁄16	1⁄2	2	13%	11/16	11⁄4	1
3⁄4	3,230	2,530	0.60								
7/8	4,480	3,508	1.70	2	1 ¹¹ ⁄ ₁₆	3⁄4	2 ¹¹ / ₃₂	1 ¹⁵ ⁄16	1	1¾	2
1	5,900	4,620	1.70								
1¼	9,500	7,440	3.60	2 ¹ / ₂	1 ¹³ ⁄16	1	3¾	23⁄8	1¼	2 ¹ ⁄4	3
1 ½	13,800	10,807	3.50								
1 ³ ⁄4	18,600	14,566	16.40	4	4	1½	6¼	4	21⁄4	3¾	4
2	24,600	19,265	15.90								
2 ¹ / ₄	32,300	25,295	15.40								
2 ¹ / ₂	39,800	31,169	14.90								

PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	🗋 Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	
24.1 15	



- C

H (max)



Weldless Eye Nut