## **SWIVEL ATTACHMENTS**



☐ Fig. 290: Right-Hand Thread ☐ Fig. 290L: Left-Hand Thread

Weldless Eye Nut

Size Range: 3/8" through 2 1/2"

Material: Forged steel

**Finish:** Plain or Zinc Plated (Hot-Dip Galvanized optional) **Service:** For use on high temperature piping installations.

**Approvals:** Complies with Federal Specification A-A-1192A (Type 17), WW-H-171-E (Type 17),

ANSI/MSS SP-69 and MSS SP-58 (Type 17).

## **Features:**

- Supports loads equal to the full limitation of the hanger rod.
- Provides flexible connection when used with straight thread rod.

**Ordering:** Specify rod size, figure number, name and finish. If other than standard combination of eye nut number and rod size, specify eye nut number and special rod tapping size.

**Note:** The acceptability of galvanized coatings at temperatures above 450°F is at the discretion of the end user. Larger eye nuts featuring smaller rod sizes are commonly available.






FIG. 290, 290L: DIMENSIONS (IN) • LOADS (LBS) • WEIGHTS (LBS)											
<b>Rod Size</b>	Max Load		Weight	В	С	D	Е	F	G	н	Eye Nut
Α	650° F	750° F	weigiit	ט	U	ט	E	<b>I</b> ⁻	u	"	Number
3/8	730	572	0.28	15⁄32	13/16	13/32	1 <sup>17</sup> / <sub>32</sub>	31/32	5/8	1	0
1/2	1,350	1,057	0.28								
5/8	2,160	1,692	0.62	1½	13/16	1/2	2	13//8	11/16	11/4	1
3/4	3,230	2,530	0.60								
7/8	4,480	3,508	1.70	2	<b>1</b> <sup>11</sup> / <sub>16</sub>	3/4	25/8	<b>1</b> <sup>15</sup> ⁄ <sub>16</sub>	1	13/4	2
1	5,900	4,620	1.70								
11/4	9,500	7,440	3.60	21/2	<b>1</b> <sup>13</sup> ⁄ <sub>16</sub>	1	33//8	23//8	11/4	21/4	3
11/2	13,800	10,807	3.50								
13/4	18,600	14,566	16.40	4	4	1½	61/4	4	21/4	3¾	4
2	24,600	19,265	15.90								
21/4	32,300	25,295	15.40								
21/2	39,800	31,169	14.90								

PROJECT INFORMATION	APPROVAL STAMP
Project:	☐ Approved
Address:	Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	