GRUVLOK PLAIN-END FITTINGS



GRUVLOK PLAIN-END FITTINGS

Gruvlok plain-end fittings are manufactured to provide minimum pressure drop and uniform flow. Fittings are designed for use with the Fig. 7005 Roughneck Couplings only.

Gruvlok plain-end fittings are available in sizes through 8" nominal pipe size in a variety of styles. Depending on size and configuration, fittings are either segment-welded steel or forged steel.

Fittings are normally coated with a rust inhibiting paint. Other coatings including Hot Dipped Zinc Galvanizing, are available.

MATERIAL SPECIFICATIONS

SEGMENT WELDED STEEL FITTINGS:

Sizes 2" - 4" Carbon Steel pipe conforming to ASTM A 53, Type "F"; Sizes 5" - 8"; Carbon Steel pipe conforming to ASTM A 53, Type "E" or "S", Grade "B".

STEEL FITTINGS: Forged Steel conforming to ASTM A 106.

ADAPTER FLANGES:

Class 150 - Carbon Steel conforming to ANSI B16.5 Class 300 - Carbon Steel conforming to ANSI B16.5

FIG. 7050P - 90° Elbow



FIGURE 7050P 90° ELBOW					
Nominal Size	0.D.	Center To End	Approx. Wt. Ea.		
In./DN(mm)	In./mm	In./mm	Lbs./Kg		
2	2.375	4 ³ ⁄4	2.7		
50	60.3	121	1.2		
2 ¹ / ₂	2.875	5½	4.8		
65	73.0	140	2.2		
3	3.500	6 ¹ ⁄4	7.2		
80	88.9	159	3.3		
4	4.500	7 ³ ⁄4	12.3		
100	114.3	197	5.6		
5	5.563	9 ¹ /2	13.4		
125	141.3	241	6.1		
6	6.625	11	31		
150	168.3	279	14.1		
8	8.625	11	38.7		
200	219.1	279	17.6		

FIG. 7051P - 45° Elbow



FIGURE 7051P 45° ELBOW					
Nominal Size	0.D.	Center To End	Approx. Wt. Ea.		
In./DN(mm)	In./mm	In./mm	Lbs./Kg		
2	2.375	3 ¹ /8	2.0		
50	60.3	79	0.9		
2 ¹ / ₂	2.875	3½	3.5		
65	73.0	89	1.6		
3	3.500	33⁄4	4.8		
80	88.9	95	2.2		
4	4.500	4 ¹ ⁄ ₄	8.0		
100	114.3	108	3.6		
5	5.563	5 ¹ /8	9.2		
125	141.3	130	4.2		
6	6.625	53⁄4	18.5		
150	168.3	146	8.4		
8	8.625	6	24.9		
200	219.1	152	11.3		

FITTING SIZE Nominal Nominal 0.D. 0.D. Size Size In./DN(mm) In./mm In./DN(mm) In /mm 2.375 4.500 2 4 100 50 60.3 114.3 21/2 2.875 5 5.563 140 141.3 65 3.500 3 6 6.625 80 88.9 150 168.3 31/2 4.000 8 8.625 90 101.6 200 219.1

The Fitting Size Chart is used to determine the 0.D. of the pipe that the fittings is to be used with. Gruvlok[®] Fittings are identified by either the Nominal size in inches or the Pipe 0.D. In./mm.

□ FIG. 7060P - Tee




FIGURE 7060P TEE					
Nominal Size	0.D.	Center To End	Approx. Wt. Ea.		
In./DN(mm)	In./mm	In./mm	Lbs./Kg		
2	2.375	4 ¹ / ₄	3.5		
50	60.3	108	1.6		
2 ¹ / ₂	2.875	4 ³ ⁄ ₄	6.2		
65	73.0	121	2.8		
3	3.500	5½	8.6		
80	88.9	130	3.9		
4	4.500	5 ⁷ /8	13.8		
100	114.3	149	6.3		
5	5.563	67⁄8	21.7		
125	141.3	175	9.8		
6	6.625	75%	30.9		
150	168.3	194	14.0		
8	8.625	10	61.1		
200	219.1	254	27.7		

Approved
Approved as noted
Not approved
Remarks: