


FIG. E-9 Drain Elbow



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

E-9 DRAIN ELBOW

Nominal Size	O.D.	Max. Working Pressure ▲	Center to End	H	Approx. Wt. Ea.
In./DN(mm)	In./mm	PSI/bar	In./mm	In./mm	Lbs./Kg
1¼	1.660	300	2¾	1¾	0.7
32	42.2	20.7	69	44	0.3
1½	1.900	300	2¾	1¾	1.7
40	48.3	20.7	69	44	0.8
2C	2.375	300	3¼	2¼	2.1
50	60.3	20.7	83	57	1.0
2½C	2.875	300	3¾	2¾	2.9
65	73.0	20.7	95	69	1.3
3C	3.500	300	4¼	2¾	4.0
80	88.9	20.7	108	69	1.8
4C	4.500	300	5	2¾	7.5
100	114.3	20.7	127	69	3.4
5	5.563	300	5½	2¾	11.5
125	141.3	20.7	140	60	5.2
6C	6.625	300	6½	2¾	16.5
150	168.3	20.7	165	69	7.5
8C	8.625	300	7¾	2¾	29.0
200	219.1	20.7	197	69	13.2
10	10.750	300	9	2¾	48.5
250	273.1	20.7	229	69	22.0
12	12.750	300	10	2¾	66.0
300	323.9	20.7	254	69	29.0

C - Cast ductile iron, all others are fabricated steel.

▲ - Working Pressure Ratings are for reference only. For the latest UL/ULC and FM ratings, please visit anvilintl.com or contact your local Anvil Representative.

MATERIAL SPECIFICATIONS

CAST FITTINGS:

2" - 8" Ductile Iron conforming to ASTM A-536, Grade 65-45-12

FABRICATED FITTINGS:

1¼" - 6" are Carbon Steel, A-135 Schedule 10

8" - 12" are Carbon Steel, A-795/A-135/.188 Wall

COATINGS:

- ☐ Rust inhibiting paint Color: ORANGE (standard) or
- ☐ Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- ☐ Other colors available (Example: RAL3000 or RAL9000 Series)

Drain elbow comes standard with 1" female NPT Outlet per ASME B1.20.1.

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	