BOLTS, NUTS, PINS & U-BOLTS



Fig. 120

Light Weight U-Bolt

Size Range: 1/2" through 10"

Material: Carbon steel

Finish: ☐ Plain or ☐ Zinc Plated (Hot-Dip Galvanized optional)

Service: Recommended for support, or guide of relatively light loads. Normally used

with two hex nuts.

Maximum Temperature: 650° F.

Ordering: Specify pipe size x rod size, figure number and name. Hex nuts must be

ordered separately.

10

4,320

2.30

Note: The acceptability of galvanized coatings at temperatures above 450°F is at the

discretion of the end user.

FIG. 120: LOADS (LBS) • WEIGHTS (LBS) • DIMENSIONS (IN)								
Pipe Size	Max Load	Weight	Rod Size A	В	С	D	E	
1/2	580	0.06	1/4	¹⁵ / ₁₆	1 ³ ⁄ ₁₆	1 15/16	13/4	
3/4		0.07		11//8	1%	21/16		
1		0.07		1%	15/8	23/16		
11/4		0.08		111/16	1 ¹⁵ ⁄ ₁₆	23/8		
11/2		0.09		2	21/4	27/16		
2		0.10		2 ⁷ / ₁₆	211/16	211/16		
21/2	1,460	0.28	3/8	2 ¹⁵ / ₁₆	35/16	31/16	2	
3		0.31		39/16	315/16	33//8		
31/2		0.35		41/16	47/16	35/8		
4		0.38		49/16	4 ¹⁵ / ₁₆	37//8		
5		0.45		55%	6	49/16	21/4	
6	2,700	0.95	1/2	63/4	71/4	51/16		
8		1.20		83/4	91/4	61/16		


 $10^{7/8}$

 $11\frac{1}{2}$

 $7^{1}/_{4}$

21/2





PROJECT INFORMATION	APPROVAL STAMP
Project:	☐ Approved
Address:	Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	