

Pool Cover & Utility Pumps



CCP300

Pool Cover Pump Features:

- Magnetic drive motor - Only one moving part.
- Completely submersible.
- Easily hooks up to any standard 3/4" garden hose.
- Extra-long 25' power cord with grounded plug.
- Sturdy ceramic shaft impeller.
- Includes easy clean clog resistant foam filter.
- 1 year warranty.
- Listed to UL and cUL standards.



CCP350 / CCP500

| Part Number | Description | Max Output | Max Pump | | Ctn Qty | List Price |
|-------------|-----------------|------------|----------|--|---------|------------|
| | | | Height | | | |
| CCP300 | Pool Cover Pump | 300 gph | 6' | | 18 | \$ 109.30 |
| CCP350 | Pool Cover Pump | 350 gph | 7' | | 6 | 168.48 |
| CCP500 | Pool Cover Pump | 500 gph | 10.5' | | 6 | 183.54 |



91025 & 91330

Submersible Utility Pump Features:

- 1/5 & 1/3 HP motors, 120 v, 60 Hz
- Corrosion resistant construction.
- 10' waterproof power cord.
- Clog resistant open type impeller.
- Fits in 6" opening.
- Capacities of 26 & 40 gpm.
- 1 year limited warranty.



Specifications:

Discharge: 1 1/4" MNPT or 3/4" GHT
 Housing & Base: Thermoplastic
 Impeller: Thermoplastic
 Bearing: Permanently lubricating
 Motors: Permanent split capacitor, continuous duty, thermally protected



92250 & 92330

Submersible Sump Pump Features:

- 1/4 & 1/3 HP motors, 120 v, 60 Hz
- Corrosion resistant construction.
- 10' waterproof power cord.
- Clog resistant open type impeller.
- Switch turns on at 9", off at 4".
- Handles 1/8" solids.
- 1 year limited warranty.



Specifications:

Discharge: 1 1/4" MNPT
 Housing & Base: Thermoplastic
 Impeller: Thermoplastic
 Bearing: Permanently lubricating
 Motors: Permanent split capacitor, continuous duty, thermally protected

| Model No. | HP | Gallons per minute at discharge height in feet _ | | | | | | Min. Lift | Min. Amps | List Price |
|-----------|-----|--|----|-----|-----|-----|-----|-----------|-----------|------------|
| | | 0' | 5' | 10' | 15' | 20' | 25' | | | |
| SP91025 | 1/5 | 26 | 21 | 14 | 10 | 7 | 1 | 25' | 3.6 | \$ 186.69 |
| SP91330 | 1/3 | 40 | 34 | 28 | 22 | 12 | 2 | 25' | 4.1 | 234.58 |
| SP92250 | 1/4 | 30 | 22 | 20 | 16 | 9 | 2 | 25' | 3.8 | 247.49 |
| SP92330 | 1/3 | 40 | 34 | 28 | 22 | 12 | 2 | 25' | 4.1 | 266.54 |

Note: Use of smaller diameter pipe, or long runs of pipe, will result in lower flow rates than those shown.