

Compression Fittings, Galvanized



Galvanized Long Pattern Compressing Fitting Features:

- Bodies made of steel tubing. (GC 10), malleable iron (GC10C)
- End nuts made of malleable iron.
- Galvanized finish
- Buna-N gaskets on domestic fittings.
- SBR gaskets on GC10C series.
- Maximum rated service temperature for gaskets: 212 °F (100° C).

WARNING: Designer and/or contractor must provide suitable anchoring of piping to prevent pull-out from fittings when applications subject piping to external forces such as ground shift and temperature variations that cause linear pipe contraction.

Recommended Maximum Pressure (PSI)

Size	Torque Ft. Lbs	Anchored Piping
1/2"	150	150
3/4"	150	150
1"	225	100
1-1/4"	225	100
1-1/2"	225	100
2"	300	75



GC10C Series

ISO 9002



Coupling GC10C - Long Pattern - Imported - Malleable Iron, 125 PSI, 120° F

Part Number	Size	Pipe O.D.	Ctn/Case Qty	List Price
GC10C1/2	1/2"	.840	30 / 60	\$ 17.25
GC10C3/4	3/4"	1.050	25 / 50	19.33
GC10C1	1"	1.315	15 / 30	22.67
GC10C11/4	1-1/4"	1.660	12 / 24	28.80
GC10C11/2	1-1/2"	1.900	9 / 18	34.12
GC10C2	2"	2.375	14	51.03



GC10 Series

Coupling GC10 - Made in U.S.A. - Steel Tube

Part Number	Size	Pipe O.D.	Ctn Qty	List Price
GC10-1/2	1/2"	.840	12	\$ 31.05
GC10-3/4	3/4"	1.050	12	33.86
GC10-1	1"	1.315	12	39.97
GC10-11/4	1-1/4"	1.660	6	53.38
GC10-11/2	1-1/2"	1.900	6	58.96
GC10-2	2"	2.375	6	74.10



GC12 Series

Adapters GC12 - Made in U.S.A. - Steel Tube

Part Number	Size	Pipe O.D.	Ctn Qty	List Price
GC12-1/2	1/2"	.840	12	\$ 43.73
GC12-3/4	3/4"	1.050	12	45.77
GC12-1	1"	1.315	12	46.35
GC12-11/4	1-1/4"	1.660	6	55.10
GC12-11/2	1-1/2"	1.900	6	76.62
GC12-2	2"	2.375	6	76.76