

# PLUMBING VALVES



[www.americanvalve.com](http://www.americanvalve.com)

# Contents

## Ball Valves

G100 LEAD-FREE	1
M100	1
G100VL LEAD-FREE	1
G100S LEAD-FREE	2
M100S	2
G111 LEAD-FREE	2
G200W LEAD-FREE	2
G200SW LEAD-FREE	3
G200C LEAD-FREE	3
G200BXB LEAD-FREE	3
2A	3

## Gate Valves

G300 LEAD-FREE	4
G300S LEAD-FREE	4
3/3F	5
3S/3FS	5
3R	6
3FG	6
4FG	6

## Globe & Check Valves

13	7
14N	7
M31	7
G31 LEAD-FREE	7
M31S	8
G31S	8
M31SL	8
G31SL LEAD-FREE	8

## Gas Service Valves

M88C	9
M88CF	9
M88CF12	9
M88CF38A	9
M88CF58	9

85CBK	10
87CBK	10
88C	10

## Stops

G50 LEAD-FREE	11
G50S LEAD-FREE	11
G60 LEAD-FREE	11
G60S LEAD-FREE	11
G63	12
G64	12
G65	12
G66 LEAD-FREE	12

## Boiler Drains

M75	13
M75C	13
M76	13
WM75	13
M75LS	13

## Bent Nose Garden Valves

M78	14
M78INV	14

## Sillcocks & Frost Proof Sillcocks

M74	15
M74S	15
M72AS	15
MVB	15
MVB2	15

## Hose Bibbs

M71	16
M71HD	16
M75NK	16

M75CNK	16
M75SNK	16
M76NK	16

## Quarter Turn Hose End Valves

M71QT	17
M74QT	17
M74SQT	17
M75QT	17
M76QT	17

## Washing Machine & Utility Valves

WMV	18
OPWMV	18
WMVCOMP	18
WMVFRONT	18
SV	18
ASTV	18
WM75CQT	19
WM75CPVCQT	19
WM75QT	19
WM76QT	19
WM75PQT	19
WM75LQT	19

## Heating Valves

9	20
9D	20
7	20
45	20
45S	20
46	20
46S	20



INDUSTRY-LEADING INNOVATION



## OUR INDUSTRY-LEADING TECHNOLOGY IS MAKING YOUR WATER SAFE.

Plumbing valves from American Valve are designed and monitored to minimize the impact of harmful chemicals on the health and safety of people and the environment. We offer a full array of brass and bronze valves certified to meet ANSI/NSF Standard 61, California Proposition 65, and AB 1953.

We start with the finest materials available. Our raw materials are carefully monitored to ensure proper chemical composition.

Every valve is tested for closing tightness and functionality to ensure safe, dependable operation.

Brass valves from American Valve meet the widest range of code approvals in the market. Our products are certified to USA and international standards by Underwriters Laboratories, CSA International, Factory Mutual, IAPMO, and the American Society of Sanitary Engineering.

**1.800.645.0101**

**[www.americanvalve.com](http://www.americanvalve.com)**

Like us on  [Facebook.com/AmericanValve](https://www.facebook.com/AmericanValve)

Follow us on  [Twitter.com/AmericanValve](https://www.twitter.com/AmericanValve)

# Ball Valves



## **G100 LEAD-FREE** Ball Valve with FIP Threaded Ends



- Full Port
- PTFE Seats
- PTFE Packing
- 600 WOG

Size	Box Qty.
1/4	12
3/8	12
1/2	24
3/4	24
1	8
1 1/4	4
1 1/2	4
2	2
2 1/2	2
3	2
4	1



## **M100** Ball Valve with FIP Threaded Ends

- 600 WOG (1/4" - 2")
- 150 psi Saturated Steam
- 400 WOG (2 1/2" - 4")
- Conforms to MSS-SP-110
- CSA Listed (1/2" - 2")
- Full Port
- PTFE Seats
- PTFE Packing
- UL Listed (1/4" - 2")
- FM Listed (1/2" - 2")

Size	Box Qty.
1/4	12
3/8	12
1/2	24
3/4	24
1	8
1 1/4	4
1 1/2	4
2	2
2 1/2	2
3	2
4	2

Not intended to convey water for human consumption



## **G100VL LEAD-FREE** Ball Valve with Push-Fit Ends



- For use with PEX, Copper and CPVC

Size	Box Qty.
1/2	6
3/4	3
1	3

# Ball Valves



## G100S LEAD-FREE Ball Valve with Solder Ends



- Full Port
- PTFE Seats
- PTFE Packing
- 600 WOG

Size	Box Qty.
1/2	30
3/4	20
1	5
1 1/4	12
1 1/2	8
2	4
2 1/2	2
3	2
4	1



## M100S Ball Valve with Solder Ends

- Full Port
- PTFE Seats
- PTFE Packing
- 600 WOG

Size	Box Qty.
3/8	12
1/2	30
3/4	20
1	5
1 1/4	12
1 1/2	8
2	4
2 1/2	2
3	2
4	2

Not intended to convey water for human consumption



## G111 LEAD-FREE Ball Valve with Press-Fit Ends



- Leak Indicator
- Full Port
- 200 PSI Connection
- 250°F Maximum Temperature
- Recommended for Rigid RP330
- Use only with hard drawn copper tube

Size	Box Qty.
1/2	50
3/4	30
1	18
1 1/4	12
1 1/2	10
2	8
2 1/2	1
3	1
4	1



## G200W LEAD-FREE Ball Valve with FIP Threaded Ends



- Waste & Cap
- Full Port
- PTFE Seats
- PTFE Packing
- 600 WOG

Size	Box Qty.
1/2	6
3/4	5
1	10

# Ball Valves



## G200SW LEAD-FREE Ball Valve with Solder Ends



- Full Port
- PTFE Seats
- PTFE Packing
- Waste & Cap

Size	Box Qty.
1/2	12
3/4	6
1	4



## G200C LEAD-FREE Ball Valve with Compression Ends



- Full Port
- PTFE Seats
- 400 WOG
- Blow-Out Proof Stem

Size	Box Qty.
1/2	6
3/4	4
1	3



## G200BxB LEAD-FREE Ball Valve with PEX Ends



- 400 WOG

Size	Box Qty.
3/8	8
1/2	8
3/4	8
1	6



## 2A Industrial Ball Valve with FIP Threaded Ends

- PTFE Seats
- PTFE Packing
- 600 WOG
- Blow-Out Proof Stem

Size	Box Qty.
1/2	10
3/4	10
1	4

\*INTENDED FOR USE IN INDUSTRIAL APPLICATIONS

Not intended to convey water for human consumption

# Gate Valves



## **G300** LEAD-FREE Full Pattern Gate Valve with FIP Threaded Ends



- Non-rising Stem
- Solid Wedge Disc
- 200 WOG

Size	Box Qty.
¼	24
¾	24
½	8
¾	10
1	6
1 ¼	2
1 ½	2
2	2
2 ½	2
3	1
4	1



## **G300S** LEAD-FREE Full Pattern Gate Valve with Solder Ends



- Non-rising Stem
- Solid Wedge Disc
- 200 WOG

Size	Box Qty.
½	10
¾	6

# Gate Valves



## 3/3F LEAD-FREE Gate Valve-125 Class, with FIP Threaded Ends



- Non-rising Stem
- Solid Wedge Disc
- PTFE Packing
- 200 WOG
- 125 WSP
- Dimensions and Workmanship  
Conforms to MSS-SP-80

Size	Box Qty.
1/4	15
3/8	15
1/2	12
3/4	18
1	12
1 1/4	8
1 1/2	4
2	2
2 1/2	1
3	1
4	1



## 3S/3FS LEAD-FREE Gate Valve-125 Class, with Solder Ends



- Non-rising Stem
- Solid Wedge Disc
- PTFE Packing
- 200 WOG
- 125 WSP
- Dimensions and Workmanship  
Conforms to MSS-SP-80

Size	Box Qty.
1/2	12
3/4	12
1	6
1 1/4	4
1 1/2	4
2	2
2 1/2	1
3	1
4	1

# Gate Valves



## 3R LEAD-FREE Gate Valve with FIP Threaded Ends



- Non-rising Stem 125 Class
- Double O-Ring Stem Seal for Pump and Underground Service
- Solid Wedge Disc
- 200 WOG
- 125 WSP

Size	Box Qty.
1/2	12
3/4	18
1	12
1 1/4	8
1 1/2	4
2	2
2 1/2	1
3	1



## 3FG LEAD-FREE Bronze Gate Valve with FIP Threaded Ends



- Non-rising Stem 150 Class
- Solid Wedge Disc
- PTFE Packing
- 300 WOG
- 150 WSP
- Dimensions and Workmanship Conforms to MSS-SP-80

Size	Box Qty.
1/2	10
3/4	8
1	12
1 1/4	4
1 1/2	4
2	2
2 1/2	1
3	1



## 4FG LEAD-FREE Bronze Gate Valve with FIP Threaded Ends



- Rising Stem 150 Class
- Solid Slip-On Wedge Disk
- PTFE Packing
- 300 WOG
- 150 WSP
- Dimensions and Workmanship Conforms to MSS-SP-80

Size	Box Qty.
1/2	18
3/4	12
1	8
1 1/4	8
1 1/2	4
2	2

# Globe & Check Valves



## 13

### Bronze Globe Valve with FIP Threaded Ends

- Bronze Disk
- PTFE Packing
- 200 WOG
- 125 WSP

Not intended to convey water for human consumption

Size	Box Qty.
¼	12
¾	12
½	12
¾	6
1	6
1 ¼	4
1 ½	2
2	2



## 14N

### Bronze Angle Valve with FIP Threaded Ends

- Neoprene Disk
- 200 WOG

Not intended to convey water for human consumption

Size	Box Qty.
¼	12
¾	12
½	12
¾	6
1	6
1 ¼	4
1 ½	2
2	2



## M31

### Brass Swing Check Valve with FIP Threaded Ends

- 200 WOG

Not intended to convey water for Human Consumption

Size	Box Qty.
½	6
¾	6
1	3
1 ¼	2
1 ½	2
2	2
2 ½	1
3	1
4	1



## G31 LEAD-FREE Swing Check Valve with FIP Threaded Ends

- 200 WOG



Size	Box Qty.
½	6
¾	6
1	3
1 ¼	2
1 ½	2
2	2
2 ½	1
3	1
4	1

# Globe & Check Valves



## M31S

Brass Swing Check Valve with Solder Ends

- 200 WOG

Not intended to convey water for human consumption

Size	Box Qty.
½	10
¾	10
1	10
1¼	5
1½	4
2	2



## G31S LEAD-FREE

Brass Swing Check Valve with Solder Ends

- 200 WOG



Size	Box Qty.
½	10
¾	10
1	10
1¼	5
1½	4
2	2



## M31SL

Brass Spring Check Valve with FIP Threaded Ends

- Inline Check
- 200 WOG
- May be used vertically or horizontally

Not intended to convey water for human consumption

Size	Box Qty.
¾	6
1	3
1¼	3



## G31SL LEAD-FREE

Brass Spring Check Valve with FIP Threaded Ends

- Inline Check
- 200 WOG
- May be used vertically or horizontally



Size	Box Qty.
¾	6
1	3
1¼	2

# Gas Service Valves



## M88C Gas Ball Valve with FIP Threaded Ends



- Quarter Turn
- PTFE Seats
- Chrome Plated Ball

Not intended to convey water for Human Consumption

Size	Box Qty.
3/8	8
1/2	20
3/4	6
1	4
1 1/4	4
1 1/2	4
2	2



## M88CF Gas Appliance Connector Valve with Flare Ends



- Quarter Turn
- PTFE Seat
- Chrome Plated Ball

Not intended to convey water for human consumption

Size	Box Qty.
3/8	12
1/2	12



## M88CF12 M88CF38A M88CF58 Gas Appliance Connector Valve

Model	Size	Box Qty.
M88CF12	1/2 x 1/2 FL	12
M88CF38A	1/2 x 3/8 FL	36
M88CF58	3/4 x 5/8 FL	10

- FIP Threaded Ends x Flare Fitting
- Quarter Turn
- Chrome Plated Ball
- PTFE Seat



Not intended to convey water for human consumption

# Gas Service Valves



## 85CBK Bronze Gas Cock with FIP Threaded Ends

- Square Head
- Double Nut
- With Check

Not intended to convey water for human consumption

Size	Box Qty.
1/4	36
3/8	36
1/2	36
3/4	24
1	12
1 1/4	8
1 1/2	6
2	5



## 87CBK Bronze Gas Cock with FIP Threaded Ends

- Tee Handle
- Double Nut
- With Check

Not intended to convey water for human consumption

Size	Box Qty.
1/4	36
3/8	36
1/2	36
3/4	24
1	12
1 1/4	8
1 1/2	6
2	5



## 88C Bronze Gas Cock with FIP Threaded Ends

- Lever Handle
- Double Nut
- With Check

Not intended to convey water for human consumption

Size	Box Qty.
1/4	36
3/8	36
1/2	36
3/4	24
1	12

# Stops



**G50 LEAD-FREE**  
Stop Valve with FIP  
Threaded Ends



Size	Box Qty.
1/2	30
3/4	15



**G50S LEAD-FREE**  
Stop Valve with Solder Ends



Size	Box Qty.
1/2	30
3/4	15



**G60 LEAD-FREE**  
Stop & Waste Valve with FIP  
Threaded Ends



Size	Box Qty.
1/2	30
3/4	15



**G60S LEAD-FREE**  
Stop & Waste Valve with  
Solder Ends



Size	Box Qty.
1/2	30
3/4	15

# Stops



## SUPPLY STOPS

### LEAD-FREE Straight Pattern



- Quarter Turn
- Chrome Plated

Model	Size	Box Qty.
G63	½ FIP x ¾ OD	48
G63	¾ FIP x ¾ OD	48
G63S	½ SWT x ¾ OD	48
G63C	¾ OD x ¾ OD	48
G63P	½ PEX x ¾ OD	48
G63PP	½ PEX x ½ PEX	48
G63CPVC	½ CPVC x ¾ OD	48



## SUPPLY STOPS

### LEAD-FREE Angle Pattern



- Quarter Turn
- Chrome Plated

Model	Size	Box Qty.
G64	½ FIP x ¾ OD	48
G64	¾ FIP x ¾ OD	48
G64S	½ SWT x ¾ OD	48
G64C	¾ OD x ¾ OD	48
G64P	½ PEX x ¾ OD	48
G64CPVC	½ CPVC x ¾ OD	48
G65	½ FIP x ¼ OD	48
G65S	½ SWT x ¼ OD	48
G65C	¾ OD x ¼ OD	48
G65P	½ PEX x ¼ OD	48
G65CPVC	½ CPVC x ¼ OD	48



## SUPPLY STOPS

### LEAD-FREE Dual Pattern



- Quarter Turn
- Chrome Plated

Model	Size	Box Qty.
G66	½ FIP x ¾ OD x ¾ OD	48
G66-14	½ FIP x ¾ OD x ¼ OD	48
G66C	¾ FIP x ¾ OD x ¾ OD	48
G66C-14	¾ FIP x ¾ OD x ¼ OD	48

# Boiler Drains



## M75 Boiler Drain

Inlet: 1/2" MIP Threaded or Solder  
3/4" MIP Threaded Only

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	40
3/4	15



## M75C Boiler Drain

Inlet: Compression

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	10
3/4	8



## M76 Boiler Drain

Inlet: FIP Threaded

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	30
3/4	12



## WM75 Boiler Drain

Inlet: PEX

Outlet: Hose Thread

- Lock Nut for Washing Machine Box

Not intended to convey water for human consumption

Size	Box Qty.
1/2	12
3/4	12



## M75LS Boiler Drain - Long Shank

Inlet: Solder or NPSM Threads

Outlet: Hose Thread

Not intended to convey water for human consumption

\* NPSM threads require a supply tube with a washer for a seal. Not for use with tapered threads. For use as a replacement valve in washing outlet boxes.

Size	Box Qty.
1/2	12

# Bent Nose Garden Valves



## M78

### Bent Nose Garden Valve

Inlet: FIP Threaded

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	10
3/4	20
1	6



## M78INV

### Bent Nose Garden Valve

Inlet: FIP Threaded

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
3/4	12

# Sillcocks & Freeze-Proof Sillcocks

## SILLCOCKS



### M74 Sillcock

Inlet: FIP Threaded  
Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	25
3/4	20



### M74S Sillcock

Inlet: Solder  
Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	12
3/4	10

## FREEZE-PROOF SILLCOCKS



### M72AS Anti-Siphon Freeze Proof Sillcock

Inlet: 1/2" MIP Threaded/Solder/PEX  
(Adapter Included)

Outlet: Hose Thread

- Anti-Siphon Design
- Built-in Vacuum Breaker
- Conforms to ASSE 1019

Not intended to convey water for human consumption

Size	Box Qty.
4	10
6	8
8	10
10	10
12	10
14	10



### MVB Vacuum Breaker

Inlet: Female Hose Thread  
Outlet: Male Hose Thread

- Conforms to ASSE 1011

Not intended to convey water for human consumption

Size	Box Qty.
3/4	10



### MVB2 Vacuum Breaker

Inlet: Female Hose Thread  
Outlet: Male Hose Thread

- Conforms to ASSE 1011

Not intended to convey water for human consumption

Size	Box Qty.
3/4	25

# Hose Bibbs



## M71 Hose Bibb

Inlet: 1/2" MIP Threaded or Solder  
3/4" MIP Threaded Only

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	40
3/4	40



## M71HD Heavy Duty Pattern Hose Bibb

Inlet: 1/2" MIP Threaded or Solder  
3/4" MIP Threaded Only

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	15
3/4	15



## M75NK No-Kink Design Hose Bibb

Inlet: 1/2" MIP Threaded or Solder  
3/4" MIP Threaded Only

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	12
3/4	12



## M75CNK No-Kink Design Hose Bibb

Inlet: Compression

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	24



## M75SNK No-Kink Design Hose Bibb

Inlet: 1/2" or 3/4" Solder

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2 x 3/4	12



## M76NK Hose Bibb

Inlet: FIP Threaded

Outlet: Hose Thread

Not intended to convey water for human consumption

Size	Box Qty.
1/2	12
3/4	12

# Quarter Turn Hose End Valves



## M71QT Hose Bibb

Inlet: 1/2" MIP Threaded or Solder  
3/4" MIP Threaded Only

Outlet: Hose Thread

- Ball Valve Design for Reliability
- Full Port for Maximum Flow
- No-Kink Design

Not intended to convey water for human consumption

Size	Box Qty.
1/2	25
3/4	25



## M74QT Sillcock

Inlet: FIP Threaded

Outlet: Hose Thread

- Ball Valve Design for Reliability
- Full Port for Maximum Flow
- No-Kink Design

Not intended to convey water for human consumption

Size	Box Qty.
1/2	20
3/4	20



## M74SQT Sillcock

Inlet: Solder

Outlet: Hose Thread

- Ball Valve Design for Reliability
- Full Port for Maximum Flow
- No-Kink Design

Not intended to convey water for human consumption

Size	Box Qty.
1/2	10
3/4	10



## M75QT Boiler Drain

Inlet: 1/2" MIP Threaded or Solder  
3/4" MIP Threaded Only

Outlet: Hose Thread

- Ball Valve Design for Reliability

Not intended to convey water for human consumption

Size	Box Qty.
1/2	12
3/4	12



## M76QT Hose Bibb

Inlet: FIP Threaded

Outlet: Hose Thread

- Ball Valve Design for Reliability
- Full Port for Maximum Flow
- No-Kink Design

Not intended to convey water for human consumption

Size	Box Qty.
1/2	25
3/4	25

# Washing Machine & Utility Valves



## WMV Washing Machine Valve

Size	Box Qty.
1/2	4

- Single Lever Control
- Easy to Operate
- Fits any Standard Valve Box

Not intended to convey water for human consumption



## OPWMV Washing Machine Valve

Size	Box Qty.
1/2	10

Inlet: MIP Threaded  
Outlet: FIP Threaded

- Nickel Plated
- Tee Handle

Not intended to convey water for human consumption



## WMVCOMP Washing Machine Valve

Size	Box Qty.
1/2	10

Inlet: Compression  
Outlet: Hose Thread

- Nickel Plated
- Tee Handle

Not intended to convey water for human consumption



## WMVFRONT Washing Machine Valve Front Operated

Size	Box Qty.
1/2	10

Inlet: FIP Threaded  
Outlet: Hose Thread

- Nickel Plated
- Tee Handle

Not intended to convey water for human consumption



## SV Shower Valve

Size	Box Qty.
1/2	4

- Self Closing
- With Pull-Chain
- Durable Chrome Finish

Not intended to convey water for human consumption



## ASTV Anti-Sweat Tank Valve

Size	Box Qty.
1/2	5

Inlet: 2-Hot / Cold Compression  
Outlet: 1 Mixed-Compression

- Adjustable

Not intended to convey water for human consumption

# Washing Machine & Utility Valves

## COMPACT QUARTER TURN HOSE END VALVES



### WM75CQT

Inlet: Compression  
Outlet: Hose Thread

- Quarter Turn
- Compact
- Red or Blue Handle

Size	Box Qty.
5/8"	12

Not intended to convey water for human consumption



### WM75CPVCQT

Inlet: CPVC  
Outlet: Hose Thread

- Quarter Turn
- Compact
- Red or Blue Handle

Size	Box Qty.
1/2"	48

Not intended to convey water for human consumption



### WM75QT

Inlet: MIP Threaded  
Outlet: Hose Thread

- Quarter Turn
- Compact
- Red or Blue Handle

Size	Box Qty.
1/2"	48
3/4"	48

Not intended to convey water for human consumption



### WM76QT

Inlet: FIP Threaded  
Outlet: Hose Thread

- Quarter Turn
- Compact
- Red or Blue Handle

Size	Box Qty.
1/2"	48

Not intended to convey water for human consumption



### WM75PQT

Inlet: PEX  
Outlet: Hose Thread

- Quarter Turn
- Compact
- Red or Blue Handle

Size	Box Qty.
1/2"	12

Not intended to convey water for human consumption



### WM75LQT

Inlet: Solder / NPSM  
Outlet: Hose Thread

- Quarter Turn
  - Compact
  - Red or Blue Handle
- \* NPSM threads are designed to be used with supply stops with a washer. Not to be used with tapered threads. Locking shank nut for locking to washing machine inlet box.

Size	Box Qty.
1/2"	12

Not intended to convey water for human consumption

# Heating Valves

## BRASS - FOR STEAM AND HOT WATER HEATING SYSTEMS



### 9 Steam Radiator Angle Valve

- Rising Stem
- Renewable Packing
- Composition Disc
- Composition Wheel
- 150 WSP

Not intended to convey water for human consumption

Size	Box Qty.
1/2	6
3/4	6
1	6
1 1/4	4
1 1/2	4
2	3



### 9D Steam Radiator Angle Valve

- Rising Stem
- Renewable Packing
- Composition Disc
- Composition Wheel
- 150 WSP

Size	Box Qty.
3/4	6
1	6
1 1/4	4

Not intended to convey water for human consumption



### 7 Radiator Gate Valve

- Non-Rising Stem
- Solid Wedge
- 200 WOG
- 125 WSP

Not intended to convey water for human consumption

Size	Box Qty.
1/2	6
3/4	6
1	4
1 1/4	4
1 1/2	4



45



45S

### 45 & 45S Hot Water Radiator Angle IPS Valve Hot Water Radiator Angle SWT Valve

- Non-Rising Stem
- Solid Wedge
- 200 WOG
- 125 WSP

Size	Box Qty.
1/2	6
3/4	6
1	4
1 1/4	4

Not intended to convey water for human consumption

## BRASS - FOR GRAVITY AND HOT WATER HEATING SYSTEMS



### 46 Hot Water Union Elbow

- FIP Threaded x MIP Union

Not intended to convey water for human consumption

Size	Box Qty.
1/2	6
3/4	6
1	6
1 1/4	4



### 46S Hot Water Union Elbow

- Solder x MIP Union

Not intended to convey water for human consumption

Size	Box Qty.
1/2	12
3/4	12

# AMERICAN VALVE TERMS & CONDITIONS

## SELLING POLICY

The possession of this catalog and or price lists by any person is not to be construed as an offer to sell him or anyone, the items listed herein at the price indicated. We reserve the right to limit quantities and accept all orders subject to our ability to fill. Our minimum order is \$100 net.

We will acknowledge the receipt of your order; however our acknowledgment does not constitute an agreement to fulfill or ship same in any specified time or at prices other than those in effect at the time of shipment or to fulfill same on items or products not in production. Our conditions and terms of sale are per the current price list at the time of the sale and no waiver, alteration or modification of these terms and conditions whether on buyer's purchase order or otherwise shall be valid unless the waiver, alteration or modification is specifically accepted in writing and signed by an authorized representative of Seller.

## CANCELLATIONS

Orders accepted by Seller cannot be countermanded, cancelled, changed, or deliveries deferred except with the Seller's consent and upon terms that will indemnify Seller against loss.

## RETURNED GOODS

We reserve the right to refuse acceptance of material returned without our written permission. Transportation charges must be prepaid on return shipments and our acceptance of same is subject to a 20% charge for rehandling plus any outgoing freight charges and any costs to put material into saleable condition. We reserve the right to issue merchandise credits for returned materials.

## CLAIMS

Claim for shortage must be made within 20 days after receipt of shipment. Any shortage or damage should be noted on B/L or transport receipt when signing. Our proof of shortage is by weight of shipment and shortage claims are subject to such weight.

## TERMS OF PAYMENT

2% cash discount, if paid on or before the 10th of the month following the date of invoice. A service charge of 1 1/2% per month will be charged on past due accounts beyond 30 days from date of invoice.

## FREIGHT TERMS

Brass, Thermoplastic, HotStop, and Ameri-Connect Couplings	Full freight allowed on single orders of \$1000 or more within the continental United States (excluding Alaska & Hawaii)
3700 Series ball valves	May be combined with the above products to meet freight minimum in states east of Colorado
4000 Series ball valves	Full freight allowed on single orders of 1000 lbs. or more within the continental United States (Excluding Alaska & Hawaii).

Freight allowance for factory shipments only on protected through rates from origin to destination. No allowance on UPS, parcel post, or air shipments.

If requested to ship other than our choice, any additional freight charges incurred must be borne by customer.

## DESIGN

American Valve reserves the right to change design, specification or materials without notice, due to a research and development program of continuous product improvement and reserves all rights to label products covered hereunder with appropriate directions or warnings as may be required in its opinion.

## ILLUSTRATIONS

Catalog illustrations are representations of a certain size of each product line but do not necessarily represent all sizes in all details. We reserve the right to institute changes in materials, designs, and specifications, without notice in keeping with our policy on continuing product improvement.

## WEIGHTS

Weights in catalogs, price schedules, quotations, and acknowledgements of all orders are approximate and in no sense guaranteed. They represent the average weight of products as made from patterns in use at time weights were compiled.

## WARRANTY

American Valve warrants, to its initial purchaser only, that its products which are delivered to this initial purchaser will be the kind described in the order or price list and will be free of defects in workmanship or material for a period of one year from the date of delivery to you, our initial purchaser.

Should any failure to conform to this warranty appear within one year after the date of the initial delivery to our initial purchaser, American Valve will, upon written notification thereof and substantiation that the goods have been stored, installed, maintained and operated in accordance with American Valve's recommendation and standard industry practice, correct such defects by suitable repair or replacement at American Valve's own expense. If any valve alleged to be defective, is returned to our factory at Greensboro, NC, it will be examined and, if found to be defective under the warranty, it will be replaced at no charge.

*Teflon® is a registered trademark of DuPont.*



P.O. BOX 35229  
GREENSBORO, N.C. 27425

1.800.645.0101  
FAX-1.800.876.0109

sales@americanvalve.com  
www.americanvalve.com