

# 102S LF

Class 125, Non Rising Stem, Solder, Gate Valve

LEAD FREE

## SUBMITTAL SHEET

"Apollo" Flow Controls



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

### DESCRIPTION

The lead free\* Apollo® Model 102S-LF (30LF Series) Gate Valve provides a "Made in the USA" alternative to globally sourced multi-turn valves for potable water service. These valves are cast, machined, assembled, and tested in South Carolina using proven ASTM quality lead free materials.

### FEATURES

- Lead Free – ANSI 3rd Party Certified
- Full Port Design
- Guided Solid Bronze Disc Wedge
- Adjustable Graphite Stem Packing
- Non-Rising Stem
- Solder Connections
- Screw-in Bonnet
- Rugged Malleable Iron Hand Wheel
- Back seat Protection
- **100% Cast, Machined and Assembled in the USA**
- **ARRA Compliant**

### PERFORMANCE RATING

- Cold Working Pressure:  
200 psi (13.8 Bar) at 100°F
- Temperature Range: -20°F to 406°F

### APPROVALS

- MSS SP-80 - Design & Testing Type 1
- MSS SP-139 - Copper Alloy Bronze Gate, Globe, & Check Valves
- NSF/ANSI 61-8 2010, Annex F & G
- ASME B16.18 - Cast Copper Alloy Solder Joint Pressure Fittings
- CSA B51 CRN OC14667.5
- NSF 372 - Lead Free

### STANDARD MATERIALS LIST

<b>BODY</b>	Bronze, ASTM B584-C89836
<b>BONNET</b>	Bronze, ASTM B584-C89836
<b>STEM</b>	ASTM B21 UNS C46400
<b>DISC WEDGE</b>	ASTM B584-C89836
<b>PACKING</b>	Grafoil® (Asbestos Free)
<b>HAND WHEEL</b>	Malleable Iron
<b>NAMEPLATE</b>	Aluminum

### DIMENSIONS

MODEL NO.	PART NO.	SIZE (IN.)	HEIGHT OPEN (IN.)	LENGTH (IN.)	WEIGHT (LB.)	CV** (GPM)
102S12LF	30LF-043-01	1/2"	3.56	1.88	.85	12.5
102S34LF	30LF-044-01	3/4"	4.05	2.43	1.19	24.0
102S1LF	30LF-045-01	1"	4.55	2.96	1.98	72.3
102S14LF	3LF0-046-01	1-1/4"	5.14	3.14	2.8	80.0
102S12LF	30LF-047-01	1-1/2"	6.02	3.44	3.95	119.0
102S2LF	30LF-048-01	2"	7.09	4.11	5.88	338.0
102S212LF	30LF-049-01	2-1/2"	9.11	4.79	12.19	395.0
102S3LF	30LF-040-01	3"	12.61	5.43	16.84	435.0

\*\*Cv = flowrate at 1.0 psid

\*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

Customer Service (704) 841-6000  
www.apolloflowcontrols.com

This specification is provided for reference only. Conbraco Industries Inc. reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. Please visit [apolloflowcontrols.com](http://apolloflowcontrols.com) for the most current information.

