

Non-Metallic Low-Profile Strain Relief Cord Connectors



LPCG50



LPCG757

WHITE SEALING
RING MATCHES
PRODUCT



LPCG50W

Non-metallic. Liquid-tight. Oil-tight. Furnished with sealing ring and locknut.

Arlington's Low Profile Cord Connector has a unique grommet with gripping fingers. These connectors have the largest cord range in the industry, so there are fewer items to stock. A liquid-tight seal and superior pullout resistance is accomplished by just tightening the nut. A sealing ring is furnished to assure a liquid-tight seal when installing in non-threaded openings.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	CORD RANGE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
LPCG503*	50350	1/2	.100 - .360	25	100	1.792	.595	.978
LPCG50*	80086	1/2	.200 - .485	25	100	1.792	.595	.978
LPCG507	50354	1/2	.385 - .600	25	100	2.250	.595	1.230
LPCG753*	50760	3/4	.100 - .360	10	50	1.963	.595	.978
LPCG754	50762	3/4	.200 - .485	10	50	1.963	.595	.978
LPCG757	36100	3/4	Grommet A - .385 to .600 Grommet B - .600 to .750	10	50	2.250	.595	1.230

*UL not applicable for cords under .200" diameter. Wire strength will not meet UL 35 lb test requirements for the fitting.

▲ Includes UF grommet 14/2 to 12/2 and cord grommet .100 to .300. Bags not available in black. When ordering black, add suffix "BL" to catalog number. When ordering white, add suffix "W" to catalog number.

PATENTED.

