

FEATURES & SPECIFICATIONS

INTENDED USE — Recessed housing rated IC or Non-IC. For new construction only.

Approved for all ceiling and wiring types.

Approved for direct burial in insulation.

CONSTRUCTION — Air-tight standard. Tested to meet current energy codes.

Aluminum housing with galvanized steel pan.

Galvanized bar hangers span up to 24" o.c. and feature stepped shank nail and positioning guide with integral T-bar locks. Two locking screws hold fixture in position.

Galvanized steel junction box with four built-in Romex clamps. Four 1/2" and two 3/4" knockouts with slots for pryout. Rated for through branch wiring.

Maximum 4 (2 in, 2 out) No. 12 AWG conductors. Rated for 90°C.

Ground wire provided.

Removable J-box doors for easy access.

ELECTRICAL — Durable medium-base porcelain socket with nickel plated copper alloy screw shell and contact.

Socket clips to top of housing to prevent paint overspray in socket screw shell.

Socket attaches to reflector to ensure proper and consistent lamp position.

Thermal protection provided against improper lamp usage.

120 volt only.

INSTALLATION — Air-tight housing suitable for air-tight installations. Refer to energy codes for proper installations.

2x8 and 2x6 wood joist or T-bar installation.

Expandable bar hangers allow for off-center mounting in wood joist or T-bar ceilings. Length of 25-1/2" maximum 13-1/4" minimum or cut to fit 5-1/2" on center joist construction.

Vertical adjustment of housing allows for flush mounting with ceiling face.

Suitable for ceilings up to 1-1/2" thick.

LISTINGS — UL Listed to US and Canadian safety standards. Damp location listing (See trim selection for wet location listing).

WARRANTY — 1-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Specifications subject to change without notice.

Catalog Number
Notes
Type



4" Housing

L3

INCANDESCENT

IC/Non-IC

New Construction



Specifications

Height: 5-1/4 (13.3)

Length: 13-1/4 (33.7)

Width: 12-3/16 (30.9)

Ceiling opening: 4 (10.2)

All dimensions are inches (centimeters) unless otherwise specified.

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: L3 R6

L3		
Series	Options	Packaging
L3	Shipped installed in fixture PHC Poke-home wire connector	R6 Resale pack of six U Unit

Accessories: Order as separate catalog number.
ATK3 R6 Airtight trim kit

Notes

See trim summary on reverse side for maximum wattages.

L3 4" New Construction Housing

Description Catalog number	Maximum wattage ¹	Description Catalog number	Maximum wattage ¹	Description Catalog number	Maximum wattage ¹	Description Catalog number	Maximum wattage ¹
General/Task				Accent/Wallwash		Wet Location²	
Open Narrow Flange 301 White 301MW Matte white 301A Clear diffuse, white plastic flange 301A PFMW Clear diffuse, matte white plastic flange 301AZ Clear specular anodized 301BLZ Black specular anodized 301BN Brushed nickel 301BZA Antique bronze 301ORB Oil-rubbed bronze		Baffle Narrow Flange 3B1 Black 3B1 TRMW Black matte, white flange 3B1BN Brushed nickel 3B1BZA Antique bronze 3B1ORB Oil-rubbed bronze		Eyeball Narrow Flange 3E1 White 3E1MW Matte white 3E1BN Brushed nickel 3E1BZA Antique bronze 3E1ORB Oil-rubbed bronze		Wetlite Narrow Flange 3H20 White 3H20MW Matte white 3H20BN Brushed nickel 3H20BZA Antique bronze 3H20ORB Oil-rubbed bronze	
IC		IC	35 PAR20	IC		IC	
Non IC		Non IC	50 PAR20	Non IC	50 PAR20 50 R20	Non IC	75 PAR30 Short neck
Baffle Narrow Flange 3B1W White 3B1MW Matte white		Baffle Deep Narrow Flange 3B2 Black		Wallwash Narrow Flange 3W1 White			
IC	30 R20 35 PAR20	Non IC	50 PAR20 50 R20	Non IC	50 R20 50 PAR20		
Non IC	50 PAR20						
Baffle Narrow Flange 3B1W White 3B1MW Matte white		Baffle Deep Narrow Flange 3B2W White		Pinhole Narrow Flange 3S1 White			
IC	50 PAR20 50 R20	IC	30 R20 35 PAR20	IC	35 PAR20		
Non IC		Non IC	50 R20	Non IC	50 PAR20		

Notes

- 1 Maximum wattage listed. Lower wattage lamps may be used.
- 2 Wetlite trim is wet location listed and outdoor rated. All other trims are damp location.

L Series Baffle Wide flange (Damp location)



Example: 4BLMW LED

L3²

ORDERING INFORMATION For shortest lead times, configure product using **bolded options**.

4BLMW		LED		
Series/Finish		Lamp/Lumen¹	Color temperature	Voltage
<u>Series</u> 4BL 4" baffle LED module	<u>Finish</u> MW Matte white	LED 400 lumens	(blank) 3000K	(blank) 120V

P Series Baffle Wide flange (Wet location)



Example: 4BPMW LED

L3²

ORDERING INFORMATION For shortest lead times, configure product using **bolded options**.

4BPMW		LED		
Series/Finish		Lamp/Lumen¹	Color temperature	Voltage
<u>Series</u> 4BP 4" Baffle LED module	<u>Finish</u> MW Matte white	LED 620 lumens, 10.6 watts	(blank) 3000K	(blank) 120V

Notes

- 1 Total system delivered lumens.
- 2 L3 must be ordered on separate line.

L3 4" New Construction Housing

LED Gimbal (Damp location)



Example: 4G1MW LED
L3²

ORDERING INFORMATION For shortest lead times, configure product using **bolded options**.

4G1		LED			
Series/Finish		Lamp/Lumen ¹	Color temperature	Voltage	
Series	Finish	LED 435 lumens, 7.9 watts	(blank) 3000K	(blank) 120V	
4G1 4" Gimbal module	MW Matte white				
	MB Matte black				
	BN Brush nickel				
	ORB Oil-rubbed bronze				

Notes
1 Total system delivered lumens.
2 L3 must be ordered on separate line.