

# Ball Valves - NO LEAD Brass



HFBV4-PEXSWNL Series

MATERIAL SPECIFICATIONS	
Handle Nut	Zinc Coated Steel
Handle	Zinc Coated Steel
Stem O-ring (2)	NBR
Ball	NL Brass
Seats	PTFE
Body	NL Forged Brass
End Adapter	NL Forged Brass

## NO LEAD Forged Brass STANDARD Port Ball Valve with PEX x SWEAT Connections Features:

- Heavy pattern, standard port, forged NO LEAD brass construction.
- PTFE seats, chrome plated NO LEAD brass ball.
- NBR double o-ring stem seal.
- Blow-out proof stem design.
- **400 PSI** W.O.G. non-shock; **125 PSI** S.W.P.
- PEX x SWEAT ends for use with PEX tubing to copper tubing connections.
- **Third party certified to NSF/ANSI 372.**



Part Number	Size	Ctn/Case Qty	List Price
HFBV4-50PEXSWNL	1/2"	25/100	\$ 10.20
HFBV4-75PEXSWNL	3/4"	10/60	13.70



HFBV6-INL Series

MATERIAL SPECIFICATIONS	
Handle	Zinc Plated Steel
Handle Nut	Zinc Plated Steel
Stem Packing	PTFE
Packing Nut	Brass
Ball	1/2"-1" Lead Free Brass 1 1/4" SS #316
Seats	PTFE
Body	NL Brass
End Adapter	NL Brass

## NO LEAD Forged Brass FULL Port Ball Valve with HOSE BARBS Connection Features:

- Heavy pattern, full port, forged NO LEAD brass construction.
- PTFE seats, chrome plated NO LEAD brass ball.
- PTFE stem packing with adjustable gland follower.
- Blow-out proof stem design.
- **600 PSI** W.O.G. non-shock; **150 PSI** S.W.P.
- Insert hose barb ends for use with polyethylene pipe connections.
- **Third party certified to NSF/ANSI 372.**



Part Number	Size	Ctn/Case Qty	List Price
HFBV6-50INL	1/2"	50/80	\$ 18.85
HFBV6-75INL	3/4"	6/60	28.23
HFBV6-100INL	1"	6/36	50.86
HFBV6-125INL	1 1/4"	5/20	80.74



HFBV6-IFTNL Series

MATERIAL SPECIFICATIONS	
Handle	Zinc Plated Steel
Handle Nut	Zinc Plated Steel
Stem Packing	PTFE
Packing Nut	Brass
Ball	3/4"-1" Lead Free Brass 1 1/4" SS #316
Seats	PTFE
Body	NL Brass
End Adapter	NL Brass

## NO LEAD Forged Brass FULL Port Ball Valve with HOSE BARB x FPT Connection Features:

- Heavy pattern, full port, forged NO LEAD brass construction.
- PTFE seats, chrome plated NO LEAD brass ball.
- PTFE stem packing with adjustable gland follower.
- Blow-out proof stem design.
- **600 PSI** W.O.G. non-shock; **150 PSI** S.W.P.
- Insert hose barb x FPT ends for use with polyethylene pipe and IPS connections.
- **Third party certified to NSF/ANSI 372.**



Part Number	Size	Ctn/Case Qty	List Price
HFBV6-75IFTNL	3/4"	6/60	\$ 23.99
HFBV6-100IFTNL	1"	6/36	43.02
HFBV6-125IFTNL	1 1/4"	5/20	66.00