



Malleable Iron Fittings - Imported

Imported Malleable Iron Fitting Features:

- Class 150 malleable iron pipe fittings
- Suitable for water, steam, air, gas and oil
- All fittings are air pressure tested
- Working pressure: Max: 300 psi @ -20°F to 150°F, Min 150 psi @ 350°F
- Made in China
- Tensile Strength: Min 48000 psi (330 MPa)
- Elongation: Min 8%
- Hardness: Max HB150

Specifications:

Material: ANSI/ASTM A197
Dimensions: ANSI B.16.3 fittings
ASME/ANSI B.16.39 unions
Threads: ASME/ANSI B.1.20.1

ISO 9002

All class 150 imported malleable iron pipe fittings are manufactured under a quality control program complying with CSA B-51 specifications.
Canadian Registration Number OA5312.5C
Galvanized ONLY: Third party certified to NSF/ANSI 372.

BLACK



GALVANIZED



BIM90L/GIM90L Series



BIM90L/GIM90L Reducer Series

Size	Inner/Master Ctn Qty	List Price
90° ELBOW fipxtfip		
BIM90L1/8	50/600	\$ 3.11
BIM90L1/4	35/420	2.97
BIM90L3/8	45/270	2.97
BIM90L1/2 UF	50/200	2.22
BIM90L3/4 UF	30/90	2.68
BIM90L1 UF	20/60	4.73
BIM90L11/4 UF	20/40	7.67
BIM90L11/2 UF	10/20	10.11
BIM90L2 UF	8/16	17.33
BIM90L21/2 UF	1/15	37.64
BIM90L3 UF	1/10	56.13
BIM90L4 UF	1/5	119.41
90° ELBOW REDUCER fipxtfip		
BIM90L3/8X1/8	60/360	6.74
BIM90L3/8X1/4	60/360	4.28
BIM90L1/4X1/8	60/360	5.82
BIM90L1/2X1/8	40/240	4.08
BIM90L1/2X1/4 UF	40/240	4.18
BIM90L1/2x3/8 UF	50/200	4.18
BIM90L3/4x1/2	40/120	4.24
BIM90L3/4X1/4 UF	50/150	5.58
BIM90L3/4X3/8 UF	50/150	5.58
BIM90L1X1/4 UF	30/90	8.80
BIM90L1x1/2	30/90	5.41
BIM90L1X3/8 UF	30/90	8.80
BIM90L1X3/4 UF	30/90	5.41
BIM90L11/4X1/2 UF	30/60	11.66
BIM90L11/4x1 UF	20/40	8.79
BIM90L11/4X3/4 UF	30/60	9.97
BIM90L11/2x1 UF	20/40	14.40
BIM90L11/2x11/4 UF	15/30	14.40
BIM90L2x1 UF	14/28	20.78
BIM90L2x11/4 UF	10/20	20.78
BIM90L2x11/2 UF	10/20	18.27
BIM90L21/2X3/4 F	9/18	50.97
BIM90L21/2X1 F	1/16	50.97
BIM90L21/2X11/4 F	1/15	50.97
BIM90L21/2X11/2 UF	1/15	50.97
BIM90L21/2X2 UF	1/15	50.09
BIM90L3X2 UF	1/10	80.95

Size	Inner/Master Ctn Qty	List Price
90° ELBOW fipxtfip		
GIM90L1/8	50/600	\$ 4.28
GIM90L1/4	35/420	4.09
GIM90L3/8	45/270	4.09
GIM90L1/2 UF	50/200	2.68
GIM90L3/4 UF	30/90	3.23
GIM90L1 UF	20/60	6.08
GIM90L11/4 UF	20/40	9.36
GIM90L11/2 UF	10/20	12.34
GIM90L2 UF	8/16	20.58
GIM90L21/2 UF	1/15	51.27
GIM90L3 UF	1/10	86.16
GIM90L4 UF	1/5	149.15
90° ELBOW REDUCER fipxtfip		
GIM90L3/8X1/8	60/360	6.14
GIM90L3/8X1/4	60/360	6.14
GIM90L1/4X1/8	60/360	6.89
GIM90L1/2X1/8	40/240	5.04
GIM90L1/2X1/4 UF	40/240	5.04
GIM90L1/2 x 3/8 UF	50/200	4.73
GIM90L3/4 x 1/2 UF	40/120	5.49
GIM90L3/4X1/4 UF	50/150	7.28
GIM90L3/4X3/8 UF	50/150	7.28
GIM90L1X1/4 UF	30/90	7.02
GIM90L1X1/2	30/90	7.45
GIM90L1X3/8 UF	30/90	11.40
GIM90L1 x 3/4 UF	30/90	7.02
GIM90L11/4 x 1 UF	20/40	11.75
GIM90L11/2 x 1 UF	20/40	18.10
GIM90L11/2 x 11/4 UF	15/30	18.10
GIM90L2 x 1 UF	14/28	25.12
GIM90L2 x 11/4 UF	10/20	25.12
GIM90L2 x 11/2 UF	10/20	21.93
GIM90L21/2X3/4 F	9/18	80.29
GIM90L21/2X1 F	1/16	80.29
GIM90L21/2X11/4 F	1/15	80.29
GIM90L21/2X11/2 UF	1/15	80.29
GIM90L21/2X2 UF	1/15	80.29
GIM90L3X2 UF	1/10	112.89

U - UL Approval
F - FM Approval



In the United States: Phone (800) 776-2266
In Canada: Phone (800) 268-7570

www.americangranby.com

Fax (800) 729-3299
Fax (905) 629-3204

10/8/18

12.35