# TOPA BATTERY MATERIAL SAFETY DATA SHEET

# PRODUCT NAME: NICKEL CADMIUM SEALED CELL BATTERY (Ni-Cd Series)

Date issued: 2015/05/05 Last Date Revised: 2019/05/04

## Safety data sheet 1907/2006/EC, 1272/2008/EC

#### 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Ni-CD BATTERY
- · Article number: Not available
- · Registration number: Not available
- · Relevant identified uses of the substance or mixture and uses advised against:
- · Sector of Use Consumer electronics and remote control toys product
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: TOPA TECHNOLOGY LIMITED

#### · Full address:

- · No.86,Puxia Road,Henggang,Longgang,Shenzhen,China
- · Phone number: +86-755-28319595
- · FAX: +86-755-28319696
- $\cdot$  Further information obtainable from: TOPA TECHNOLOGY LIMITED  $\cdot$  Emergency telephone number: +86-755-28319595

#### 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008
- The product is not classified according to the CLP regulation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not Applicable

- · Information concerning particular hazards for human and environment:
- The product is not classified as dangerous according to Directive 67/548/EEC, 1999/45/EC and Regulation (EC) No. 1272/2008.
- · Classification system:

The classification is according to the latest edition of the Directive 67/548/EEC , 1999/45/EC and Regulation (EC) No. 1272/2008, and extended by company and literature data.

· Additional information:

A sealed Ni-CD battery is not hazardous in normal use on pinciple.

The product has not to be labelled due to the calculation procedure of international guideline.

The materials contained in this product may only represent below hazard if the integrity of the battery is compromised, physically or electrically abused:

	Very toxic by inhalation.
R45-48/23/25	
	through inhalation and if swallowed.
R35	Causes severe burns.
R62-68-63	Possible risk of impaired fertility. Possible risk of irreversible effects. Possible risk of harm
	to the unborn child.
R42/43	May cause sensitisation by inhalation and skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

· Label elements

- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements

Safety data sheet available on request.

· Additional information:

Important! This product contains substance that is of restricted use under Annex XVII of Regulation (EC) No.1907/2006. For details, please refer to Section 15 and 16 of this Safety Data Sheet.

(Contd. on page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description:

Mixture of the substances listed below with nonhazardous additions.

For the wording of listed risk phrases refer to section 16.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 1306-19-0 EINECS: 215-146-2 EU number: 048-002-00-0	cadmium oxide (nonpyrophoric) I + R26; E T Carc. Cat. 2 R45-48/23/25; Xn R62-68-63; N R50/53 Muta. Cat. 3, Repr. Cat. 3 Acute Tox. 2, H330; Muta2, H341; Carc. 18, H350; Repr. 2, H361fd; STOT RE 1, H372; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	30,0~35,0%
CAS: 7440-02-0 EINECS: 231-111-4 EU number: 028-002-00-7	nickel T R48/2 Garc. Cat. 3 Carc. 2, H351; () Skin Sens. 1, H317	25,0~30,0%
CAS: 1310-58-3 EINECS: 215-181-3 EU number: 019-002-00-8	potassium hydroxide C R35; Mark R22 Skin Corr. 1A, H314; Acute Tox. 4, H3D2	10,0~15,0%
CAS: 7440-48-4 EINECS: 231-158-0 EU number: 027-001-00-9	R53 R53 R53 Resp. Sens. 1, H334; Skin Sens. 1, H317; Aquatic Chronic 4, H413	4,0~8,0%
· Non-dangerous component	S:	
CAS: 7439-89-6 EINECS: 231-096-4	iron	15,0~25,0%
CAS: 7732-18-5 Einecs: 231-791-2	Pure water	10,0~12,0%

### 4 First aid measures

- $\cdot$  Description of first aid measures
- If exposure to internal materials within battery due to damaged outer casing, the following actions are recommended.
- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- $\cdot$  After skin contact: Immediately wash with water and soap and rinse thoroughly.
- $\cdot$  After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- $\cdot$  After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. of page 1)

FII

- $\cdot$  Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed:
- No further relevant information available.

## **5** Firefighting measures

- $\cdot$  Extinguishing media
- $\cdot$  Suitable extinguishing agents:
- CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture:
- Battery may burst and release hazardous decomposition products when exposed to a fire situation.
- · Advice for firefighters Cool fire exposed batteries to prevent rupture.
- · Protective equipment: Mouth respiratory protective device.

# 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:
- Do not allow product to reach sewage system or any water sourse.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- $\cdot$  Reference to other sections:
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

# 7 Handling and storage

- · Handling
- · Precautions for safe handling:
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- · Information about fire and explosion protection: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s): No further relevant information available.

#### 8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

(Contd. of page 2)

		(Contd. of page 3)
· Control parameters		10
-	values that require monitoring at the workplace:	
1306-19-0 cadmium o		
PEL (USA)	0,005 mg/m³ as Cd; see 29 CFR 1910,1027	
REL (USA)	as Cd; SEE 25 CFR (510,1027) as Cd; LFC (LOQ 0,1 mg/m3)	
TLV (USA)	D,DI* 0,002** mg/m <sup>3</sup>	
	as Cd; *inhalable **respirable fraction; BEI	
MAK (Germany) einan	tembare Fraktion; vgl.Abschn.XIII	
7440-02-0 nickel		
PEL (USA)	mg/m <sup>3</sup>	
REL (USA)	0,0Ĭ5 mg/m³	
	as Ni; See Pocket Guide App. A	
TLV (USA)	1.5* 0.2** 0.1*** mg/m <sup>3</sup>	
MAK (Commony) singt	inhal.fraction;*elemental;**insol.,***sol.compds. embare Fraktion; vgl.Abschn.XIII	
1310-58-3 potassium		
i i i i i i i i i i i i i i i i i i i	,	
REL (USA) TLV (USA)	C2 mg/m³ Short-term value: C 2 mg/m³	
7440-48-4 cobalt		
PEL (USA)	D,1* mg/m³ as Co; *for metal dust & fume, as Co	
REL (USA)	$0,05^* \text{ mg/m}^3$	
	inorg. compds.: *metal dust & fume, as Co	
TLV (USA)	0,02 mg/m <sup>3</sup>	
	as Co; BEI	
	embare Fraktion; vgl.Abschn.XIII	
· DNELs: Not available · PNECs: Not available · Additional information	. The lists valid during the making were used as basis.	
<ul> <li>Exposure controls</li> <li>Based on the compositive measure</li> <li>Personal protective ed</li> </ul>	tion shown in Section 3, the following measures are suggested for occupational safety	
· General protective and		
Keep away from foods	tuffs, beverages and feed.	
	Il soiled and contaminated clothing	
	eaks and at the end of work.	
Store protective cloth Avoid contact with the		
· Respiratory protection		
	 ure or low pollution use respiratory filter device. In case of intensive or longer exposure	
use self-contained re:	spiratory protective device.	
· Protection of hands:		
Ma		
Protect	ive glaves	
	s to be impermeable and resistant to the product/ the substance/ the preparation. 10 recommendation to the glove material can be given for the product/ the preparation/	
	ve material on consideration of the penetration times, rates of diffusion and the	
The selection of the s	uitable gloves does not only depend on the material, but also on further marks of quality	
and varies from manu	facturer to manufacturer. As the product is a preparation of several substances, the	(Contd. on page 5)
		EU

(Contd. of page 4)

#### Trade name: Ni-CD BATTERY

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

 $\cdot$  Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

<ul> <li>Information on basic physical and chemical properties</li> <li>General information</li> </ul>	
· General Information · Appearance	
Form:	Cvlinder
Colour:	Silvery white
· Odour:	Odourless
· Odour threshold:	Not available
· pH-value:	6~8
· Change in condition	
Melting point/Melting range:	Not available
Boiling point/Boiling range: • Freezing point:	Not available Not available
· Flash point:	Not available
· Flammability (solid, gaseous):	Not available
· Ignition temperature:	Not available
· Decomposition temperature:	Not available
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits	
Lower:	Not available
Upper:	Not available
· Oxidizing properties:	The substance does not belong to oxidizing substance.
· Vapour pressure:	Not available
· Density:	2,5~4,5 g/cm³
Relative density:	Not available
· Vapour density:	Not available
· Evaporation rate:	Not available
· Salubility in / Miscibility with	
water: · Segregation coefficient (n-octanol/water): Not availab	Not available Ile.
· Viscosity	
Dynamic:	Not available. Not available
Kinematic:	
	(Contd. on page 6) EU

(Contd. of page 5)

Trade name: Ni-CD BATTERY

· Other information:

No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity: Data not avaiable
- Chemical stability: Stable
- · Possibility of hazardous reactions: Danger of explosion.
- Danger of causing burns.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- $\cdot$  Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

1306-19-0 cadmium oxide (nonpyrophoric)

Oral LD50 72 mg/kg (rat)

1310-58-3 potassium hydroxide

Oral LD50 273 mg/kg (rat)

7440-48-4 cobalt

Oral LD50 6170 mg/kg (rat)

7439-89-6 iron

0ral LD50 30000 mg/kg (rat)

· Primary irritant effect

• on the skin: Contact with battery contents may cause strong caustic effect on skin and mucous membranes.

 $\cdot$  on the eye: Contact with battery contents may cause strong caustic effect.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers if leakage occours according to the calculation

method of the General EU Classification Guidelines for Preparations as issued in the latest version:

- Harmful
- Corrosive

Irritant

Very toxic

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic.

 $\cdot$  Toxicokinetics, metabolism and distribution: No further relevant information available

· Acute effects (acute toxicity, irritation and corrosivity): No further relevant information available

### 12 Ecological information

Toxicity

· Aquatic toxicity: No further relevant information available.

· Persistence and degradability: No further relevant information available.

· Bioaccumulative potential: No further relevant information available

 $\cdot$  Behaviour in environmental systems: No further relevant information available

EU

(Contd. of page 6)

#### Trade name: Ni-CD BATTERY

- $\cdot$  Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- $\cdot \ {\sf E}{\sf cotoxical} \ {\sf effects}$
- $\cdot \, \text{Remark:} \, \, \text{Very toxic for fish}$
- · Additional ecological information
- · General notes:
- Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
- Do not allow product to reach ground water, water course or sewage system, even in small quantities.
- Must not reach sewage water or drainage ditch undiluted or unneutralized.
- Danger to drinking water if even extremely small quantities leak into the ground.
- Also poisonous for fish and plankton in water bodies.
- Very toxic for aquatic organisms
- $\cdot$  Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

# 13 Disposal considerations

 $\cdot$  Waste treatment methods

 $\cdot$  Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number · ADR, IMDG, IATA	UN3028
	UNAUZO
· UN proper shipping name · ADR	3028 BA TTE RI ES , DR Y, CON TA INI NG PO TAS SIUM Hydroxide, Solid
·IMDG	BATTERIES, DRY, CONTAINING POTASSIUM HYDROXIDE, Solid, Marine Pollutant
·IATA	BATTERIES, DRY, CONTAINING POTASSIUM HYDROXIDE, Solid
· Transport hazard class(es)	
· ADR	
· Class	8 Corrosive substances.
· Label	8 Lorrosive substances. 8 8
· Label	

	(Contd. of page 7,
· Label	8
· IATA	
Class	8 Corrosive substances.
· Label	8
· Packing group · ADR, IMDG, IATA	Not applicable
· Environmental hazards:	Product contains environmentally hazardous substances:
· Marine pollutant:	cadmium oxide (nonpyrophoric) Yes
·	Symbol (fish and tree)
· Special precautions for user:	Warning: Corrosive substances.
· Danger code (Kemler):	Not applicable
<ul> <li>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:</li> </ul>	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ):	2 kg
· UN "Model Regulation":	UN3D28, BATTERIES, DRY, CONTAINING POTASSIUM Hydroxide, Solid, 8
	Batteries may explode or leak if inserted improperly, recharged or disposed of in fire. Do not mix with non- alkaline or used batteries.

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

$\cdot$ Section 335(extremely hazadous substances):	
1306-19-0 cadmium oxide (nonpyrophoric)	
Section 313(specific toxic chemical listings):	
1306-19-0 cadmium oxide (nonpyrophoric)	
7440-02-0 nickel	
7440-48-4 cobalt	
TSCA(Toxic Substances Control Act):	
All ingredients are listed.	
Proposition 65	
Chemical known to cause cancer:	
7440-02-0 nickel	
7440-48-4 cobalt	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity foe males:	
None of the ingredients is listed.	
	(Contd. on page 9)

	(Contd. of page 8)
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Cancerogenity categories	
· EPA(Environmental Protection Agency)	
1306-19-0 cadmium oxide (nonpyrophoric)	BI
· IARC(International Agency for Research on Cancer)	
1306-19-0 ca¢mium oxide (nonpyrophoric)	1
7440-02-0 nickel	28
7440-48-4 cobalt	2B, 2A
· NTP(National toxicology Program)	
1306-19-0 cadmium oxide (nonpyrophoric)	K
7440-02-0 nickel	R
· TLV(Threshold Limit Value established by ACGIH)	<b>_</b>
1306-19-0 cadmium oxide (nonpyrophoric)	A2
7440-02-0 nickel	A5
7440-48-4 cobalt	A3
· MAK(German Maximum Workplace Concentration)	211
1306-19-0 cadmium oxide (nonpyrophoric)	2
7440-02-0 nickel	1
7440-48-4 cobalt	2
· NIDSH-Ca(National Institution for Occupational Safety & Health )	
1306-19-0 cadmium oxide (nonpyrophoric)	
7440-02-0 nickel	
· OSHA-Ca(Occupational Safety & Health Administration)	
1306-19-0 cadmium oxide (nonpyrophoric)	
<ul> <li>National regulations</li> <li>Other regulations, limitations and prohibitive regulations</li> <li>SVHC Candidate List of REACH Regulation Annex XIV Authorisation (20/06/2011)</li> <li>None of the igredients is listed</li> </ul>	
REACH Regulation Annex XVII Restriction (21/5/2011) 7440-02-0 Nickel	

- REACH Regulation Annex XIV Authorisation List (18/2/2011) None of the igredients is listed
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

The contents and format of this MSDS/SDS are in accordance with REGULATION (EC) No. 1272/2008, (EC) No. 1907/2006, REGULATION (EU) No. 453/2010 and EU Commission Directive 1999/45/EC, 67/548/EEC.

DISCLAIMER OF LIABILITY

The information in this MSDS/SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in anyway connected with the handling, storage, use or disposal of the product. This MSDS/SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS/SDS information may not be applicable. Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.

(Contd. on page 10)

<sup>-</sup> EU

	(Contd. of page 9)
H330	Fatal if inhaled.
1334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
1341	Suspected of causing genetic defects.
1350	May cause cancer.
1351 1361fd	Suspected of causing cancer.
136110 1372	Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.
1400	Very toxic to aquatic life.
1410	Very taxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
S 33 53 5	
722 726	Harmful if swallowed.
735	Very toxic by inhalation. Causes severe burns.
740	Limited evidence of a carcinogenic effect.
(40 742/43	May cause sensitisation by inhalation and skin contact.
743	May cause sensitization by initiation and skin contact. May cause sensitization by skin contact.
745	May cause cancer.
748/23	Toxic: danger of serious damage to health by prolonged exposure through inhalation.
	5 Toxic: danger of serious damage to health by prolonged exposure through inhalation and if
	swallowed.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
753	May cause long-term adverse effects in the aquatic environment.
762	Possible risk of impaired fertility.
763	Possible risk of harm to the unborn child.
768	Possible risk of irreversible effects.
	ded restriction of use
. Shall not	
. Shall not a) in any j inless the b) in artic	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0,2 □g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as:
. Shall not (a) in any   unless the (b) in artic - earrings, - necklace	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0,2 □g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings,
. Shall not (a) in any j unless the (b) in artic earrings, enecklace wrist-wa	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0,2 _g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners,
. Shall not (a) in any j unless the (b) in artic earrings, enecklace wrist-wa rivet but	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than D,2 _g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, cons, tighteners, rivets, zippers and metal marks, when these are used in garments,
. Shall not (a) in any j unless the (b) in artic earrings, earring	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than D,2 _g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, cons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the
. Shall not a) in any j unless the b) in artic earrings necklace wrist-wa rivet but f the rate skin is gre	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than D,2 _g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, cons, tighteners, rivets, zippers and metal marks, when these are used in garments,
. Shall not a) in any j inless the b) in artic earrings necklace wrist-wa wrist-wa skin is gre skin is gre c) in artic o ensure	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0.2 □g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, cons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than 0.5 □g/cm 2 / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged
. Shall not (a) in any j unless the (b) in artic earrings, enecklace exrist-wa rivet but f the rate skin is gre (c) in artic to ensure contact wi	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0,2 _g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, cons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than 0,5 _g/cm 2 / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient
. Shall not (a) in any j unless the (b) in artic earrings, enecklace evrist-wa rivet but f the rate skin is gre skin is gre (c) in artic contact wi article.	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0.2 $\Box g/cm 2$ /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, tons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than 0.5 $\Box g/cm 2$ / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged the skin will not exceed 0.5 $\Box g/cm 2$ / week for a period of at least two years of normal use of the
. Shall not (a) in any j unless the (b) in artic earrings, enecklace wrist-wa rivet but f the rate skin is gre skin is gre (c) in artic contact wi article. 2. Articles	be used: boost assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than $0.2 \ g/cm 2$ /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, tons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than $0.5 \ g/cm 2$ / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed $0.5 \ g/cm 2$ / week for a period of at least two years of normal use of the which are the subject of paragraph 1 shall not be placed on the market unless they conform to the
. Shall not (a) in any j unless the (b) in artic earrings necklace wrist-wa rivet but f the rate (c) in artic co ensure contact wi article. 2. Articles requireme	be used: bost assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than $D,2 \square g/cm 2$ /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, ions, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than $D,5 \square g/cm 2$ / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed $D,5 \square g/cm 2$ / week for a period of at least two years of normal use of the which are the subject of paragraph I shall not be placed on the market unless they conform to the nts set out in that paragraph.
. Shall not (a) in any unless the (b) in artic earrings necklace wrist-wa rivet but f the rate (c) in artic co ensure contact wi article. 2. Articles requireme 3. The star	be used: bost assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than $D_1 \square Q / cm 2$ /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, tons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than $D_1 \square Q / cm 2$ / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed $D_2 \square Q / cm 2$ / week for a period of at least two years of normal use of the which are the subject of paragraph I shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test
. Shall not (a) in any j unless the (b) in artic earrings. necklace wrist-wa rivet but f the rate skin is gre (c) in artic contact wi article. 2. Articles requireme 3. The star nethods fi	be used: bost assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than $D_{1,2} \square g/cm 2$ /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, tons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than $D_{1,5} \square g/cm 2$ / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed $D_{1,5} \square g/cm 2$ / week for a period of at least two years of normal use of the which are the subject of paragraph 1 shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test or demonstrating the conformity of articles to paragraphs 1 and 2.
. Shall not (a) in any p unless the (b) in artic earrings, necklace wrist-wa rivet but f the rate (c) in artic contact wi article. 2. Articles requireme 3. The star nethods fu	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0.2 □g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, tons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than 0.5 □g/cm 2 / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed 0.5 □g/cm 2 / week for a period of at least two years of normal use of the which are the subject of paragraph 1 shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test or demonstrating the conformity of articles to paragraphs 1 and 2. Ins and acronyms:
. Shall not (a) in any j unless the (b) in artic earrings, necklace wrist-wa rivet but f the rate skin is gre (c) in artic contact wi article. 2. Articles requireme 3. The star methods fu (DR: Accord Carriage of C	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0.2 □g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, cons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than 0.5 □g/cm 2 / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed 0.5 □g/cm 2 / week for a period of at least two years of normal use of the which are the subject of paragraph I shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test or demonstrating the conformity of articles to paragraphs I and 2. Ins and acronyms: auropéen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International angerous Boods by Road)
. Shall not (a) in any j unless the (b) in artic earrings, necklace wrist-wa rivet but f the rate skin is gre contact wi article. 2. Articles requireme 3. The star methods fu labreviatic QR: Accord Carriage of C RD: Règleme	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than $D_{i} \square Q / cm 2 / week$ (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, icons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than $D_{i} \square Q / cm 2 / week$ . les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed $D_{i} \square Q / cm 2 / week$ for a period of at least two years of normal use of the which are the subject of paragraph I shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test or demonstrating the conformity of articles to paragraphs I and 2. Ins and acronyms: suropéen sur le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
. Shall not (a) in any j unless the (b) in artic earrings, necklace wrist-wa rivet but f the rate skin is gre contact wi article. 2. Articles requireme 3. The star methods fu labreviatic QR: Accord Carriage of C RD: Règleme nternational	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0.2 □g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, cons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than 0.5 □g/cm 2 / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed 0.5 □g/cm 2 / week for a period of at least two years of normal use of the which are the subject of paragraph I shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test or demonstrating the conformity of articles to paragraphs I and 2. Ins and acronyms: auropéen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International angerous Boods by Road)
. Shall not (a) in any junless the (b) in artic earrings recklace wrist-wa rivet but f the rate skin is gre (c) in artic contact wi article. 2. Articles requireme 3. The star methods fu (bDreviatic Articles of C (DR: Regleme nternational MDG: Interna ATA: Interna	be used: nost assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than $D_{i} \square g/cm 2$ /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, cons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than $0,5 \square g/cm 2$ / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed $0,5 \square g/cm 2$ / week for a period of at least two years of normal use of the which are the subject of paragraph I shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test ar demonstrating the conformity of articles to paragraphs I and 2. Ins and acronyms: zuropéen sur le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Transport 5 Dangerous Boods by Road) nt international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Transport of Dangerous Boods by Riad)
. Shall not (a) in any j unless the (b) in artic earrings necklace wrist-wa rivet but f the rate skin is gre (c) in artic contact wi article. 2. Articles requireme 3. The star methods fu (bDreviatic DR: Accord Carriage of C Carriage of C C Carriage of C C Carriage of C C Carriage of C C Carriage of C C C C C C C C C C C C C C C C C C C	be used: post assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than $D_{i} \square g/cm 2$ /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners. cons, tighteners, rivets, zippers and metal marks, when these are used in garments. of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than $0.5 \square g/cm 2$ / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed $0.5 \square g/cm 2$ / week for a period of at least two years of normal use of the which are the subject of paragraph 1 shall not be placed on the market unless they conform to the nts set out in that paragraph. Idards adopted by the European Committee for Standardisation (CEN) shall be used as the test prodemonstrating the conformity of articles to paragraphs 1 and 2. Ins and acronyms: suropeen sur la transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Transport of Dangerous Goods by Rail) tional Maritime Code for Dangerous Goods innal Air Transport Association
. Shall not (a) in any j unless the (b) in artic earrings. necklace wrist-wa rivet but f the rate skin is gre (c) in artic contact wi article. 2. Articles requireme 3. The star nethods fi bbreviatic vDR: Accord arriage of C (10: Règleme nternational MDG: Interna ATA: Interna CAD: Interna CAD: Interna CAD: Interna	be used: loss assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than 0.2 □g/cm 2 /week (migration limit): les intended to come into direct and prolonged contact with the skin such as: s. bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, tons, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than 0.5 □g/cm 2 / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed 0.5 □g/cm 2 / week for a period of at least two years of normal use of the which are the subject of paragraph I shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test prodemsure tarsport des marchandises dangereuses par Route (European Agreement concerning the International angerous Goods by Road) nt international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Transport Ongareus Goods by Reat) timal Maritime Code for Dangerous Goods timal Air Transport Association timal Air Transport Association
. Shall not (a) in any junless the (b) in artic earrings. necklace wrist-wa rivet but f the rate skin is gre (c) in artic contact wi article. 2. Articles requireme 3. The star nethods fu bbreviatic DRE Accord Carriage of C (D: Regleme nternational MDG: Interna ATA: Interna GAD:	be used: Jost assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than D.2 □g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: as. bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, ions, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than D.5 □g/cm 2 / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed D.5 □g/cm 2 / week for a period of at least two years of normal use of the which are the subject of paragraph 1 shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test ur demonstrating the conformity of articles to paragraphs 1 and 2. ns and acronyms: auropéen sur le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Transport of Dangerous Goods by Rail) tional Martime Code for Dangerous Goods by Rail) tional Air Transport Association tional Civil Aviation Organization Harmonized System of Classification and Libelling of Chemicals con Conference of Givernmental Industrial Hygienists No-Effect Level (REACH)
. Shall not (a) in any j unless the (b) in artic earrings. necklace wrist-wa rivet but f the rate skin is gre (c) in artic contact wi article. 2. Articles requireme 3. The star methods fi lobreviatic ADR: Accord Carriage of C RD: Regleme nternational MOG: Interna 3HS: Globally CGDH: Ameri DNEL: Derive PNEC: Predic	be used: nost assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than $D_{12} \square g/cm 2$ /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: s, bracelets and chains, anklets, finger rings. tch cases, watch straps and tighteners. ons, tighteners, rivets, zippers and metal marks, when these are used in garments. of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than $D_{5} \square g/cm 2$ / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed $D_{5} \square g/cm 2$ / week for a period of at least two years of normal use of the which are the subject of paragraph 1 shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test ar demonstrating the conformity of articles to paragraphs 1 and 2. Ins and acronyms: auropéan sur le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Transport of Dangerous Goods by Rad) nt international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Transport of Dangerous Goods by Rad) nt inder Transport descoints in and Labelling of Chemicals can Conference of Bovernmental Industrial Hygienists INO-Effect Level (REACH)
. Shall not (a) in any j unless the (b) in artic earrings, necklace wrist-wa rivet but f the rate skin is gre (c) in artic to ensure contact wi article. 2. Articles requireme 3. The star nethods fi bbreviatic NDE: Derive NE: Regleme nternational MDE: Interna SHS: Globally CGIH: Ameri NE: Derive PNEC: Predic C50: Lethal	be used: Jost assemblies which are inserted into pierced ears and other pierced parts of the human body rate of nickel release from such post assemblies is less than D.2 □g/cm 2 /week (migration limit); les intended to come into direct and prolonged contact with the skin such as: as. bracelets and chains, anklets, finger rings, tch cases, watch straps and tighteners, ions, tighteners, rivets, zippers and metal marks, when these are used in garments, of nickel release from the parts of these articles coming into direct and prolonged contact with the ater than D.5 □g/cm 2 / week. les referred to in point (b) where these have a non-nickel coating unless such coating is sufficient that the rate of nickel release from those parts of such articles coming into direct and prolonged th the skin will not exceed D.5 □g/cm 2 / week for a period of at least two years of normal use of the which are the subject of paragraph 1 shall not be placed on the market unless they conform to the nts set out in that paragraph. dards adopted by the European Committee for Standardisation (CEN) shall be used as the test ur demonstrating the conformity of articles to paragraphs 1 and 2. ns and acronyms: auropéen sur le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Transport of Dangerous Goods by Rail) tional Martime Code for Dangerous Goods by Rail) tional Air Transport Association tional Civil Aviation Organization Harmonized System of Classification and Libelling of Chemicals con Conference of Givernmental Industrial Hygienists No-Effect Level (REACH)