

## FEATURES & SPECIFICATIONS

### INTENDED USE

For use with housings LCP, LC6, L7XPR, L7X, L7XR, L7XF and L7XFR.

### CONSTRUCTION

Aluminum one-piece reflector.

White polyester powder coat paint.

### INSTALLATION

Socket to trim interface.

Retaining clips riveted to top of reflector hold trim inside housing.

### LISTINGS

UL Listed to US and Canadian safety standards.

Damp location listed.

### WARRANTY

1-year limited warranty. Complete warranty terms located at [www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

Actual performance may differ as a result of end-user environment and application.

Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

6" Finishing Trim

# C01

**OPEN SHALLOW**  
Wide Flange




### Specifications

Height: 5-7/8 (14.9)

Lamp opening: 4-1/4 (10.8)

Diameter: 7-3/4 (19.7)

All dimensions are inches (centimeters) unless otherwise indicated.



### ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

**Example: C01**

<b>C01</b>	
Series	Finish
<b>C01</b>	<b>(blank)</b> White

Housing Compatibility: Housing and trim ordered separately.			
Application	Source	Maximum wattage	Housing
IC	Incandescent	75 PAR30 short neck	LCP, LC6, L7XPR, L7X, L7XR
		65 BR30	
		60 A19	
	Fluorescent	13DTT	L7XF, L7XFR

