

## FEATURES & SPECIFICATIONS

**INTENDED USE** — Recessed housing rated IC or Non-IC. For new construction or remodel<sup>1</sup> applications. Approved for all ceiling types, except air handling plenums. Not for pulling wires. Romex only. Approved for direct burial in insulation.

**CONSTRUCTION** — Air-tight standard. Tested to meet current energy codes.

Aluminum housing with engineering-grade thermoplastic frame.

Galvanized bar hangers span up to 24" o.c. and feature stepped shank nail and positioning guide with integral T-bar locks. Two locking screws hold fixture in position.

Engineering-grade thermoplastic junction box with four built-in romex clamps; five 7/8" knockouts with slots for pryout.

Maximum 8 (4in, 4out) No 12 AWG conductors. Rated for 90° C.

Ground wire provided.

Pre-assembled poke-home connectors for ease of wiring.

Tilt-up captive J-box doors for easy access.

Trim retention (clips): Retaining clips riveted to top of reflector hold trim inside housing.

Trim retention (TOR): Two-side mounted torsion springs on the trim and 2 receiving brackets in the can ensure a consistently tight fit with the ceiling.

**ELECTRICAL** — Durable medium base porcelain socket with nickel-plated copper alloy screw shell and contact.

Socket clips to top of housing to prevent paint overspray in socket screw shell.

Socket attaches to reflector to ensure proper and consistent lamp position.

Thermal protection provided against improper lamp usage.

120 volt only.

**INSTALLATION** — Air-tight housing suitable for air-tight installations. Refer to energy codes for proper installations.

2 x 8 wood joist or T-bar installation.

Expandable bar hangers allow for off-center mounting in wood joist or T-bar ceilings. Length of 25-1/4" maximum 13-1/4" minimum or cut to fit 9" on center joist construction.

Vertical adjustment of housing allows for flush mounting with ceiling face.

Suitable for ceilings up to 1-1/2" thick.

**LISTINGS** — UL Listed to US and Canadian safety standards.

Damp location listed.

See trim selection for wet location listing.

**WARRANTY** — 1-year limited warranty. Complete warranty terms located at [www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

**Note:** Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Catalog Number
Notes
Type





6" Housing

# LC6

**INCANDESCENT**

IC/Non-IC

New Construction/Remodel



### Specifications

Height: 7-1/2 (19.1)

Length: 13 (33.0)

Width: 9 (22.9)

Ceiling cutout: 7-1/8 (18.1)

All dimensions are inches (centimeters) unless otherwise indicated.

### ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

**Example:** LC6 R6

LC6		
Series	Options	Packaging
LC6	<b>GSKT</b> Foam gasketing. Aids in air-tight installation.	<b>R6</b> Resale pack of six <b>U</b> Unit (non-stock)

Accessories: Order as separate catalog number.			
LSMC	T-Bar mounting clips, set of four	HS6875	6-7/8" Hole saw
ARC R24	Remodeler clips <sup>1</sup>	CTR6	6" goof ring, white (8-3/4" O.D.)
ATK6 R6	6" Air-tight trim kit		

### Notes

<sup>1</sup> When using in remodel applications the ARC R24 clips must be ordered separately. Sold in packages of 24 only.

See trim summary on reverse side for maximum wattages.

# LC6 6" New Construction Housing

Description Catalog number	Maximum wattage <sup>1</sup>	Description Catalog number	Maximum wattage <sup>1</sup>	Description Catalog number	Maximum wattage <sup>1</sup>	Description Catalog number	Maximum wattage <sup>1</sup>
<b>General/Task</b>							
Open Wide Flange <b>601</b>	White 65 BR30 75 PAR30	Shallow Open, Narrow Flange <sup>2</sup> <b>6B1</b> <b>6B1W</b>	Black White 40 A19 65 BR30 75 PAR30	Baffled Eyeball Narrow Flange <b>6E2</b>	Black/white 65 BR30 75 PAR30	Pinhole Narrow Flange <b>6S1</b>	White 60 A19 75 BR30 50 R20/PAR20
IC/Non-IC		IC/Non-IC		IC/Non-IC		Non-IC	
Open Wide Flange <b>601 TOR</b> <b>601ORB TOR</b> <b>601BZA TOR</b>	White Oil-rubbed bronze Antique bronze 65 BR30 75 PAR30	Baffle Wide Flange <b>6B1 TOR</b> <b>6B1W TOR</b> <b>6B1BN TOR</b>	Black White Brushed nickel 40 A19 65 BR30 75 PAR30	Regressed Eyeball Narrow Flange <b>6RE1</b> <b>6RE1W</b>	Black/white White/white 65 BR30 75 PAR30	<b>Lens/Wet Location <sup>3</sup></b>	
IC/Non-IC		IC/Non-IC		IC/Non-IC		WETlite™ <b>6H20 TOR</b> White <b>6H20BN TOR</b> Brushed nickel <b>6H20ORB TOR</b> Oil-rubbed bronze 75 PAR38 75 PAR30	
Open Narrow Flange <b>602</b> <b>602A</b> <b>602AZ</b>	White Clear diffuse Clear specular 65BR40	Baffle Narrow Flange <b>6B3</b> <b>6B3W</b>	Black White 100 A19 120 BR40 150 PAR38	Baffle Regressed Eyeball Narrow Flange <b>6RE2</b> <b>6RE2W</b>	Black/black White/white 65 BR30 75 PAR30	IC/Non-IC	
IC		Non-IC		IC/Non-IC		Shower/Closet Lens Narrow Flange <b>6LD1</b> Drop opal plastic* <b>6LD2</b> Drop prismatic plastic* <b>6LF1</b> Flush opal plastic* <b>6LF2</b> Flush prismatic plastic*	
Non-IC		Non-IC		IC/Non-IC		Non-IC	
Open Narrow Flange <b>602 TOR</b> <b>602BN TOR</b> <b>602ORB TOR</b> <b>602BZA TOR</b>	White Brushed nickel Oil-rubbed bronze Antique bronze 65BR40	Baffle Narrow Flange <b>6B4</b> <b>6B4W</b>	Black White 75 A19 120 BR40 150 PAR38	Baffle Adjustable Narrow Flange <b>6AB1</b> <b>6AB1W</b>	Black White 65 BR30 75 PAR30	Non-IC	
IC		Non-IC		Non-IC		Glass Lens Narrow Flange <b>6LD3</b> Drop opal white splay <b>6LDB3</b> Drop opal black baffle <b>6LF3</b> Flush white white splay <b>6LFB3</b> Flush white black baffle <b>6L4</b> Fresnel white splay <b>6LB4</b> Fresnel black baffle <b>6L4MW</b> Matte white 75 A19	
Non-IC		Non-IC		Non-IC		Non-IC	
Open Cone Narrow Flange <b>6C3BLZ</b> <b>6C3AZ</b>	Black specular Clear specular 100A19 120 BR40 150 PAR38	<b>Accent/Adjustable</b>		Cone Adjustable Narrow Flange <b>6AC1AZ</b> <b>6AC1BLZ</b>	Clear specular Black specular 65 BR30 75 PAR30	* For plastic flange add suffix PF	
Non-IC		Eyeball Narrow Flange <b>6E1</b>	White 65 BR30 75 PAR30	Non-IC		Non-IC	
Shallow Open, Narrow Flange <sup>2</sup> <b>603AZ</b>	Clear specular 100A19 120 BR40 150 PAR38	IC/Non-IC		Wallwash Narrow Flange <b>6W1</b>	White 100 A19	Non-IC	
Non-IC		Non-IC		Baffled Wallwash Narrow Flange <b>6W2W</b>	White 100 A19	Notes	
Non-IC		Non-IC		Non-IC		1 Maximum wattage listed. Lower wattage lamps may be used. 2 Shallow trims may be used for lower lamp position. 3 Lens trims and WETlite™ are wet location listed. All others are damp location.	

## Notes

- See LED modules on page 3 and page 4.
- 7 and C series trims also compatible options.

# LC6 6" New Construction Housing

## REALITY™ ENERGY STAR® (ESL) Open Narrow Flange LED Module (Wet location)



Example: REAL6 D6MW ESL 1000L 35K .60SC  
LC6<sup>1</sup>

**ORDERING INFORMATION** For shortest lead times, configure products using **bolded options**.

Series/Finish		ESL		Lumen output <sup>2</sup>		Color temperature		Distribution		Voltage		Options			
Series <b>REAL6 D6</b>	6" ENERGY STAR® retrofit module	Finish <b>MW</b>	Matte white	<b>ESL</b>	ENERGY STAR® qualified	<b>600L</b>	8W, 600 lumens	27K	2700 K	<b>.60SC</b>	.60 spacing criteria	(blank)	120V	PFMW	Matte white plastic flange ring
		A	Clear diffuse			<b>1000L</b>	11W, 1000 lumens	30K	3000 K	.90SC	.90 spacing criteria			PFBL	Black plastic flange ring
		AZ	Clear specular					35K	3500 K					ISH	Insect shield
		BN	Brushed nickel					40K	4000 K						
		BLZ	Black specular												
		BZA	Antique bronze												
		ORB	Oil-rubbed bronze												
		WT	Wheat diffuse												

**Notes**

- 1 LC6 housing ordered on a separate line.
- 2 Total system delivered lumens.

## P Series Open and Baffle Wide Flange LED Modules (Wet Location)



Example: 6BP TRMW LED 27K 90CRI  
LC6<sup>1</sup>

**ORDERING INFORMATION**

Series/Finish		Lamp	CCT / CRI / W / Lumens <sup>2</sup>				Voltage	
6BPMW	6" Baffle LED module, matte white	LED	(blank)	3000 K / 83 CRI / 8.9W / 620L			(blank)	120V
6BP TRMW	6" Baffle LED module, black baffle, matte white flange		27K 90CRI	2700 K / 93 CRI / 11.2W / 600L				
6BPBN	6" Baffle LED module, brushed nickel		30K 90CRI	3000 K / 93 CRI / 11.2W / 600L				
6BPORB	6" Baffle LED module, oil-rubbed bronze		40K 90CRI	4000K / 92CRI / 9.9W / 650L				
60PA	6" Open LED module, clear diffuse							
60PAZ	6" Open LED module, clear specular	HL LED	(blank)	3000 K / 83 CRI / 15.2W / 950L				
60PA TRMW	6" Open LED module, clear diffuse, matte white flange		27K 90CRI	2700 K / 93 CRI / 16.5W / 860L				
60PAZ TRMW	6" Open LED module, clear specular, matte white flange		30K 90CRI	3000 K / 93 CRI / 16.5W / 860L				
			40K 90CRI	4000K / 92CRI / 16.4W / 950L				

**Notes**

- 1 LC6 housing ordered on a separate line.
- 2 Total system delivered lumens.



LC6

# LC6 6" New Construction Housing

## LED Gimbal Module (Damp location)



Example: 6G1MW LED  
LC6<sup>1</sup>

### ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

6G1		LED			
Series/Finish		Lamps	CCT / CRI / W / Lumens <sup>3</sup>		Voltage
Series	Finish	LED	(blank)	3000k / 83CRI / 10.8W / 620L	(blank) 120V
<b>6G1</b>	6" Gimbal Module	<b>MW</b>	Matte white	27K 90CRI 2700K / 91CRI / 11W / 680L	
		<b>MB</b>	Matte black <sup>2</sup>	30K 90CRI 3000K / 91CRI / 10.3W / 790L	
		<b>BN</b>	Brush nickel <sup>2</sup>	40K 90CRI 4000K / 94CRI / 10.5W / 820L	
		<b>ORB</b>	Oil-rubbed bronze <sup>2</sup>		

#### Notes

- 1 LC6 housing ordered on a separate line.
- 2 Available in 30K 83CRI only.
- 3 Total system delivered lumens.

## E Series Baffle Wide Flange LED Modules (Wet Location)



Example: 65BEMW LED 27K  
LC6<sup>1</sup>

### ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

6BEMW		LED			
Series/Finish		Lamp	CCT / CRI / W / Lumens <sup>2</sup>		Voltage
<b>65BEMW</b>	5" / 6" Baffle LED module, matte white	LED	<b>27K</b>	2700 K / 82CRI / 11.9W / 640L	(blank) 120V
			<b>30K</b>	3000 K / 82CRI / 11.9W / 687L	
			<b>40K</b>	4000K / 82CRI / 11.9W / 711L	
			<b>27K 90CRI</b>	2700K / 93CRI / 10.3W / 650L	
			<b>30K 90CRI</b>	3000K / 93CRI / 10.1W / 690L	

#### Notes

- 1 LC6 housing ordered on a separate line.
- 2 Total system delivered lumens.