WTSF 120

Product no.: T0051390799



Benefits

- Efficient, single-handed soldering
- Nonstick coating inside solder feed tube (no flux adhesion; save on maintenance costs)
- Integrated start / stop / standby functions conserves energy and extends the service life of the unit
- Amount of solder can be pre-set for efficient use. Feed motion is adjustable from 1 mm/s to 27.5 mm/s (0.04 in./s to 1.08 in./s)
- Timer mode: a defined amount of solder is applied time the finger switch is pressed (LED on)
- Pulse mode: the solder wire is continuously delivered as long as the switch is pressed (LED off)
- Compatible with Weller WD1M, WR2, WR3M and WT soldering and rework base stations (sold separately)
- Compatible with 0.5mm, 0.8mm, and 1.0 mm solder wire diameters
- Consists of WTSF120 solder feeder unit, XTB (2.4 mm) soldering tip, 120W soldering iron with integrated solder feeder

For this purpose, we recommend:



Solder fume extractors


Pre-heating plates



Cleaning


Soldering tips

Technical Data

Active Tip heating element technology	---
Power Response heating element technology	on
Silver Line heating element technology	---
Voltage	24 V AC
Power	120 W (126 W)
Tip range	XT
Supply unit	WD 1M, WSD 121, WR 2, WR 3M
WX-compatible	---
Temperature range °C	100 - 450
Temperature range °F	200 - 850
Heating time	14
Safety rest	---
Safety rest (optional)	---
Barrel	T0058763731
Integrated direct extraction	---

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE

Weller Tools GmbH
Carl-Benz-Straße 2
74354 Besigheim
Germany

Phone: +49 (0) 7143 / 580-0
Fax.: +49 (0) 7143 / 580-108
Email: info@weller-tools.com
Web: www.weller-tools.com