



| | |
|------------------|--|
| Job Name: | |
| Job Location: | |
| Engineer: | |
| Contractor: | |
| Tag: | |
| PO#: | |
| Rep.: | |
| Wholesale Dist.: | |

DESCRIPTION

ASME Section IV Capacity Certified Bronze Safety Relief Valves protect ASME Section IV hot water heating boilers and hydronic heating systems. High capacity design features corrosion resistant construction. Brass, satin or polished chrome finishes available. **Proudly made in the USA.**

FEATURES

- ASME Section IV Certified Capacity (20-60psi only)
- 15-60 psig (1.4 - 4.1 bar) Set Pressure at 250°F (121°C) max
- Corrosion Resistant Construction
- Registered in all Canadian Provinces and Territories, CRN #OG8547.5C
- Stainless Steel Springs Standard
- Male or Female NPT inlet
- Optional Satin or Polished Chrome Finish
- **Made in the USA**

APPROVALS

- ASME Section IV Heating Boilers
- Canadian Registration Number OG8547.5C

OPTIONS

CONNECTION

- Male NPT Inlet
- Female NPT Inlet

FINISH

- Brass Finish
- Polished Chrome Finish
- Satin Chrome Finish

SEAT

- EPDM
- Silicone

SET PRESSURE

- 15-60, psig

STANDARD MATERIALS LIST

| | |
|---------------|------------------|
| BODY | ASTM B584 Bronze |
| NOZZLE | ASTM B584 Bronze |
| SPRING | Stainless Steel |
| SEAT | EPDM |

CAPACITY

| SET PRESSURE PSIG (BAR) | 10-300 (1" OUTLET) BTU/HR |
|-------------------------|---------------------------|
| 20 (1.38) | 420,000 |
| 25 (1.72) | 485,000 |
| 30 (2.07) | 550,000 |
| 35 (2.41) | 610,000 |
| 40 (2.76) | 675,000 |
| 45 (3.10) | 740,000 |
| 50 (3.45) | 805,000 |
| 55 (3.79) | 870,000 |
| 60 (4.14) | 935,000 |

DIMENSIONS

| MODEL NUMBER | ITEM NUMBER | SIZE | A | B | C |
|--------------|-------------|-------------|-----------|-----------|-----------|
| RVW30F | 10301 | 3/4M x 3/4F | 1.85 (47) | 3.82 (97) | 1.42 (36) |
| RVW30 | 10303 | 3/4F x 3/4F | 1.44 (37) | 3.41 (87) | 1.42 (36) |

