

77G-UL SERIES

Bronze Full Port Fuel Shut Off Valve - UL/CSA Listed

Job Name:	Contractor:		
Job Location:	P.O. Number:		
Engineer:	Representative:		
Tag:	Wholesale Distributor:		

DESCRIPTION

The Apollo® 77G-UL series ball valve is a UL and CSA listed fuel shut off valve approved for a variety of flammable gases and liquids. Cast and machined in Apollo's South Carolina manufacturing plants, these valves feature a durable bronze body, premium "multi-fill" MPTFE seats and stem packing, and a "Solid Ball" design that delivers true full port flow performance.

FEATURES

- Multi-Fill PTFE Seats & Seals
- Blow-out Proof Stem Design
- Adjustable Stem Packing
- CSA to ASME B16.33, 125
- CGA 3.16-M88, 125
- UL LISTED

MHKZ Manual valves YSDT LP gas shutoff, 250 YQNZ Compressed gas shutoff YRBX Flammable liquid shutoff YRPV Gas shut off

CUL LISTED

YRPV7 Gas shutoff YRBX7 Flammable Liquid shutoff MHKZ7 Manual valves YSDT7 LP gas shutoff

PERFORMANCE RATING

- Maximum Body Pressure: 600 psig CWP
- Pressure CSA: Up To 125 psig
- Temperature Range CSA: -20°F to 150°F
- Pressure UL: 250 psig max @ 125°F
- Service: A (Air or non-toxic, non flammable gas),
 G (City gas supplied by public utilities),
 Ga (Gasoline),
 LP (Liquefied petroleum gases),
 (No. 1 & 2 fuel oil),
 (No. 4 fuel oil),
 (No. 5 fuel oil),
 (Steam 150 psig)

STANDARD MATERIAL

Part Name	Material				
Body	Cast Bronze B584				
Seat	Multi-Fill PTFE				
Ball	ASTM B16 Brass				
Stem Packing	Multi-Fill PTFE				
Nut	Corrosion Resistant Plated Steel				
Stem	ASTM B16 Brass				
Retainer	ASTM B505 Bronze (1/2")				
	Cast Bronze B584 (3/4" - 1")				
Handle	Plated Steel/Insulated Polyvinyl				
Gland	ASTM B16 Brass				

APPROVALS

- MSS SP-110 Ball Valves
- UL (Canada & US)
- CSA







DIMENSIONS

PART#	SIZE	Α	В	С	D	Е	Wt.
77G103UL	1/2"	0.50	1.19	2.35	1.80	3.74	0.68
77G104UL	3/4"	0.75	1.42	2.74	1.98	4.78	1.26
77G105UL	1"	1.00	1.64	3.18	2.18	4.78	2.08

