



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

### DESCRIPTION

The **Apollo® Model 116T (30 Series) Gate Valve** with solid wedge disc and Stainless Steel seats provides a cost effective "made in the USA" alternative to globally sourced multi-turn valves. These heavy duty valves are cast, machined, assembled, and tested in South Carolina. The Apollo Gate Valve is ideal for steam and liquid service and can reliably be installed in most plumbing and heating systems including building service piping and OEM applications.

### FEATURES

- Guided Solid Bronze Disc Wedge
- Stainless Steel Body Seats
- Adjustable Graphite Stem Packing
- Union Bonnet
- Rising Stem
- NPT Connections
- Dezincification Resistant Bronze Construction
- Rugged Malleable Iron Hand Wheel
- 100% Factory Tested to MSS SP-80
- **100% Cast, Machined and Assembled in the USA**
- **ARRA Compliant**

### PERFORMANCE RATING

- Saturated Steam: 300 psi (20.7 Bar)
- Cold Working Pressure: 1000 psi @100°F (68.9 Bar @ 38°C)
- Temperature Range\*: -20°F to 422°F (-29°C to 216°C)

*\*Valves should be in open position to allow complete drainage during freezing conditions.*

### APPROVALS

- MSS SP-80 - Bronze Gate, Globe, Angle & Check Valves - Type 2
- ASME B1.20.1 - Pipe Threads, General Purpose (Inch)
- CRN OC14667.5

### STANDARD MATERIALS LIST

<b>BODY</b>	Bronze, ASTM B61
<b>BONNET</b>	Bronze, ASTM B61
<b>STEM</b>	ASTM B21 UNS C46400
<b>UNION NUT</b>	Bronze, ASTM B61
<b>DISC WEDGE</b>	Bronze, ASTM B61
<b>SEATS</b>	316 SS
<b>PACKING</b>	Grafoil® (Asbestos Free)
<b>PACKING NUT</b>	Brass, ASTM B16
<b>HAND WHEEL</b>	Malleable Iron
<b>NAMEPLATE</b>	Aluminum

### DIMENSIONS

MODEL NO.	PART NO.	SIZE (IN.)	HEIGHT OPEN (IN.)	LENGTH (IN.)	WEIGHT (LB.)	CV (GPM)
116T12	30-453-01	1/2"	4.97	2.31	1.4	12.5
116T34	30-454-01	3/4"	6.22	2.56	2.3	24.0
116T1	30-455-01	1"	6.94	2.89	3.5	72.3
116T114	30-456-01	1-1/4"	8.29	3.01	5.1	80
116T112	30-457-01	1-1/2"	9.28	3.05	6.8	119
116T2	30-458-01	2"	11.37	3.08	9.6	338