

120T LF

Class 125, PTFE Seat, NPT Globe Valve

LEAD FREE

SUBMITTAL SHEET

"Apollo" Flow Controls



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

DESCRIPTION

The lead free* Apollo® Model 120T-LF (33 Series) Globe Valve provides a reliable, long lasting "Made in the USA" alternative to globally sourced multi-turn valves for potable water service. These valves are cast, machined, assembled, and tested in South Carolina using proven ASTM quality materials.

FEATURES

- Lead Free* ABI953 Certified
- Optimum Flow Capacity
- Adjustable Graphite Stem Packing
- 100% Factory tested per MSS
- NPT Connection
- Screw-in Bonnet
- Malleable Iron Rugged Hand Wheel
- Back seat protection
- **100% Cast, Machined and Assembled in the USA**
- **ARRA Compliant**

PERFORMANCE RATING

- Saturated Steam: 125 psi (8.6 Bar) to 353°F(178°C)
- Cold Working Pressure: 200 psi (13.8 Bar) at 100°F
- Temperature Range: -20°F to 406°F

APPROVALS

- MSS SP-80 Design & Testing
- MSS SP-139, "Copper Alloy Gate, Globe, & Check Valves"
- ASME B1.20.1, "Pipe Threads, General Purpose (Inch)"
- Canadian Registration Number OC14667.5
- NSF/ANSI 61-8 2010 Annex F & G
- NSF 372 Lead Free

STANDARD MATERIALS LIST

Body	ASTM B584 C89836 Bronze
Bonnet	ASTM B584 C89836 Bronze
Stem	ASTM B21 UNS C46400
Disc	PTFE
Packing	Grafoil®
Hand Wheel	Malleable Iron
Nameplate	Aluminum

DIMENSIONS

MODEL NO.	PART NO.	SIZE (IN.)	HEIGHT OPEN (IN.)	LENGTH (IN.)	WEIGHT (LB.)	CV** (GPM)
120T38LF	33LF132-01	3/8"	3.37	2.39	1.0	2.6
120T12LF	33LF133-01	1/2"	3.47	2.70	1.1	4.4
120T34LF	33LF134-01	3/4"	4.75	3.20	1.9	7.4
120T1LF	33LF135-01	1"	5.40	3.75	3.0	12.1
120T114LF	33LF136-01	1-1/4"	7.78	4.74	7.3	29.0
120T112LF	33LF137-01	1-1/2"	7.78	4.74	7.0	30.0
120T2LF	33LF138-01	2"	8.43	5.72	10.7	49.0

**Cv = flowrate at 1.0 psid

*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

Customer Service (704) 841-6000
www.apolloflowcontrols.com

This specification is provided for reference only. Conbraco Industries Inc. reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. Please visit apolloflowcontrols.com for the most current information.

