Oil-Only 65-Gallon Hi-Viz OverPack Drum Spill Kit #SPKO-65-HV - Absorbs up to 43.8 Gallons



Be prepared for fast response with a high-visibility SpillTech® Oil-Only Spill Kit!

- Packed with a variety of quality SpillTech® Oil-Only sorbents to handle spills of oil and other petroleum-based fluids — while repelling water
- Lightweight, polypropylene drum resists chemicals and keeps contents clean and dry
- Bright green drum stands out, even in low light conditions
- Nonthreaded lid lifts off for easy access (not rated as a shipping container)

Online: **spilltech.com**

Phone: **1-800-228-3877 (N.Am.)** **1-770-475-3877 (Other)**

Fax: **1-800-872-3764 (N.Am.)** **1-770-410-1812 (Other)**

Email: **sales@spilltech.com**

6455 East Johns Crossing, Suite 375 • Johns Creek GA 30097

© 2020 SpillTech Environmental Corporation. All rights reserved.

SPKO-65-HV Specifications

Dimensions:	ext. dia. 28.25" x 37.37" H
Shipping Dimensions:	28.25" W x 37.37" L x 28.25" H
Sold as:	1 per package
Absorbency:	Up to 43.8 gal. per package
Weight:	62.04 lbs.
# per Pallet:	2
Incinerable:	No
Ship Class:	175
Includes:	40 - 15" x 19" White Oil-Only HeavyWeight SonicBonded Pads (WPB100H) 10 - 3" x 4' White Oil-Only Sorbent Socks (WSO430) 6 - 3" x 8' White Oil-Only Sorbent Socks (WSO815) 6 - 18" x 18" White Oil-Only Sorbent Pillows (WPIL1818) 2 - Pair Nitrile Gloves (A-GLV-NIT) 3 - 30" x 6" x 60" Yellow Disposal Bags & Ties (A-DISPBAG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KITLABEL) 1 - Safey Goggles (A-GOG) 6 - 6" x 2" TamperProof Seals (A-SEAL) 1 - 28.25" x 37.37" Hi-Viz 65-Gallon Overpack (A65OVER-HV)

Metric Equivalent Specifications

Dimensions:	ext. dia. 71.8cm x 94.9cm H
Shipping Dimensions:	71.8cm W x 94.9cm L x 71.8cm H
Absorbency:	Up to 165.8 L per package
Weight:	28.1 kg

© 2020 SpillTech Environmental Corporation. All rights reserved.

SPKO-65-HV Technical Information

Warnings & Restrictions:
There are no known warnings and restrictions for this product.

Regulations and Compliance:
40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation…so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

Technical Documents:
(Available at **spilltech.com**)

Product Data Sheet (PDS)

© 2020 SpillTech Environmental Corporation. All rights reserved.