


FREC & FRTC SERIES FLEXIBLE END CAP (WITH HOSE BIBB)

SPECIFICATION:

- Reusable
- Designed to fit schedule 40 nominal pipe sizes
- Drain, waste and vent (DWV) piping applications
- Convex face allows cap to withstand greater pressure for testing and minimize ballooning
- Flexible PVC Conforms to ASTM C564
- Max Test Pressure: 4.3 PSI (29.6KPA)
- Max Operating Temperature: 140°F (60°C)
- Min Operating Temperature: -30°F (-34°C)
- Includes one marine grade 300 Stainless Steel clamp

CERTIFICATION:

- UPC Certified to PS90-2006 & CSA B602 Standards by IAPMO
- Clamps UPC certified to ANSI / SAE J-1670 by IAPMO



DIMENSIONS								
Part No.	Connection Sizes	A		B		C		Weight
		inches	mm	inches	mm	inches	mm	grams
End Cap								
FREC-15 †	1-1/2" C.I. / PL	1.90	48	1.18	30	-	-	60
FREC-20 †	2" C.I. / PL	2.38	60	1.26	32	-	-	90
FREC-30 †	3" C.I. / PL	3.50	89	4.48	114	-	-	150
FREC-40 †	4" C.I. / PL	4.50	114	1.65	42	-	-	220
FREC-60	6" C.I. / PL	6.56	166	2.10	53	-	-	525
End Cap with Hose Bibb								
FRTC-15	1-1/2" C.I. / PL	1.90	48	1.18	30	3.65	93	60
FRTC-20	2" C.I. / PL	2.38	60	1.26	32	3.73	95	90
FRTC-30	3" C.I. / PL	3.50	89	1.40	36	3.87	98	150
FRTC-40	4" C.I. / PL	4.50	114	1.65	42	4.12	105	220

† Manufactured onsite at Boshart Industries

BOSHART
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 800-561-3164

boshart.com ♦ **blog.boshart.com**