OPTIONS

Flow Rate

- ☐ 0.5 gpm (2 Lpm) (0.5GPM)
- ☐ 0.35 gpm (1 Lpm) (0.35GPM)

Mixer

- ☐ Back-Check Tee (TEE)
- ☐ Below Deck Manual Mixing Valve (BDM)

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet.
Find a compatible sink for this faucet.



Image for a standard SF-2100 shown

DESCRIPTION

Sloan® Hardwired-Powered Deck-Mounted Low Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Pedestal Hand Washing Faucet with the following features:

- Adjustable Infrared Sensor Range
- 36” (914 mm) Long Sensor Cable
- 24” (610 mm) Long Flex Hose
- Filtered Solenoid Valve with serviceable Strainer Filter
- Includes Four (4) AA-size Batteries
- Includes appropriate Mounting Hardware
- 1 Year limited warranty

DOWNLOADS

- SF Series Installation Instructions
- SF Series (FR) Installation Instructions
- SF Series (SP) Installation Instructions
- SFP 35-A Installation Instructions
- SF 2100/2150 Faucet Extension Installation Instructions
- Trim Plates Repair and Maintenance Guide
- Sloan 2100/2150 Repair and Maintenance Guide
- Additional Downloads

Sloan 10500 Seymour Ave, Franklin Park, IL 60131
Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com