


ROUGHING IN DIMENSIONS MAY VARY AND ARE SUBJECT TO CHANGE. NO RESPONSIBILITY IS ASSUMED FOR USE OF SUPERCEDED OR VOIDED DATA.

| | | | | | | | |
|--|--|--|--|--|--|------------------------------------|--|
| CHICAGO FAUCETS a Geberit company | | 2100 South Clearwater Drive Des Plaines, IL 60018 Phone: 847-803-5000 Fax: 847-803-5454 www.chicagofaucets.com | | ROUGH-IN | | FITTING NO. 201-202078AB | |
| FOR TECHNICAL ASSISTANCE 1-800-TEC-TRUE (1-800-832-8783) | | BY: SID | | DATE: 07-30-13 | | SUBMITTED MODEL NO. | |
| | | CHK: <i>[Signature]</i> | | REV: | | | |
| SUBMITTED AS SHOWN | | SUBMITTED AS NOTED | | SEE ATTACHED FOR SUBMITTED MODIFICATION | | | |
| JOB NAME | | | | ITEM NO. | | | |
| <p>4 [102]</p> <p>8 [203]</p> <p>2-1/4 [57]</p> <p>1-1/4 [32]</p> <p>1-1/8 [29]</p> <p>4 [102]</p> <p>8 [203]</p> <p>4-5/8 [117]</p> <p>6-1/4 [159]</p> <p>1-3/8 [35] MAXIMUM WARE THICKNESS</p> <p>1/2 NPSM COUPLING NUT FOR 3/8 OR 1/2 FLEXIBLE RISER</p> | | | | | | | |
| DIMENSIONS ARE IN INCHES AND [MILLIMETERS]. | | | | | | | |
| TECHNICAL DATA | | | | | | | |
| <ul style="list-style-type: none">- DECK MOUNTED SINK FITTING- L8 CAST SWING SPOUT- 317 INDEXED WRISTBLADE HANDLES- QUATURN OPERATING CARTRIDGES- E36VP VANDAL RESISTANT PCA LAMINAR FLOW OUTLET- 1.5 GPM [5.7 L/min.] MAXIMUM FLOW RATE- FINISH: CHROME PLATE | | | | <ul style="list-style-type: none">- ASME A112.18.1/CSA B125.1 COMPLIANT- COMPLIANT TO NSF/ANSI 61, SECTION 9- MEETS THE LEAD CONTENT REQUIREMENTS OF: CALIFORNIA, VERMONT AND NSF/ANSI 372- ADA ANSI/CC A117.1 COMPLIANT- CALGREEN | | | |
| | | | |  ADA COMPLIANT | | | |