

PRODUCT DATA SHEET

Chute Lube™ Lubricant, 11 Wt Oz No. 03204 | Item# 1003459 | Case# 1003458

Product Description An NSF registered H2, silicone lubricant for package handling applications. It eliminates the binding and

sticking of packages and boxes, while protecting most

surfaces.

Applications Recommended to lubricate package handling equipment,

such as chutes, slides, guides, and rails.

Unit Package Description 20 Ounce Aerosol

CRC Brand

Generic Description 1 Silicone Lubricant

Net Fill 11 Wt Oz

UPC Code 078254032047

Unit Dimensions 9.25H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 9.7H x 8.3W x 11.1D in

Cases Per Pallet 114 Case Weight 12 lbs

30078254032048 I 2 of 5 Code

Appearance Clear Light Yellow Liquid

Base Type Silicone <0°F Flash point (F) Flash point (C) <-18°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate

Plastic Safe May Harm Sensitive Plastics

Film Type Silicone

Fast **Evaporation Rate**

Dielectric Strength Not Determined Working Temp (F) -15 to 400°F -25 to 204°C Working Temp (C)

Last revised: 12/28/2017

Page 1 of 2



Chute Lube[®]

Lubricante de Silicona

Reduces Friction Relos Packages Slide Easier

Wide Temperature Range Reduce la Fricción

Amplio Rango de Temperaturas

Silicone Lubricant

kyuda a los Paquetes más Fácil Deslizarse

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

of CRC Industries, Inc.



PRODUCT DATA SHEET

Propellant

Hydrocarbon

NSF Category Code

H2

NSF Number

138031

Aerosol Flammability Level

Ш

DOT Proper Shipping Name

Aerosols, Flammable, Limited Quantity

VOC % (Consumer Product

94.97

def)

VOC g/L (Consumer

646

Product def)

VOC lbs/gal (Consumer Prod def)

5.4

VOC Category

Not Regulated (Single Purpose Lubricant)

Removal (How To)

Remove with Petroleum Distillates.

Reduces Friction Relps Packages Slide Easier Wide Temperature Range Reduce la Fricción kyuda a los Paquetes más Fácil Deslizarse Amplio Rango de Temperaturas

Chute Lube°

Lubricante de Silicona

Silicone Lubricant

Last revised: 12/28/2017

Page 2 of 2

