SAFETY DATA SHEET

1. Identification

Product identifier Trewax® Boat Paste Wax

Other means of identification

MK66 Product code

Recommended use Boat paste wax Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries, Inc. Company name

885 Louis Dr. **Address**

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

Customer Service 800-272-4620 24-Hour Emergency 800-424-9300 (US)

703-527-3887 (International) (CHEMTREC) Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable solids Category 1 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B

> Specific target organ toxicity, single exposure Category 3 narcotic effects

Hazardous to the aquatic environment, acute **Environmental hazards**

hazard

Hazardous to the aquatic environment,

long-term hazard

Not classified.

Label elements

OSHA defined hazards



Signal word Danger

Hazard statement Flammable solid. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness.

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use explosion-proof

equipment. Avoid breathing vapors. Wash thoroughly after handling. Wear protective gloves/eye

Category 3

Category 3

protection/face protection. Avoid release to the environment.

Response If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off

> contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Use appropriate

media to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Material name: Trewax® Boat Paste Wax MK66 Version #: 01 Issue date: 06-23-2015

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), hydrotreated heavy		64742-48-9	50 - 60
Distillates (petroleum), hydrotreated light		64742-47-8	20 - 30

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Drink plenty of water. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Diarrhea. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.
General fire hazards	Flammable solid.

6. Accidental release measures

Personal	precautions,
protectiv	e equipment and
emergen	cy procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

100 ppm

8. Exposure controls/personal protection

Occu	national	exposure	limite
Occu	pationai	exposure	11111111

oupanonai oxpoodio illino	
US. OSHA Table Z-1 Limits for	or Air Contaminants (29 CFR 1910.1000)
Components	Type

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m3		
ŕ		100 ppm		
US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Туре	Value		
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3		
Naphtha (petroleum), hydrotreated heavy (CAS	TWA	400 mg/m3		

Biological limit values

64742-48-9)

No biological exposure limits noted for the ingredient(s).

Exposure guidelines Appropriate engineering

controls

Occupational Exposure Limits are not relevant to the current physical form of the product.

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency

shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Wear protective gloves such as: Nitrile. Latex. Hand protection Wear appropriate chemical resistant clothing. Other

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. **Physical state** Paste. **Form** Tan. Cream. Color

Material name: Trewax® Boat Paste Wax MK66 Version #: 01 Issue date: 06-23-2015 Odor Solvent.

Odor threshold Not available.
pH Not available.

Melting point/freezing point 130 - 172 °F (54.4 - 77.8 °C)

Initial boiling point and boiling

range

Not available.

Flash point 150 °F (65.6 °C) Tag Closed Cup

Evaporation rate Not available. Flammability (solid, gas) Flammable solid.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

0.5 % estimated

Flammability limit - upper

(%)

5.5 % estimated

Vapor pressure0.1 hPa estimatedVapor densityNot available.

Relative density 0.75
Solubility (water) Insoluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 410 °F (210 °C) estimated

Decomposition temperatureNot available.Viscosity (kinematic)Not available.Percent volatileNot available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Strong acids. Strong oxidizing agents. Strong alkalies.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation.

Eye contact Causes eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. May cause drowsiness and dizziness. Nausea, vomiting. Diarrhea. Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes. Exposed individuals may experience

eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Product Species Test Results

Trewax® Boat Paste Wax

<u>Acute</u> Dermal

LD50 Rabbit 3636 mg/kg estimated

Product Species		Test Results	
Inhalation			
LC50	Rat	18 mg/l, 4 hours estimated	
Oral			
LD50	Rat	6249 mg/kg, 2.5 hours estimated	

^{*} Estimates for product may be based on additional component data not shown.

Causes skin irritation. Skin corrosion/irritation Serious eye damage/eye Causes eve irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Not likely, due to the form of the product. **Aspiration hazard**

12. Ecological information

Harmful to aquatic life with long lasting effects.		
Species		Test Results
ax		
EC50	Daphnia	6.8182 mg/l, 48 hours estimated
LC50	Fish	16.3636 mg/l, 96 hours estimated
	Species	Test Results
	ex EC50	Species ax EC50 Daphnia LC50 Fish

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Aquatic Acute

LC50 Fish Fathead minnow (Pimephales promelas) 45 mg/l, 96 hours

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours Fish LC50 Rainbow trout, donaldson trout 8.8 mg/l, 96 hours (Oncorhynchus mykiss)

8.8 mg/l, 96 hours

Persistence and degradability Bioaccumulative potential

No data is available on the degradability of this product.

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

^{*} Estimates for product may be based on additional component data not shown.

Hazardous waste code Not regulated.

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN3175 **UN** number

Solids containing flammable liquid, n.o.s. (Petroleum distillates), Limited Quantity **UN proper shipping name**

Transport hazard class(es)

4.1 Class Subsidiary risk Label(s) 4.1 П **Packing group**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

47, IB6, IP2, T3, TP33 **Special provisions**

151 Packaging exceptions Packaging non bulk 212 Packaging bulk 240

IATA

UN3175 **UN** number

UN proper shipping name

Solids containing flammable liquid, n.o.s. (Petroleum distillates), Limited Quantity

Transport hazard class(es) Class

4.1 Subsidiary risk Packing group Ш **Environmental hazards** No. 3L **ERG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only

Allowed.

IMDG

UN3175 **UN** number

SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Petroleum distillates), LIMITED UN proper shipping name

QUANTITY

Transport hazard class(es)

4.1 Class Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No. F-A, S-I **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Material name: Trewax® Boat Paste Wax MK66 Version #: 01 Issue date: 06-23-2015

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - No
Fire Hazard - Yes

Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

No

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

US. Massachusetts RTK - Substance List

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

US. Rhode Island RTK

None

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2)
Ethylbenzene (CAS 100-41-4)
Naphthalene (CAS 91-20-3)
Listed: February 27, 1987
Listed: June 11, 2004
Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)

Toluene (CAS 108-88-3)

Listed: December 26, 1997

Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009 US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 65.4 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products Not regulated

MK66 Version #: 01 Issue date: 06-23-2015

65.4 % VOC content (CA) VOC content (OTC) 65.4 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

06-23-2015 Issue date Allison Cho Prepared by

Version # 01

Further information Not available. **HMIS®** ratings Health: 1 Flammability: 2

Physical hazard: 0 Personal protection: A

NFPA ratings Health: 1

Flammability: 2 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.

Material name: Trewax® Boat Paste Wax MK66 Version #: 01 Issue date: 06-23-2015

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).