



Lectra Clean® II Non-Chlorinated Heavy Duty Degreaser

I. Product Description

CRC Lectra Clean® II is a versatile, non-chlorinated, non-conductive, zero VOC and non-corrosive heavy duty degreaser intended for use on electric motors and other electrical equipment. **Lectra Clean® II** will remove heavy deposits of wax, dust, oil, tar, ink, grease and carbon dust from metal, plastic and nylon surfaces. Additionally, **Lectra Clean® II's** controlled evaporation enhances its strong cleaning action. It provides an excellent alternative to chlorinated solvents for cleaning applications where chlorinated solvents are not acceptable.

II. Applications

Recommended for use on electric motors, fusible disconnects, switchgears, transformers, circuits, insulators, relays, switches, air tools, generators, compressors, pumps, tools, dies, molds and a wide variety of other electrical and industrial equipment.

III. Features & Benefits

- **High Flash Point.** Reduces potential for fire.
- **Non-Chlorinated.** Lowers personal risk.
- **No Residue.** Reduces need for additional cleaning steps.
- **Low Odor and Zero VOC Formulation.** Promotes a better work environment and user comfort.
- **Contains No Class I or Class II ODCs.** Complies with EPA ozone depleting regulations.
- **M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	180°F PMCC		Boiling Point	>350° F
Odor	Slight hydrocarbon		Solubility	Slight in water
Appearance	Clear liquid		Specific Gravity	0.839
Vapor Density	>4 (air=1)		Propellant (Aerosol)	CO ₂
VOC Content (Fed)	<u>Aerosol</u> 0 g/L	<u>Bulk</u> 0 g/L	Vapor Pressure	<0.1 mmHg @68°F
Sara Title III, Sect. 313 Chemicals	No			
Prop 65	No			

V. Specifications and Approvals

- NSF K1 and K2 Registered for use in meat and poultry plants.

VI. Performance Characteristics

ASTM D-877 (Dielectric Strength)	42,100 volts
ASTM D-56 (Flash Point)	180°F
ASTM D-1130 (KB Value)	75

VII. Directions

- May be harmful to some plastics. Test on small area before using. Do not use on sensitive electronic equipment such as tape decks, VCRs, computers, etc. Use a CRC precision cleaner instead.
- To remove grease, oil, hydraulic fluids and related contaminants, spray until clean. For hard to reach areas, use the extension tube. For heavier soils, apply product and allow to penetrate for several minutes. Re-apply and soil should flush off.
- Air dry or dry with a clean, absorbent cloth.
- If necessary, repeat application.
- Allow to dry thoroughly and vent before reactivating system.
- **For personal safety, do not use on energized equipment.**

VIII. Package Description

Part Number	Container Size
02120	20 oz Aerosol
02121	1 Gallon Bottle
02122	5 Gallon Pail
02124	55 Gallon Drum

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.