

PRODUCT DATA SHEET

Honing & Cutting Oil, 1 Gal

No. SL2523 | Item# 1007833 | Case# 1007832

Product Description

An all-purpose metal working/ cutting lubricant that extends tool life and improves machined surface finish.

Applications Valve refacing, piston pin fitting, honing, tapping,

reaming, grinding, threading, boring, broaching, drilling

and milling

Unit Package Description 1 Gallon Bottle

Brand Sta-Lube

Generic Description 1 Honing & Cutting Oil

Net Fill 1 Gal

UPC Code 072213252309

Unit Dimensions 10.63H x 4.75W x 6D in

Units Per Case 4

Case Dimensions 11.25H x 11.25W x 13.5D in

Cases Per Pallet 60
Case Weight 33 lbs

1 2 of 5 Code 30072213252300

Appearance Red Liquid

Flash point (F) 378°F Flash point (C) 192°C

Flammability Class - CPSC None Spec Gravity Concentrate 0.89

Plastic Safe Yes

Evaporation Rate Slow ISO Viscosity Grade 32

SAE Grade 15W

Working Temp (F) 50 to 150°F

Working Temp (C) 10 to 65.6°C

DOT Proper Shipping Name Not Regulated

Last revised: 3/27/2018

Page 1 of 2




of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair



PRODUCT DATA SHEET



VOC g/L (Consumer 26 Product def)

VOC lbs/gal (Consumer Prod def)

VOC Category Cutting or Tapping Oil (Non-Aerosol)

0.2

Restricted from Sale In: SCAQMD



Last revised: 3/27/2018

Page 2 of 2



of CRC Industries, Inc.