


PRODUCT DATA SHEET





A sodium-based short fiber grease for autos & trucks with drum brake systems and slow speed industrial bearings. Meets most demands for economical wheel bearing

lubrication. Good adhesive characteristics.

Applications

Drum brake systems, for use where heavy loads & slow

speeds are present

Unit Package Description

14 Ounce Can

Brand

Sta-Lube

Generic Description 1

HD Drum Brake Wheel Bearing Grease

Net Fill

14 Wt Oz

UPC Code

072213313109

Unit Dimensions

3.44H x 4.13W x 4.13D in

Units Per Case

12

Case Dimensions

3.5H x 12.5W x 17D in

Cases Per Pallet

108 13 lbs

Case Weight
I 2 of 5 Code

30072213313100

Appearance

Dark Amber Semi-Solid to Solid Grease

Base Type

Sodium

Flash point (F)

428°F

Flash point (C)

220°C

None

Flammability Class - CPSC Spec Gravity Concentrate

0.9 at 60°F

2.5

NLGI Grade Plastic Safe

Not Determined

Evaporation Rate

<0.01 (Butyl Acetate=1)

Working Temp (F)

10 to 250°F

Working Temp (C)

-12.2 to121.1°C

Drop Point

360°F

Last revised: 11/30/2017

Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com





PRODUCT DATA SHEET



Leakage Not Determined

Oil Separation <10
Oxidation Stability 5 Lbs
Pour Point (F) 10.4°F

Pour Point (C) -17.78°C

ISO Viscosity Grade 190

Water Washout Not Determined

Worked Penetration 235 to 265

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.

Last revised: 11/30/2017

Page 2 of 2

