



PRODUCT DATA SHEET

Lithium General Purpose Grease, 35 Lbs
No. SL3315 | Item# 1007907



Product Description

A high purity, NLGI Grade 2 lithium based grease. Provides superior lubrication & durability in any weather and most temperatures. It is a versatile grease designed for light duty applications requiring a long grease life. Will not break down or run out.

Applications

Hinges, latches, overhead door tracks, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment. A break-in lubrication for bearings.

Unit Package Description

35 Pound Pail

Brand

Sta-Lube

Generic Description 1

Lithium General Purpose Grease

Net Fill

35 Lb

UPC Code

072213331509

Unit Dimensions

13.8H x 11.3W x 11.3D in

Units Per Case

1

Case Dimensions

13.8H x 11.3W x 11.3D in

Cases Per Pallet

36

Case Weight

40 lbs

Appearance

Amber Semi-Solid to Solid Grease

Base Type

Lithium-12

Flash point (F)

302°F

Flash point (C)

150°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.9 at 60°F

NLGI Grade

2

Timken OK Load Lbs.

Not Determined

Plastic Safe

Not Determined

Evaporation Rate

Slow

Working Temp (F)

0 to 250°F

Last revised: 11/30/2017
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (C)	-18 to 121°C
4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	350°F
Elastomer Compatibility	Not Determined
Leakage	Not Determined
Low Temp Torque	Not Determined
Oil Separation	<10%
Oxidation Stability	5
Pour Point (F)	-15°F
Pour Point (C)	-26°C
ISO Viscosity Grade	150
Water Washout	<15%
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	Not Determined
VOC g/L (Consumer Product def)	Not Determined
VOC lbs/gal (Consumer Prod def)	Not Determined
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 11/30/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.