

## PRODUCT DATA SHEET

2-26® Multi-Purpose Precision Lubricant, 55 Gal No. 02011 | Item# 1003170

**Product Description** 

Plastic safe lubricant, penetrant and corrosion inhibitor that helps prevent electrical malfunctions caused by water penetration, humidity, condensation or corrosion. Restores resistance values and helps stop current leakage.

**Applications** 

Connectors, relays, circuit breakers, transformers, switchgear, motors, generators, controls, instruments, communication assemblies, electronics, alarm systems, starters, tubing, castings, gears, weld rod, wire, fixtures,

Multi-Purpose Precision Lubricant Plastic Safe

dies, jigs, shim stock, chucks.

Unit Package Description

Generic Description 1

CRC

55 Gallon Drum

Brand

Net Fill 55 Gal

**UPC** Code 078254020112

**Unit Dimensions** 35H x 24.5W x 24.5D in

Units Per Case 1

Case Dimensions 35H x 24.5W x 24.5D in

Cases Per Pallet

Case Weight 430 lbs

**Appearance** Amber Liquid

Petroleum Distillate Base Type

Flash point (F) 200°F

Flash point (C) 93°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.82 Plastic Safe Yes

Film Type Thin, Non-Drying Film Thickness 0.025 to 0.075 Mils

**Evaporation Rate** Slow

Dielectric Strength 51,300 Volts

Last revised: 11/28/2017

Page 1 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair

of CRC Industries, Inc.



## **PRODUCT DATA SHEET**



Working Temp (F) Max 250°F Working Temp (C) Max 121.1°C

Propellant None
NSF Category Code H2

NSF Number 017223

Military Specification Not Determined

Number

Federal Specification V-V-P-216

Number

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Multi-Purpose Lubricant

Removal (How To) Remove with Petroleum Distillates.

0

0

Last revised: 11/28/2017

Page 2 of 2



of CRC Industries, Inc.