

## **PRODUCT DATA SHEET**

Copper Coat® Gasket Compound, 4 FI Oz No. 401504 | Item# 1006075 | Case# 1006074

**Product Description** 

High temperature, high quality gasket sealer. Prevents compression loss on paper, cork and premium gaskets. Dauber built into the lid for easy application and storage.

**Applications** 

Automatic transmissions, cover plates, diesel heads, high compression engines, hi-speed turbine superchargers,

hydraulic pumps

Unit Package Description

K&W

Brand

Generic Description 1 Gasket Compound

Net Fill

4 FI Oz

**UPC** Code

078372015045

**Unit Dimensions** 

2.75H x 2.5W x 2.5D in

4 ounce Brush Top Bottle

Units Per Case

12

Case Dimensions

3.7H x 6.8W x 8D in

Cases Per Pallet

280 5 lbs

Case Weight

10078372015042

I 2 of 5 Code

Viscous Copper Liquid

Appearance

30°F

Flash point (F)
Flash point (C)

-1.1°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

0.76

Plastic Safe

Yes

Evaporation Rate

Moderate

Dielectric Strength

Not Determined

Working Temp (F)

-80 to 400°F

Working Temp (C)

-62.2 to 204.4°C

Propellant

None

**DOT Proper Shipping Name** 

Flammable Liquids, N.O.S. (Heptane, Cyclohexane),

Limited Quantity (Marine Pollutant)

Last revised: 2/28/2018

Page 1 of 2




Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com





## **PRODUCT DATA SHEET**



def)

VOC g/L (Consumer Product def)

549

74.2

VOC lbs/gal (Consumer

4.57

Prod def)

**VOC Category** 

Not Regulated

Removal (How To)

Gasket remover



Last revised: 2/28/2018

Page 2 of 2

