


PRODUCT DATA SHEET



Product Description A sodium-based short fiber grease for autos & trucks with drum brake systems and slow speed industrial bearings.

Meets demands for most economical wheel bearing

lubrication. Good adhesive characteristics.

Applications Drum brake systems, for use where heavy loads & slow

speeds are present

Unit Package Description 7 Pound Pail

Brand Sta-Lube

Generic Description 1 HD Drum Brake Wheel Bearing Grease

Net Fill 7 Lb

UPC Code 072213313604

Unit Dimensions 7.75H x 7.5W x 7.5D in

Units Per Case 4

Case Dimensions 8H x 16.5W x 16.5D in

Cases Per Pallet 54
Case Weight 33 lbs

1 2 of 5 Code 30072213313605

Appearance Dark Amber Semi-Solid to Solid Grease

Base Type Sodium

Flash point (F) 428°F

Flash point (C) 220°C

Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 2.5

Plastic Safe Not Determined

Evaporation Rate <0.01 (Butyl Acetate=1)

Working Temp (F) 10 to 250°F

Working Temp (C) -12.2 to121.1°C

Drop Point 360°F

Last revised: 11/30/2017

Page 1 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

and adheres to the strictest guidelines for quality in all facets of research, development and production.



PRODUCT DATA SHEET



Leakage Not Determined

Oil Separation <10
Oxidation Stability 5 Lbs
Pour Point (F) 10.4°F
Pour Point (C) -17.78°C

ISO Viscosity Grade 190

Water Washout Not Determined Worked Penetration 235 to 265

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.

Last revised: 11/30/2017

Page 2 of 2

