



# PRODUCT DATA SHEET

Ultra Lite 3-36® Ultra Thin Non Staining Lubricant, 1 Gal  
No. 03161 | Item# 1003429 | Case# 1003428



## Product Description

Ultra-thin, non-staining lubricant that resists oil, dirt and dust build-up. Seals out moisture and prevents corrosion with protective film. Excellent for drying out electrical/electronic components.

## Applications

Locks, latches, hinges, gauges, taps, dies, fixtures, fans, precision metal processing equipment, metal plating, coin mechanisms, solid work surfaces, clips, springs, control buttons, switches, bushings, window slides and rollers.

## Unit Package Description

1 Gallon Bottle

## Brand

CRC

## Generic Description 1

Ultra Thin Non Staining Lubricant

## Net Fill

1 Gal

## UPC Code

078254031613

## Unit Dimensions

10.25H x 5W x 6.13D in

## Units Per Case

4

## Case Dimensions

11.1H x 10.6W x 13.1D in

## Cases Per Pallet

60

## Case Weight

31 lbs

## I 2 of 5 Code

30078254031614

## Appearance

Amber Liquid

## Base Type

Petroleum Solvent

## Flash point (F)

172°F

## Flash point (C)

78°C

## Flammability Class - CPSC

Combustible

## Spec Gravity Concentrate

0.8

## Plastic Safe

No

## Film Type

Ultra Thin and Dry

## Film Thickness

0.05 Mils

## Evaporation Rate

Slow

## Dielectric Strength

37,600 Volts

Last revised: 11/28/2017  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



Working Temp (F)	-40 to 300°F
Working Temp (C)	-40 to 148.9°C
Propellant	None
NSF Category Code	H2
NSF Number	136113
Military Specification Number	Meets requirements of Mil-PRF-16173E, Grade 3 (Corrosion test only)
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	45
VOC g/L (Consumer Product def)	361.5
VOC lbs/gal (Consumer Prod def)	3.0
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with petroleum solvents, Stoddard solvent or mineral spirits.

Last revised: 11/28/2017  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.