

PRODUCT DATA SHEET

Extreme Pressure Engine Assembly Lube, 10 Wt Oz No. SL3331 | Item# 1007912 | Case# 1007911

Product Description Engine Assembly lube is a lithium 12 hydroxy stearate

based grease which adheres to metal surfaces to prevent destructive metal to metal contact. Prevents friction,

galling and wear on all types of engines.

Applications The assembly of all mechanical parts. Lubricating areas of

rotation sliding contact, such as cylinders, crank shafts and cam shafts. Also recommended for coating internal

engine parts during assembly

Unit Package Description 10 Ounce Tube

Brand Sta-Lube

Generic Description 1 Anti-Seize Engine Assembly Lube

Net Fill 10 Wt Oz

UPC Code 072213333107 Unit Dimensions 10H x 3W x 2D in

Units Per Case 6

Case Dimensions 4.13H x 6.75W x 10.25D in

Cases Per Pallet 250
Case Weight 6 lbs

I 2 of 5 Code 30072213333108

Appearance Black Semi-Solid to Solid Grease

Base Type Lithium-12

Flash point (F) 450°F
Flash point (C) 232°C
Flammability Class - CPSC None
Spec Gravity Concentrate 0.90
Plastic Safe Yes

Evaporation Rate Slow ISO Viscosity Grade 230

NLGI Grade 0.5

Working Temp (F) 0 to 250°F

Last revised: 3/22/2018

Page 1 of 2



MOLY-GRAPHITE

Part No. SL3331

10 oz. (284g)





PRODUCT DATA SHEET

Working Temp (C)

-17.78 to 121°C

Propellant

None

DOT Proper Shipping Name

Not Regulated

VOC % (Consumer Product

< 0.1

def)

VOC g/L (Consumer

< 0.9

Product def)

VOC lbs/gal (Consumer

< 0.007

Prod def)

10.00

VOC Category

Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.



MOLY-GRAPHITE

Last revised: 3/22/2018

Page 2 of 2

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.

