



PRODUCT DATA SHEET

Ultra Lite 3-36® Ultra Thin Non Staining Lubricant, 5 Gal
No. 03162 | Item# 1003430



Product Description	Ultra-thin, non-staining lubricant that resists oil, dirt and dust build-up. Seals out moisture and prevents corrosion with protective film. Excellent for drying out electrical/electronic components.
Applications	Locks, latches, hinges, gauges, taps, dies, fixtures, fans, precision metal processing equipment, metal plating, coin mechanisms, solid work surfaces, clips, springs, control buttons, switches, bushings, window slides and rollers.
Unit Package Description	5 Gallon Pail
Brand	CRC
Generic Description 1	Ultra Thin Non Staining Lubricant
Net Fill	5 Gal
UPC Code	078254031620
Unit Dimensions	13.75H x 11.25W x 11.25D in
Units Per Case	1
Case Dimensions	13.8H x 11.3W x 11.3D in
Cases Per Pallet	24
Case Weight	35 lbs
Appearance	Amber Liquid
Base Type	Petroleum Solvent
Flash point (F)	172°F
Flash point (C)	78°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.8
Plastic Safe	No
Film Type	Ultra Thin and Dry
Film Thickness	0.05 Mil
Evaporation Rate	Slow
Dielectric Strength	37,600 Volts
Working Temp (F)	-40 to 300°F

Last revised: 11/28/2017
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (C)	-40 to 148.9°C
Propellant	None
NSF Category Code	H2
NSF Number	136113
Military Specification Number	Meets requirements of Mil-PRF-16173E, Grade 3 (Corrosion test only)
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	40.6
VOC g/L (Consumer Product def)	326.2
VOC lbs/gal (Consumer Prod def)	2.7
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with petroleum solvents, Stoddard solvent or mineral spirits.

Last revised: 11/28/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.