

## **PRODUCT DATA SHEET**



**Product Description** 

Thin, non-staining film protects indoors for up to 9 months. Use for protection of all metals and for parts subjected to high humidity conditions. Perfect as an anti-corrosion coating for shrink-wrapped parts and a moisture

displacer for finished parts.

**Applications** 

Machined surfaces, parts in process, power units, electrical boards, cutting tools, blades, welds, aluminum extrusions, h& tools, dies, molds, chains, guns, artillery &

packaged goods.

Unit Package Description

55 Gallon Drum

CRC

Brand

Generic Description 1 Corrosion Inhibitor (Light Duty)

Net Fill 55 Gal

UPC Code 078254032283

Unit Dimensions 35H x 24.5W x 24.5D in

Units Per Case 1

Case Dimensions 35H x 24.5W x 24.5D in

Cases Per Pallet 4

Case Weight 430 lbs

Appearance Amber Liquid

Flash point (F) 172°F Flash point (C) 78°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.8034

Film Type Ultra Thin and Dry
Coverage 3,000 Sq Ft per Gal

Plastic Safe No
Propellant None

Military Specification Meets requirements of Mil-PRF-16173E, Grade 3

(Corrosion test only)

NSF Category Code H2

Number

Last revised: 11/9/2017

Page 1 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

and adheres to the strictest guidelines for quality in all facets of research, development and production.



## **PRODUCT DATA SHEET**



**NSF Number** 132839

**DOT Proper Shipping Name** Not Regulated

VOC % (Consumer Product 45.1

def)

VOC g/L (Consumer

Product def)

VOC lbs/gal (Consumer

Prod def)

**VOC Category** 

Removal (How To)

360.8

3

Not Regulated - (Not for field application)

Remove with petroleum solvents, Stoddard solvent or

mineral spirits.

Last revised: 11/9/2017

Page 2 of 2

