



PRODUCT DATA SHEET

Brake Caliper Synthetic Grease, 12 Wt Oz

No. 05353 | Item# 1003789 | Case# 1003788



Product Description

A specially developed synthetic grease with a high-tech formula for use in disc & drum brake systems. High temperature grease is plastic & rubber safe. Use on metal to metal contact points and sliding surfaces. Resists moisture and will not washout.

Applications

Backing plates, brake pad contact points, caliper o-rings, calipers, disc brake pads, drum brake systems, grommets, parking brake areas of lubrication, pivot points, self adjusters

Unit Package Description

12 Ounce Tub With Brush

Brand

CRC

Generic Description 1

Brake Caliper Synthetic Grease

Net Fill

12 Wt Oz

UPC Code

078254053530

Unit Dimensions

4.25H x 4W x 4D in

Units Per Case

12

Case Dimensions

5H x 12.25W x 16D in

Cases Per Pallet

64

Case Weight

11 lbs

I 2 of 5 Code

30078254053531

Appearance

Black Semi-Solid Grease

Base Type

Synthetic base with Molybdenum Disulfide, PTFE and Graphite

Flash point (F)

450°F

Flash point (C)

232°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.89

NLGI Grade

2

Timken OK Load Lbs.

60 Lbs

Plastic Safe

Yes

Evaporation Rate

Slow

Last revised: 11/30/2017
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (F)	-30 to 600°F
Working Temp (C)	-45.5 to 232°C
4 Ball EP	Not Determined
4 Ball Wear	0.67 mm
Drop Point	None
Leakage	None
Oil Separation	Not Determined
Oxidation Stability	5
Pour Point (F)	-20°F
Pour Point (C)	-29°C
ISO Viscosity Grade	Not Determined
Water Washout	1.7
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0.58
VOC g/L (Consumer Product def)	5.62
VOC lbs/gal (Consumer Prod def)	0.04
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 11/30/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.