



PRODUCT DATA SHEET

Silaramic® Brake System Grease, 5 Wt Oz

No. 05361 | Item# 1003793 | Case# 1003792



Product Description

A synthetic, dry-film, ceramic lubricant formulated to reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects against uneven pad wear.

Applications

All brake systems and brake components, including calipers, bushings, holes, pins, inserts, anchors, bolts, calipers and boots

Unit Package Description

5 Ounce Tube

Brand

CRC

Generic Description 1

Brake System Grease

Net Fill

5 Wt Oz

UPC Code

078254053615

Unit Dimensions

6.25H x 2W x 2D in

Units Per Case

12

Case Dimensions

8H x 6.38W x 7.63D in

Cases Per Pallet

175

Case Weight

5 lbs

I 2 of 5 Code

30078254053616

Appearance

Off White Semi Solid Grease

Base Type

Polydimethylsiloxane

Flash point (F)

550°F

Flash point (C)

288°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

1.0

NLGI Grade

2

Timken OK Load Lbs.

Not Determined

Plastic Safe

Yes

Evaporation Rate

Very Slow

Dielectric Strength

Not Determined

Last revised: 11/30/2017

Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (F)	-50 to 3000°F
Working Temp (C)	-45.6 to 1648.89°C
4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	None
Elastomer Compatibility	Compatible
Leakage	0.2
Low Temp Torque	Not Determined
Oil Separation	0.2
Oxidation Stability	Not Determined
Pour Point (F)	Not Determined
Water Washout	0.25
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated
Removal (How To)	Remove with petroleum solvents.

Last revised: 11/30/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.