

## **PRODUCT DATA SHEET**

Marine Boat Trailer and 4x4 Wheel Bearing Grease, 35 Lbs No. SL3125 | Item# 1007859

Product Description

A blue tacky, aluminum complex grease using a highly refined base oil. It has been formulated with a polymer to provide adhesive, non-blend and water wash-out

characteristics. Will resist water under the most severe water conditions.

**Applications** 

Anti-friction bearings, blocks, boat trailer bearings, deck equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel

bearings, winches

35 Pound Pail

Unit Package Description

Brand St

Sta-Lube

Generic Description 1

Marine Grease for Boat Trailer

Net Fill 35 Lb

UPC Code 072213312508

Unit Dimensions 14.5H x 12W x 12D in

Units Per Case

Case Dimensions 14.5H x 12W x 12D in

Cases Per Pallet 36
Case Weight 41 lbs

Appearance Blue Semi-Solid to Solid Grease

Base Type Aluminum Complex

Flash point (F)  $>450^{\circ}F$ Flash point (C)  $>232.2^{\circ}C$ 

Flammability Class - CPSC None
Spec Gravity Concentrate 0.9

NLGI Grade 2

Plastic Safe Not Determined

Evaporation Rate Slow


Working Temp (F) 0 to 325°F

Working Temp (C) -17.8 to 162°C

Last revised: 2/28/2018

Page 1 of 2









## **PRODUCT DATA SHEET**



**Drop Point** 500°F Leakage 5 Oxidation Stability 5

Pour Point (F) Pour Point (C) -17.78°C

ISO Viscosity Grade Water Washout 5% at 175°F Worked Penetration 265 to 295

Propellant

**DOT Proper Shipping Name** Not Regulated

VOC % (Consumer Product 0

def)

VOC g/L (Consumer

Product def)

VOC lbs/gal (Consumer

Prod def)

**VOC Category** 

Removal (How To)

0°F

180 Cst at 40°C

None

0

0

Not Regulated

Remove with a degreaser or brake cleaner product.

Last revised: 2/28/2018

Page 2 of 2

